

WOOD guard® XL



EXTERIOR WOOD PRESERVATIVE AND FINISH

LASTS 3-5 YEARS • OIL-BASED WOOD PRESERVATIVE

- CONTROLS SURFACE MOLD, DECAY & MILDEW • MEETS ALL VOC STANDARDS
- EXCEPTIONAL WATER REPELLENCY • THE SUPERIOR DEEP PENETRATING TREATMENT
- CONTAINS SYNERGISTIC FUNGICIDES (U.S. PATENT NO. 5200421)

KEEP OUT OF REACH OF CHILDREN WARNING

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.



STATE OF HAWAII
Department of Agriculture

ACCEPTED

LICENSE NO. **8075.25**

INGREDIENTS:

ACTIVE INGREDIENTS:

3-Iodo-2-Propynyl Butyl Carbamate	0.450%
Propiconazole:1-[[2-(2,4-dichlorophenyl)-4-propyl-1, 3-dioxolan-2-yl]-methyl]-1H-1,2,4-triazole	0.125%

OTHER INGREDIENTS:	99.425%
TOTAL:	100.000%

THIS PRODUCT CONTAINS PETROLEUM DISTILLATES

Manufactured for:
ISK Biocides, Inc.
416 East Brooks Road
Memphis, TN 38109

EPA Reg. No. 1022-590-71581
EPA Est. No. 1022-TN-001

IBD-PL-212

9/12

WOOD guard® XL

IDEALLY SUITED FOR LOG HOMES, ROOFS, SIDING, AND FENCES
ESPECIALLY ROUGH SAWN LUMBER
OLD WEATHERED WOOD
NEW POROUS WOODS

Test before using on smooth dense wood.

Do not use on painted surfaces.

WOODGUARD® XL must penetrate to be effective
Wood must be dry before application (less than 18% moisture)

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
WARNING

Causes skin irritation. Do not get on skin or on clothing. Avoid contact with eyes. Wear coveralls over long sleeved shirt and long pants and chemical resistant gloves. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. Remove and wash contaminated clothing before reuse.

Personal Protective Equipment (PPE):

Applicators and other handlers must wear:

- Coveralls over long sleeved shirt and long pants
- Shoes plus socks
- Chemical resistant gloves
- For Cleaning Equipment: Chemical resistant apron.

User Safety Requirements:

Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions exist for washables, use detergent and hot water. Keep and wash PPE separately from other laundry.

User Safety Recommendations:

- Users should wash hands before eating, drinking, chewing gum, using tobacco or using the toilet.
- Users should remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing.
- User should remove personal protective equipment immediately after handling this product. Wash outside of gloves before removing. As soon as possible, wash thoroughly.

FIRST AID

IF SWALLOWED:	<ul style="list-style-type: none">• Call a poison control center or doctor immediately for treatment advice.• Have person sip a glass of water if able to swallow.• Do not induce vomiting unless told to by a poison control center or doctor.• Do not give anything to an unconscious person.
IF IN EYES:	<ul style="list-style-type: none">• Hold eye open and rinse slowly and gently with water for 15 – 20 minutes.• Remove contact lenses, if present, after the first 5 minutes, then continue rinsing.• Call a poison control center or doctor for treatment advice.
IF ON SKIN OR CLOTHING:	<ul style="list-style-type: none">• Take off contaminated clothing.• Rinse skin immediately with plenty of water for 15 – 20 minutes.• Call a Poison Control Center or doctor for further treatment advice.
In case of emergency, call Chemtrec toll free at 800-424-9300. Have the product container or label with you when calling a poison control center or doctor or going for treatment.	
NOTE TO PHYSICIAN: This product contains petroleum distillates. Vomiting may cause aspiration pneumonia.	

ENVIRONMENTAL HAZARDS

This product is toxic to fish and shrimp. DO NOT discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. DO NOT discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the Environmental Protection Agency.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

PESTICIDE STORAGE: Store in a secure, well-ventilated area protected from extreme temperatures. Do not transfer to unmarked containers. Keep container closed when not in use.

PESTICIDE DISPOSAL: Wastes resulting from the use of this product must be disposed of on site or at an approved waste disposal facility.

CONTAINER HANDLING: Nonrefillable container. Do not reuse or refill this container.

If Empty: Place in trash or offer for recycling if available.

If Partially Filled: Call your local solid waste agency or 1-800-CLEANUP for disposal instructions. Never place unused product down any indoor or outdoor drain.

WOODGUARD XL is an oil-based, transparent preservative designed for log homes, wood shingle roofs, siding, and fences. WOODGUARD XL's oil formula provides long-term protection by penetrating deeply into the wood. It achieves maximum performance on rough sawn lumber, old weathered wood and new porous wood where maximum penetration results in exceptional water repellency on sloping roofs and vertical surfaces; horizontal surfaces are normally subjected to more severe weathering and will usually require earlier retreatment. In harsh exposures involving standing water, retreatment may be required annually to maintain water repellency.

Surfaces previously treated with a semi-transparent stain (non-film forming) may be satisfactorily recoated with WOODGUARD XL when a superior, water repellent wood preservative is desired. If WOODGUARD XL is applied to non-porous or film-covered surfaces which prevent or significantly retard penetration, reduced performance or even complete failure can result. Test first if in doubt.

See the WOODGUARD Preparation and Application Guide for guidelines on preparation of the wood surface for WOODGUARD XL application.

WOODGUARD XL combines mold and decay control with unique and EXCEPTIONAL WATER REPELLENCY THAT WITHSTANDS OUTDOOR VERTICAL WEATHERING, ESPECIALLY ON OLD, CRACKED, WEATHERED WOOD. WILL LAST 3 – 5 YEARS.

WOODGUARD XL cannot chip, crack or peel. When applied as directed, it leaves a uniform, streak-free appearance.

WOODGUARD XL protects and extends service life by inhibiting mold and decay, as well as cupping and warping. A single coat application is recommended every 3 to 5 years on vertical surfaces. Always apply to the point of refusal. Double coat applications are not needed or recommended.

WOODGUARD XL cleans up with water and detergent at time of application – provided it has not soaked into the surface. Cured WOODGUARD XL will clean up with paint thinner or mineral spirits.

WOODGUARD XL (clear) temporarily darkens wood color which later greys after weathering. Use pigmented WOODGUARD XL to help hide this greyed effect.

DIRECTIONS FOR USE

It is a violation of Federal Law to use WOODGUARD XL in a manner inconsistent with its labeling.

Do not allow adults, children, or pets to enter the treated area until sprays have dried. Do not apply this product in a way that will contact adults, children, or pets, either directly or through drift.

Apply liberally to log buildings, roof, wood siding, or fence by simply wetting down the surface as follows:

Spray – Do not use airless spray equipment. Use a garden-type, pump-up sprayer with adjustable nozzle. Set nozzle to deliver a low pressure, coarse spray and backbrush as necessary.

Brush – A regular paint brush is fine for most surfaces. For uneven shingle or rough surfaces, use a stiff bristle brush. Apply evenly, brushing out sags, etc. as necessary.

Roller – Use a long nap for rough surfaces.

Manufactured for:

ISK Biocides, Inc.

416 East Brooks Road • Memphis, TN 38109

IBD-PL-212

ONE COAT IS SUFFICIENT. Surface must be clean and free of all loose debris. Apply to dry wood for maximum penetration and fastest drying. Wood must be dry before application (less than 18% moisture).

Avoid contact with plants, shrubs and trees.

NOTE:

1. The wood surface must be clean before application. See the Preparation and Maintenance Guide for cleaning directions.
2. Stir or shake well before use.
3. WOODGUARD XL goes on "dark" but lightens considerably during the curing period.
4. Cure time will range from 4 days to 2 weeks, depending on temperature and wood porosity.
5. Coverage: 150 to 300 sq. ft. per gallon, depending on surface condition and wood porosity. Always apply to the point of refusal.
6. Application temperature: Do not apply if the overnight low temperature is below 55°F/12.5°C or the daytime high temperature is above 95°F/35°C. At 55-60°F, dilute with mineral spirits or turpentine - one pint to one gallon of WOODGUARD XL. Below 65°F, WOODGUARD XL may become too viscous to spray, but easily spreads by brush down to 55°F.
7. WOODGUARD XL softens asphalt (including asphalt shingles) – avoid contact.
8. Do not apply if rain is expected within 48 hours.
9. WOODGUARD XL provides an immediate water repellent barrier; however, its ability to bead water develops as it cures. Re-treat when the surface exhibits signs of losing capability to inhibit water penetration.
10. Avoid open flame during application and until WOODGUARD XL has soaked in completely.
11. Subsequent painting – WOODGUARD XL provides such strong properties of water repellency that subsequent applications of paint will not adhere as long as the WOODGUARD XL barrier remains intact. If in doubt, test first.
12. WOODGUARD XL protection will not withstand repeated contact with chlorine or chlorinated water. Avoid using on wood in contact with this chemical, or retreat as necessary.
13. Until WOODGUARD XL has thoroughly cured, treated surface may be slippery. WOODGUARD XL in its clear, untinted form is effective on many wood products – greenhouse items, fruit and vegetable boxes, and other farm uses, especially wood surfaces in close proximity with animals, feedstuffs and the like.

TINTING INSTRUCTIONS

WOODGUARD XL is compatible with and may be colored by the addition of small quantities of the Universal Machine Colorants employed to color oil or water based paints. It is important to note that different colorants weather differently, and that color development varies with wood species, wood grain and wood undertone.

Consult your dealer for assistance in tinting WOODGUARD XL. WOODGUARD XL is a transparent preservative oil finish that can be tinted to a light stain; do not attempt to obtain a heavy or solid color stain by overloading with pigment. Approved formulas are available from your dealer or at www.WOODGUARD.com.

Stir tinted WOODGUARD XL frequently when applying to keep pigments evenly dispersed and uniform. Coat surfaces evenly. Smooth sags or runs by feathering with a brush or cloth in order to achieve a uniform appearance.

WARRANTY AND LIMITATION OF DAMAGES

Seller warrants to those persons lawfully acquiring title to this product that at the time of the first sale of this product by seller this product conformed to its chemical description and that it was reasonably fit for the purposes stated on the product label when used both in accordance with the Direction for Use appearing on the product label and under normal conditions of use. Buyers and users of this product assume the risk of all loss or damage from use or handling of this product that results from their failure to read and comply with the Directions for Use of this product which appear on the product label. SELLER MAKES NO OTHER EXPRESS OR IMPLIED WARRANTY, INCLUDING ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS OR OF MERCHANTABILITY, AND NO AGENT OF SELLER IS AUTHORIZED TO DO SO. Unless expressly prohibited by state law, the liability of seller for any breach of warranty shall not exceed the purchase price of the product as to which a claim is made.

9/12

WOODGUARD® is a registered trademark of IBC Manufacturing Company.