

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

DANGER

**CORROSIVE. CAUSES IRREVERSIBLE EYE DAMAGE AND SKIN BURNS.
MAY CAUSE ALLERGIC SKIN REACTION. HARMFUL IF INHALED.
HARMFUL IF SWALLOWED OR ABSORBED THROUGH THE SKIN**

Do not get in eyes, on skin, or on clothing. Mixers, loaders and others exposed to this product must wear: long-sleeved shirt and long pants; chemical resistant gloves such as nitrile or butyl rubber; shoes plus socks; goggles and face shield; and chemical resistant apron. Discard clothing or other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exists, use detergent and hot water. Keep and wash PPE separately from other laundry. Users should wash hands before eating, drinking, chewing gum, using tobacco or using the toilet. Users should remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users should remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly. This product may cause skin sensitization reactions in some people.

ENVIRONMENTAL HAZARDS

This chemical is toxic to aquatic plants, fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on this label.

STORAGE AND DISPOSAL

PESTICIDE STORAGE:

Do not contaminate water, food or feed by storage, disposal, or cleaning of equipment. Do not apply this product in a way that will contact workers or other persons.

PESTICIDE DISPOSAL:

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

NONREFILLABLE CONTAINER. Do not reuse or refill this container. Triple rinse or pressure rinse container (or equivalent) promptly after emptying. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by procedure approved by state and local authorities.

GENERAL: CONSULT FEDERAL, STATE, OR LOCAL DISPOSAL AUTHORITIES FOR APPROVED ALTERNATIVE PROCEDURES.

CONDITIONS OF SALE AND WARRANTY

ChemTreat, Inc. warrants that this product conforms to its chemical description and is reasonably fit for the purpose stated on the label only when used in accordance with label directions and as defined in the Direction for Use on this label. CHEMTREAT, INC. MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, EITHER OF MERCHANTABILITY OR FITNESS, OR A PARTICULAR USE. Handling, storage, and use of the product by Buyer or User are beyond the control of ChemTreat, Inc. and Seller. Risks such as ineffectiveness or other unintended consequences resulting from, but not limited to, failure to follow directions will be assumed by the Buyer or User. TO THE EXTENT PERMITTED BY LAW, NEITHER CHEMTREAT, INC NOR SELLER SHALL BE LIABLE FOR CONSEQUENTIAL, SPECIAL OR INDIRECT DAMAGES RESULTING FROM THE HANDLING, STORAGE OR USE OF THIS PRODUCT.



LICENSED

PERIOD **2014-2016** LIC. NO.

8102.10

CHEMTREAT CT-2015

INDUSTRIAL MICROBIOCIDIC FOR USE IN RECIRCULATING WATER COOLING TOWERS, AIR WASHER SYSTEMS, RECIRCULATING CLOSED LOOP WATER COOLING SYSTEMS, BREWERY PASTEURIZER/CAN WARMER SYSTEMS AND PAPERMILL SLIME CONTROL

ACTIVE INGREDIENTS:

5-Chloro-2-methyl-4-isothiazolin-3-one.....1.11%

2-Methyl-4-isothiazolin-3-one.....0.39%

INERT INGREDIENTS.....98.50%

Total:..... 100.00%

KEEP OUT OF REACH OF CHILDREN

DANGER

FIRST AID

IF ON SKIN: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15 – 20 min. Call a poison control center or doctor for treatment advice.

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15 – 20 min. Remove contact lenses, if present, after first 5 min., then continue rinsing eye. Call a poison control center or doctor for treatment advice.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible. Call a poison control center or doctor for further treatment advice.

IF SWALLOWED: Call a poison control center or doctor immediately for treatment advice. Do not induce vomiting unless told to do so by a poison control center or doctor. Have person sip a glass of water if able to swallow. Do not give anything to an unconscious person.

Have the product container or label with you when calling a poison control center or doctor, or going for treatment.

IN CASE OF EMERGENCY, CALL 1-800-424-9300.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsions may be necessary.

SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

DISTRIBUTED BY:

CHEMTREAT, INC.

5640 COX ROAD, GLEN ALLEN, VA 23060

804-935-2000

EPA REG. NO. 707-133-15300 EPA EST. NO. 15300-VA-01

15300-TX-01

NET WEIGHT 55 GAL (8.4 LBS/GALLON)

DIRECTIONS FOR USE: It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

For the control of microbial biofilm, bacteria, algae, and fungi, add **ChemTreat CT-2015** to: **industrial recirculating water cooling towers, industrial recirculating closed loop water cooling systems, brewery pasteurizer and can water systems.** Add **ChemTreat CT-2015** at some point in the system to ensure uniform mixing.

INITIAL DOSE: When the system is noticeably fouled, apply 148 - 883 ppm **ChemTreat CT-2015** (1.26 - 7.46 pound or 19 - 113 fluid ounce of **ChemTreat CT-2015** per 1000 gallon of water in the system.) Repeat until control is achieved. Badly fouled systems should be cleaned before treatment is begun.

SUBSEQUENT DOSE: When microbial control is evident, add 35 - 219 ppm **ChemTreat CT-2015** (0.3 - 1.86 pound or 4.5 - 28 fluid ounce of **ChemTreat CT-2015** per 1000 gallon of water in the system) weekly or as needed to maintain control.

AIR WASHER SYSTEMS:

Add to the air washer sump or chill water sump to ensure uniform mixing, 35 - 883 ppm **ChemTreat CT-2015** (0.3 to 7.46 pound or 4.5 - 113 fluid ounce of **ChemTreat CT-2015** per 1000 gallon of water in the system) depending on the severity of contamination to control microbial biofilms, bacteria, fungi and algae which cause fouling in industrial air washer systems.

INTERMITTENT OR SLUG METHOD:

INITIAL DOSE: When the system is noticeably fouled, apply 148 - 883 ppm **ChemTreat CT-2015** (1.26 to 7.46 pound or 19 - 113 fluid ounce of **ChemTreat CT-2015** per 1000 gallon of water in the system.) Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 35 - 219 ppm **ChemTreat CT-2015** (0.3 - 1.86 pound or 4.5 - 28 fluid ounce of **ChemTreat CT-2015** per 1000 gallon of water) in the system weekly or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

CONTINUOUS FEED METHOD:

INITIAL DOSE: When the system is noticeably fouled, apply 148 - 883 ppm **ChemTreat CT-2015** (1.26 - 7.46 pound or 19 - 113 fluid ounce of **ChemTreat CT-2015** per 1000 gallon of water in the system).

SUBSEQUENT DOSE: Maintain this treatment level by adding a continuous feed of 35 - 219 ppm **ChemTreat CT-2015** (0.3 - 1.86 pound or 4.5 - 28 fluid ounce of **ChemTreat CT-2015** per 1000 gallon of makeup water). Badly fouled systems must be cleaned before initial treatment.

NOTE: For use only in systems that maintain effective mist-eliminating components.

PAPERMILLS

For the control of microbial biofilm, bacteria, algae and fungi, add **ChemTreat CT-2015** to the Beater, Hydropulper, or Fan or Broke Storage Pumps or some other point in the system to insure uniform mixing. Apply 0.44 to 1.5 lb. (7 - 23 fluid ounce) of **ChemTreat CT-2015** per ton (dry basis) of pulp or paper produced as a slug dose. If needed, repeat daily. Badly fouled systems should be cleaned before initial treatment.