

.625" (15.88mm) FIN SEAL	3.375" (85.73mm) BACK PANEL (TOP WHEN FORMED)	6.75" (171.45mm) FACE PANEL	2.75" (69.85mm) BACK PANEL (BOTTOM WHEN FORMED)	.625" (15.88mm) UNDER FIN SEAL	.625" (15.88mm) FIN SEAL
--------------------------	---	-----------------------------	---	--------------------------------	--------------------------

.094" (2.4mm) END SEAL
 .39" (10mm) END SEAL
 .12" NO PRINT

Cut on dotted line to open

Cut on dotted line to open

.12" NO PRINT
 .39" (10mm) END SEAL
 .094" (2.4mm)

For above ground 18' to 21' or in ground pools

5,000 to 10,000 gallons



Replacement Chlorine Cartridge

Cartucho de cloro

Fits Flippin' FROG® XL™



Lasts 3-4 Weeks
Dura de 3 a 4 semanas

Keep Out of Reach of Children
DANGER
SEE FIRST AID AND ADDITIONAL PRECAUTIONARY STATEMENTS ON SIDE AND BACK PANELS

Active Ingredient:
Trichloro-s-Triazinetrione.....99.0%
Other Ingredients.....1.0%
Total.....100.0%
Available Chlorine: 90%

EPA Reg. No.: 53735-2
EPA Est. No.: 69470-WV-002
Net Wt.: 28 oz. (794 gms)

When Flippin' FROG XL fills over the chlorine cartridge is empty and must be replaced. To release the bottom chlorine cartridge, squeeze the tabs and pull the empty cartridge out. If Flippin' FROG XL has not been used for 6 months or one pool season whichever is shorter, simply attach a new chlorine cartridge and set the complete system back in the water. If the chlorine cartridge still contains a small amount of chlorine after the system has flipped over, hang on the tether via the hook on the side of the cartridge until completely empty. Do not allow chlorine cartridges to sink to the bottom or pool bleaching may occur. Once Flippin' FROG XL has been used for 6 months or one pool season whichever is shorter, the minerals are no longer active. Replace the entire Flippin' FROG XL System and discard the mineral cartridge in the trash.

To assemble: Remove outer packaging. Align the bottom orange chlorine cartridge with tab guides on this top green mineral cartridge. **SEE FIGURE A**

- Push together until you hear the cartridge click into place.
- First setting from initial setting chart. **SEE FIGURE B**
- Test the dial on the chlorine cartridge to the setting number.
- Adjust cover and tether to pool.
- Maintain 1.5 to 2.0 ppm free chlorine level.
- Initially test water daily with FROG® Test Strips.

Para el montaje: Retire empaque exterior.

- Utilice las guías de las lengüetas para alinear el cartucho inferior con el cartucho superior.
- Indique las menbradas al dial con el cartucho superior que contiene las menbradas.
- Presione una parte cubierta de una mesa o un dispositivo que indique que los cartuchos encajaron.
- Encuentre el nivel de ajuste inicial. **VER FIGURA B**
- Coloque la perilla selector del cartucho que contiene el dial en el número que corresponde. **VER FIGURA B**
- Mantenga un nivel de cloro libre de 1.5 a 2.0 ppm.
- Al principio, pruebe el agua cada día con FROG® Test Strips.
- Después de probar, revise cuando la piscina esté en uso.
- Este producto puede romperse cuando la piscina está en uso.
- Aplique un tratamiento de choque a la piscina para mantener la cantidad del agua.

PRECAUTIONARY STATEMENTS: HAZARDS TO HUMANS AND DOMESTIC ANIMALS: DANGER: CORROSIVE: If product is removed from its original container, causes irreversible eye damage and skin burns. May be fatal if absorbed through skin. May be fatal if inhaled. Do not breathe dust or spray mists. Inhaling to nose and throat. Harmful if swallowed. Do not get in eyes, on skin or on clothing. Follow directions for use carefully. Wash thoroughly with soap and water after handling and before eating, drinking or using tobacco or using the toilet. Remove contaminated clothing and wash before reuse. **PHYSICAL OR CHEMICAL HAZARDS:** Corrosive. Strong oxidizing agent. Non-refillable container. Do not attempt to refill empty cartridge. Place only into water or installed equipment made for this product. Contamination with moisture, dirt, organic matter or other chemicals (including other pool chemicals) or any other foreign matter may start a chemical reaction with generation of heat, liberation of hazardous gases and possible fire and explosion. Avoid any contact with flammable or burning material such as a lighted cigarette. Do not use this product in any chlorinating device which has been used with any inorganic or unstabilized chlorinating compounds (e.g., calcium hypochlorite). Such use may cause fire or explosion.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish and aquatic organisms. **STORAGE AND DISPOSAL:** Do not contaminate food or feed with this product. **Product Storage:** Store cartridge in original container in a cold, dry, well-ventilated area away from heat or open flame. In case of decomposition, isolate container and flood area with large amounts of water to dissolve all material before discarding this cartridge. **Pesticide Disposal:** Product or residues that cannot be used must be diluted with water before disposal in a sanitary sewer. **Container Handling:** Non-refillable container. Do not reuse or refill this container. Shake the cartridge over the pool and away from your face to ensure it is empty before offering for recycling if available or dispose of in a sanitary landfill, or by other procedures approved by state and local authorities. **NPTN hotline number for public information: 1-800-858-7378.** EQ04214553081443N 20-45-2032

FIRST AID: If in Eyes: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice. **If on Skin or Clothing:** Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice. **If Swallowed:** Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to an unconscious person. Have the product container or label with you when calling a poison control center or doctor, or going for treatment. **If Inhaled:** Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice. **Note to Physician:** Probable mucosal damage may contraindicate the use of gastric lavage. In case of a medical emergency call 1-800-424-9300.

INITIAL SETTING CHART

Gallons Setting#	1	2	3	4
5,000	1	2	3	4
6,000	1	2	3	4
7,000	1	2	3	4
8,000	1	2	3	4
9,000	1	2	3	4
10,000	1	2	3	4

Mr. King Technology, Inc. 11th Ave S.
Hopkins, MN 55343 www.kingtechnology.com

22906 08551 5

11.938" (303.225mm) REPEAT


14.75" (374.65mm) WEB WIDTH



LICENSED

PERIOD 2015-2017 LIC. NO. 8272.11

	= WHITE SUBSTRATE (NO PRINT)		= AVAILABLE NON-CRITICAL PRINT AREA (NO LOGOS, UPCs, OR IMPORTANT LEGAL COPY RECOMMENDED IN THESE AREAS)
	= PRINT/COPY IS VISIBLE IN THIS AREA, BUT AREA IS AT AN ANGLE TO THE CRITICAL COPY PANEL.		= CRITICAL PRINT AREA PLACEMENT OF LOGOS, UPCs, OR IMPORTANT LEGAL COPY RECOMMENDED IN THESE AREAS.



*PLEASE NOTE: "OFFSET FIN" refers to the position of the seal on the back of the package and not the position of the print. The face panel artwork is not offset for this type of seal.

This design was created to work with equipment producing the type of back seal shown above. If this is not the type of seal utilized for this packaging, please contact your customer service representative immediately.

COMMENTS:

- 6/12/14 - Highlighted .12" no print areas adjacent to end seals.
- 9/5/14 - Revised visible print areas based on formed/filled sample provided 8/29.
 - Changed end seal to 1.125" width based on formed/filled sample.
 - Revised repeat to 11.938" to accommodate current press tooling.
 - Updated back seal chart to agree with print orientation of new design.
- 9/8/14 - Reduced web width to 14.75", back seals to .625"

