Nature2® Mineral Sanitizers for Pools

PRECAUTIONARY STATEMENT
Hazards to Humans and Domestic Animals.

CAUTION
In the unlikely event that a cartridge breaks, mineral media should not be ingested by humans or animals as it may cause gastric distress.

FIRST AID
IF INGESTED: Call poison control center or doctor immediately for treatment advice.

DISPOSAL
After six (6) months of use, discard cartridge in household trash. Do not save the cartridge for re-use. The cartridge is manufactured with mineral media sealed inside. In the unlikely event a cartridge breaks, remove it and vacuum out any media introduced into the pool water.

DIRECTIONS FOR USE
It is a violation of Federal law to use this product in a manner inconsistent with its labeling. See owner's manual inside box for directions for use.

CHANGE THIS CARTRIDGE EVERY SIX (6) MONTHS
Use of this cartridge for longer than six (6) continuous months will void the warranty. Discard this cartridge at the end of six (6) months.

Zodiac Pool Systems, Inc.
2620 Commerce Way
Vista, CA 92081-8438

APSP
The Association of Pool & Spa Professionals™

©2010 Zodiac Pool Systems, Inc.

Assembled in USA from components made in USA and China.

W12234M Rev C

Nature2® Mineral Sanitizers for Pools

Department of Agriculture
STATE OF HAWAII
LICENSED
PERIOD 2015-2017 LIC. NO.
8300.6

Department of Agriculture
STATE OF HAWAII
LICENSED
PERIOD 2012-2014 LIC. NO.

FOR INGROUND POOLS

The Mineral Pool Sanitizer

Controlled Release Technology (CRT) controls the release of silver and copper mineral ions into your pool water.

The Nature2® System* with CRT effectively sanitizes your pool

- Destroys bacteria
- Restores water clarity
- Reduces chlorine use to just 0.5 ppm

To keep your patented Nature2 Sanitizer operating properly, it is necessary to change the cartridge every six (6) months.

CONTROLLED RELEASE TECHNOLOGY CRT

Nature2® Mineral Sanitizers for Pools

M CARTRIDGE

FOR INGROUND POOLS

The Low Chlorine Alternative*

Destroys bacteria with CRT

CONTROLLED RELEASE TECHNOLOGY CRT

ACTIVE INGREDIENTS:
Metallic Silver** 3.51%
Copper sulfate pentahydrate*** . . .8.23%
INERT INGREDIENTS:. 88.26%
TOTAL:. 100.00%

**From Silver Nitrate
***Copper (Cu) as Metallic. 2.09%

*The Nature2® System consists of the patented Nature2 technology used in conjunction with a chlorine delivery device or 0.5 ppm of an EPA registered chlorine pool product.

†Nature2 technology consists of the minerals silver and copper.

KEEP OUT OF REACH OF CHILDREN

CAUTION

See back panel for additional precautionary statements.

EPA Reg. No. 67712-1
EPA Est. No. 67712-CA-001

NET CONTENTS: ONE (1) CARTRIDGE

Nature2® Mineral Sanitizers for Pools

FOR INGROUND POOLS

The Low Chlorine Alternative*

Nature2® water is brilliantly clear and soft

- Reduces potential for stinging eyes, skin irritation, and unpleasant odors
- Enhances swimmer comfort
- Lower chlorine levels help keep the pool pH balanced

It's Compatible

- Compatible with most pool maintenance products****
- Will not damage your pool equipment

CONTROLLED RELEASE TECHNOLOGY CRT

****Do not use Nature2 Cartridge with copper-based algaecides or Biguanides.

Nature2® *Mineral Sanitizers for Pools*

Nature2® Cartridge Owners Manual

For Nature² G Cartridges, Nature² M Cartridges and Nature² VC Cartridges

EPA Reg. No. 67712-1
EPA Est. No. 67712-CA-001

IMPORTANT
Pool Owner, save this manual.
Builders, leave this manual with the pool owner.

Cartridge Capacity

G Cartridge	10,000 - 25,000 gallons 25,000 - 35,000 gallons 35,000 - 45,000 gallons
M Cartridge	5,000 - 25,000 gallons
VC Cartridge	5,000 - 20,000 gallons 20,000 - 40,000 gallons

We ask you to take the time to get familiar with this manual.

Thank you for purchasing Nature². We believe the more you know, the more enjoyable your family's swimming experience will be – and the more you will reduce the time, effort and cost of maintaining your pool. Pool owners who switch from conventional chemical programs to the Nature2 System* spend less time maintaining their pools. Every pool has its own characteristics of water type, amount of sunlight, etc. The recipe included in this manual will help insure good water quality for your pool. Remember, your Nature2 dealer can provide advice and service.

Safety Instructions - Important Information Please read prior to installation

Nature2 G Cartridges, Nature2 M Cartridges and Nature2 VC Cartridges have been designed to sanitize swimming pools from 5,000 to 45,000 gallons depending on cartridge model. Make sure that your Nature2 Cartridge corresponds with the proper vessel and is appropriate for your pool size by consulting the chart above.

⚠ ATTENTION

Failure to heed the following can result in permanent injury, or drowning.

EQUIPMENT UNDER PRESSURE

- Always turn pump off prior to installing or changing Nature2 cartridge. Your pump/filter system is operated under pressure and the pressure must be released before you begin work. Please see your pump/filter owner's manual for further instructions.

PREVENT CHILD DROWNING

- Do not let anyone, especially small children, sit, step, lean or climb on any equipment installed as part of your pool's operational system. Locate the components of your operational system at least 3 feet from the pool so children cannot use the equipment to access the pool and be injured or drown.

LOW CHLORINE RECIPE

- You must strictly follow the low chlorine recipe included in this manual to maintain proper water chemistry and avoid health hazards. Failure to follow these instructions can lead to sickness from bacteria and other noxious organisms.

⚠ CAUTION

PRECAUTIONARY STATEMENT
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION
In the unlikely event that a cartridge breaks, mineral media should not be ingested by humans or animals as it may cause gastric distress.

FIRST AID
If Ingested: Call poison control center or doctor immediately for treatment advice.

The Nature2 Pool Sanitizer is designed only for residential swimming pools.

*The Nature2 System consists of the patented Nature2 technology† used in conjunction with a chlorine delivery device or 0.5 ppm of an EPA registered chlorine pool product.

†Nature2 technology consists of the minerals silver and copper

DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

NATURE^{2}® COMPATIBILITY

Nature^{2} Systems* can be used with all types of pool chemical treatments available except biguanide products and copper based algaecides.

Important: When converting either a biguanide or bromine treated pool to the Nature^{2} low chlorine System*, the pool must be completely drained and refilled. Then follow the Nature^{2} cartridge start-up procedure below.

Start Up

- Before starting up a new Nature^{2} cartridge, clean debris and algae out of the pool and pool equipment.

Important: Do not install the new cartridge until the pool water is clean and chemically balanced.

- Balance pool water before installing Nature^{2} cartridge.
  - pH 7.4-7.8
  - Calcium hardness 200-400 ppm
  - Total alkalinity 80-150 ppm

Consult with your Nature^{2} Dealer for specific water balance instructions.

Balance the Water

To find out if your pool water is balanced:

- take a water sample to your dealer to be tested regularly, or
- ask your dealer to recommend a pool test kit for water balance.

Element: **pH** **Range:** 7.4-7.8	**If it's too low:**	The surface of your pool can become etched. Metal parts in the pump and plumbing will corrode.	**How to fix:**	Add pH increaser.
	If it's too high:	"Scale" forms on the surface of your pool. The water can become cloudy. Equipment can become damaged.	**How to fix:**	Add pH decreaser.
Element: **Calcium Hardness** **Range:** 200-400 ppm	**If it's too low**:	Water is less stable. In plaster pools, the calcium is taken out of the plaster, causing the surface to deteriorate.	**How to fix:**	Add calcium hardness increaser.
	If it's too high:	Rough, discolored deposits ("scale") will form on the pool surface and inside pool equipment.	**How to fix:**	Drain or dilute the pool water. Consult your dealer.
Element: **Total Alkalinity** **Range:** 80-150 ppm	**If it's too low:**	It provides no buffer so that you constantly get fluctuating pH readings, which can damage equipment and pool surfaces.	**How to fix:**	Use an alkalinity increaser.
	If it's too high:	White deposits ("scale") form on the tile line. The plaster on pool surface becomes rough or discolored. The water becomes cloudy or milky white.	**How to fix:**	Add acid to bring alkalinity down.

Install the Cartridge

1. **Install the cartridge** after water is balanced. Refer to your Nature$^{2®}$ vessel operating manual for additional instructions regarding your particular model's installation.
2. **Superoxidize the pool** water with chlorine according to manufacturer's instructions to burn off contaminants and activate cartridge.

Important: Initial superoxidation with chlorine is required to burn off contaminants and activate cartridge.

3. **Run the circulating pump either**:
   - 24 hours a day for 4 days, maintaining 1-2 ppm free chlorine throughout, or
   - 6 hours a day for 14 days, maintaining 1-2 ppm free chlorine throughout.
4. **Let chlorine dissipate** to 0.5 ppm once start up period is completed.
   - Do not enter the pool if the free available chlorine residual is over 3 ppm.

Recipe

There is one (1) recipe for maintaining clean, clear, sanitized water with minimum time and effort.

This recipe provides the easiest and most economical way to care for your Nature^2 pool.

Low-Chlorine Recipe

Ingredients:

- Nature^2 Cartridge
- Chlorine granules, tablets, liquid or generator
- pH and total alkalinity adjusting chemicals
- Calcium hardness increaser, if needed
- Water test kit

Once the 4-day or 14-day start-up period is done, allow the free available chlorine residual to drop to 0.5 ppm (by reducing the amount of chlorine you add) then:

When:	What to do:
Every day	Run pump and filter at least six (6) hours every day.
Once a week	Balance pH and total alkalinity.
Twice a week	Check chlorine residual; add chlorine to maintain at least a 0.5 ppm range using the chart below.
As needed	If water is hazy, superoxidize with chlorine according to manufacturer's instructions. Additional shocking is recommended following rainstorms or heavy bather load. Do not re-enter the pool if the free available chlorine residual is over 3 ppm.

Add the following amounts of chlorine per 10,000 gallons of water to increase free chlorine by 0.5 ppm.

Type of Chlorine Containing Compound	% Active Ingredient	% Available Chlorine Content	Ounce Quantity Required	Gram Quantity Required
Sodium Hypochlorite Liquid	5.25	5.25	12.7	361
Sodium Hypochlorite Liquid	9.2	9.2	7.3	206
Sodium Hypochlorite Liquid	10	10	6.5	184
Sodium Hypochlorite Liquid	12	12	5.6	158
Calcium Hypochlorite	65	64	1.1	30
Dichloroisocyanurate	99	62	1.1	30
Lithium Hypochlorite	29	35	1.9	54
Trichloro-s-triazintrione	99	90	0.7	21
Chlorine Gas, from any source including chlorine generators	100	100	0.7	19

Provide Filtration/Circulation

To manage:	You need to:
Circulation	Follow the manufacturer's directions for keeping the circulating pump in good working order and operate it at least six (6) hours a day. Consult your Nature^2 dealer for optimum run times.
Filtration	Check the pool's filter periodically and clean it as recommended by the manufacturer.

Troubleshooting Guide

Consult your Nature^{2}® Dealer for additional assistance or call 1-800-822-7933.

	Problem	What to look for	Treatment
Cloudy water Frequently caused by improper start up. See section on Start Up and Installing the Cartridge.	Poor filtration	Slow filter turnover rates.	1 Backwash and clean filter. 2 Run filter for 24 hours. 3 Increase run time per day.
	Algae growth	Hazy pool water; may have slightly green appearance.	Superchlorinate water with chlorine according to manufacturer's instructions and brush pool walls.
	Unbalanced water	1. High hardness. 2. High TDS (total dissolved solids). 3. High pH. 4. High total alkalinity.	Balance the pool water.
Algae Algae may be caused by insufficient levels of oxidizer and/or inadequate water circulation.	Green algae	Pea green color; attaches to pool walls; sometimes colors the entire body of water.	1 Check pH and adjust if necessary. 2 Superchlorinate with chlorine according to manufacturer's instructions and brush pool walls. 3 Repeat steps 1 and 2 until algae is gone.
	Black algae Mustard algae	Black spots on pool walls. Yellow or brown film on steps or walls.	1 Brush affected areas. 2 Superchlorinate water with chlorine according to manufacturer's instructions. 3 Add algaecide. 4 Vacuum pool. 5 Repeat steps 1 through 4 until algae is gone.
	Note: Regular algaecide treatments are recommended for outdoor pools that experience persistent algae problems. Do not use algae treatments containing either copper or sodium bromide.		
Stains	Blue/green Red/brown Black	Copper or iron from pool equipment corrosion or water supply. Iron or manganese from equipment corrosion or water supply. Manganese in water supply.	1 Adjust pH and total alkalinity to ideal ranges. 2 Vigorously brush stained areas. 3 Add sequestrant. 4 Run filter. 5 Twelve hours later, superchlorinate pool. 6 Test and balance water. 7 Test pool water for dissolved metals.
	Metal tarnishing	High native mineral content in water; unbalanced water.	Clean with soft cloth and mild detergent. Test water for minerals; use a sequestrant; maintain water balance.
Scale	Crusty deposits on pool surfaces	High pH and high total alkalinity.	Adjust pH and total alkalinity to ideal ranges.
		High TDS (total dissolved solids) or high hardness levels.	1 Replace a volume of pool water with water low in hardness and dissolved solids. 2 Use sequestrant to prevent scale buildup if high hardness levels are a continuing problem.

Nature^{2} Cartridge Replacement Intervals

Use the month indicator ring on the top of the unit to identify the date on which the cartridge should be replaced. Always turn pump off prior to installing or changing Nature^{2} cartridge. Your pump/filter is operated under pressure and the pressure must be released before you begin work. Please see your pump/filter owner's manual for further instructions.

A cartridge lasts six (6) months or one (1) season, whichever is shorter. The cartridge should not be used longer than six (6) continuous months.

Winterizing Your Pool

Use these steps as a guide. Consult your dealer for specific information in your area.

Warm Climate

1. **Reduce the number of hours the pump runs** since the cooler weather decreases the spread of algae and other pollutants.
2. **There is no need to superoxidize** the pool during cool weather unless the water becomes cloudy (as may occur after a winter storm). See Cloudy Water in Troubleshooting section.

Cold Climate

1. **Check total alkalinity and pH** of pool to make sure that they are in proper balance.
2. **Vacuum the pool bottom** to remove any debris or other potential contaminants.
3. **Superoxidize the pool** with chlorine according to manufacturer's instructions to clear the water.
4. **Add a winter algaecide** following manufacturer's instructions.

Important: Do not use a winter algaecide with copper in it. This will void the Nature^{2}® no-stain warranty.

5. **Backwash the filter**.
6. **Drain part of the pool water**. The amount to drain varies from one part of the country to another. Consult your dealer for advice.
7. **Remove the Nature^{2}** cartridge and discard with household trash.
8. **Winterize the pipes** with pool antifreeze following manufacturer's instructions.
9. **Drain the water** out of all equipment (pump, filter, etc.).
10. **Store** all baskets, hoses and cleaning equipment, indoors if possible.
11. **Cover the pool** with a winter cover.

Disposal

After six (6) months of use, discard Nature^{2} cartridge in household trash. Do not save the cartridge for re-use. The cartridge is manufactured with the mineral media sealed inside. In the unlikely event a cartridge breaks, remove it and vacuum out any media introduced into the pool.

Limited Warranty

NATURE^{2}® LIMITED WARRANTY

The limited warranties contained within this document are the only warranties given with your Nature^{2} G Cartridge, Nature^{2} M Cartridge and Nature^{2} VC Cartridge and supercede any prior warranties. **All other warranties, expressed or implied, including the implied warranty of merchantability or the implied warranty of fitness for a particular purpose are hereby disclaimed**. Our sole obligation under this warranty, and the purchaser's sole remedy, is limited to repair or replacement of the Nature^{2} G Cartridge, Nature^{2} M Cartridge and Nature^{2} VC Cartridge. The Nature^{2} warranty applies to the original owner only.

THE LIMITED WARRANTIES OF THE NATURE^{2} G CARTRIDGE, NATURE^{2} M CARTRIDGE AND NATURE^{2} VC CARTRIDGE ARE:

Nature^{2} G Cartridges, Nature^{2} M Cartridges and Nature^{2} VC Cartridges are warranted to be free of defects in materials and to perform satisfactorily for a period of six months from the date of purchase. Nature^{2} G Cartridges, Nature^{2} M Cartridges and Nature^{2} VC Cartridges are warranted not to cause copper staining in your pool. This limited warranty requires that you exercise reasonable care of your pool and keep water in balance at all times and not use a copper-based algaecide. This limited warranty does not cover discoloration to chromium fittings. This warranty does not cover cartridges used with any biguanide products. If the cartridge is defective and does not perform satisfactorily for the entire six (6) months, we will make a prorated rebate based on your actual period of use. You are responsible to pay the below-indicated percentage on the then applicable retail cost: < 1 month-0%; 1-2 months- 25%; 3-4 months-50%; 5-<6 months-75%.

EXCLUSIONS FROM WARRANTY

Nature^{2} G Cartridges, Nature^{2} M Cartridges and Nature^{2} VC Cartridges are designed for use on inground pools from 5,000 to 45,000 gallons, depending on cartridge model. If it is used in any other application, the warranty is void, and the purchaser and/or pool owner releases the manufacturer from any and all claims related to the use of the Nature^{2} Sanitizer.

This warranty does not cover problems arising in whole or in part from purchaser's negligence, misuse or abuse, improper maintenance or storage, accident, improper installation, improper application, failure to follow all appropriate safety precautions, Acts of God, abnormal weather conditions, damage from plants or animals, and improper use of chemicals.

This warranty specifically excludes all incidental or consequential damages, except where state law requires them to be paid. This warranty gives you specific rights. You may have other rights that vary from state to state.

TO SUBMIT A CLAIM

Report claims to Zodiac Pool Systems, Inc. by calling 1-800-822-7933. Only the original purchaser may submit a claim under this limited warranty. All claims must be accompanied by an original purchase receipt.

ZODIAC POOL SYSTEMS, INC.
2620 Commerce Way
Vista, CA 92081
Tel: 800-822-7933
Fax: 877-327-1403
www.zodiacpoolsystems.com

© 2010 Zodiac Pool Systems, Inc. All rights reserved.
TL-2800 Rev B 04/10