



LICENSED

LICENSED

LICENSED

PERIOD 2009-2011 LIC. NO. PERIOD 2012-2014 LIC. NO. PERIOD 2015-2017 LIC. NO. **8425.4**

LOT# 51124287 DOM 06/02/2008

STORAGE AND DISPOSAL

Health	3
Fire hazard	3
Reactivity	1
Protective Equipment	C

DO NOT CONTAMINATE WATER, FOOD OR FEED BY STORAGE OR DISPOSAL. KEEP CONTAINER CLOSED WHEN NOT IN USE. IN CASE OF SPILLAGE, ABSORB WITH INERT MATERIAL AND DISPOSE OF IN ACCORDANCE WITH APPLICABLE REGULATIONS.

PESTICIDE DISPOSAL

PESTICIDE WASTES ARE TOXIC. IMPROPER DISPOSAL OF EXCESS PESTICIDE, SPRAY MIXTURE OR RINSATE IS A VIOLATION OF FEDERAL LAW. IF THESE WASTES CANNOT BE DISPOSED OF BY USE ACCORDING TO LABEL INSTRUCTIONS, CONTACT YOUR STATE PESTICIDE OR ENVIRONMENTAL CONTROL AGENCY, OR THE HAZARDOUS WASTE REPRESENTATIVE AT THE NEAREST EPA REGIONAL OFFICE FOR GUIDANCE.

CONTAINER DISPOSAL
NONREFILLABLE CONTAINER

DO NOT REUSE OR REFILL THIS CONTAINER. OFFER FOR RECYCLING IF AVAILABLE. TRIPLE RINSE CONTAINER PROMPTLY AFTER EMPTYING. TRIPLE RINSE AS FOLLOWS: EMPTY THE REMAINING CONTENTS INTO APPLICATION EQUIPMENT OR A MIX TANK AND DRAIN FOR 10 SECONDS AFTER THE FLOW BEGINS TO DRIP. FILL THE CONTAINER 1/10TH FULL WITH THINNER AND RECAP. SHAKE FOR 10 SECONDS. POUR RINSATE INTO APPLICATION EQUIPMENT OR A MIX TANK OR STORE RINSATE FOR LATER USE OR RECYCLING. DRAIN FOR 10 SECONDS AFTER THE FLOW BEGINS TO DRIP. REPEAT THIS PROCEDURE TWO MORE TIMES. THEN OFFER FOR RECYCLING OR RECONDITIONING, OR PUNCTURE AND DISPOSE OF IN A SANITARY LANDFILL, OR BY OTHER APPROVED STATE AND LOCAL PROCEDURES.

D.O.T. SHIPPING NAME: PAINT

D.O.T. HAZARD CLASS: FLAMMABLE LIQUID

D.O.T. HAZARD IDENTIFICATION NUMBER: UN1263

3GE099

E.P.A. REG. NO.: 2568-93
E.P.A. EST. NO.: 002568-LA-001

Jotun Paints, Inc.
9203 Highway 23
Belle Chasse, LA 70037

**ANTIFOULING
SEAFORCE 200 AV
BLACK
3GE099**

ACTIVE INGREDIENT: CUPROUS OXIDE.....44.59%*
INERT INGREDIENTS.....55.41%**
.....100.00%

- * METALLIC COPPER EQUIVALENT: 39.60%
- ** CONTAINS PETROLEUM DISTILLATES, XYLENE, OR XYLENE RANGE AROMATIC SOLVENTS

KEEP OUT OF THE REACH OF CHILDREN.

WARNING

FOR COMMERCIAL USE ONLY. DO NOT USE IN OR AROUND A HOUSEHOLD OR DWELLING.

NOT SOLD FOR USE IN AIR POLLUTION REGULATION AREAS.
PHOTOCHEMICALLY REACTIVE PER RULE 102

SEE SIDE PANEL FOR FIRST AID AND ADDITIONAL PRECAUTIONARY STATEMENTS

**Net 3.785 Liters (1 gallons)
3GE099DSJ**

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS & DOMESTIC ANIMALS**

WARNING

CAUSES EYE IRRITATION.
HARMFUL IF ABSORBED THROUGH SKIN.

AVOID CONTACT WITH EYES, SKIN AND CLOTHING. WEAR PROTECTIVE CLOTHING SUCH AS GLOVES, LONG-SLEEVED COTTON SHIRT, LONG PANTS, AND HAT. MAY BE FATAL IF SWALLOWED OR INHALED. DO NOT BREATHE VAPORS OR SPRAY MIST. WHEN USED IN ENCLOSED AREAS, SPRAYING PAINT OR SANDING BOAT SURFACE. WEAR APPROPRIATE PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) DURING AND AFTER APPLICATION UNLESS AIR MONITORING DEMONSTRATES VAPOR/ MIST LEVELS ARE BELOW APPLICABLE LEVELS.

REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING AND BEFORE EATING, DRINKING, CHEWING GUM, USING TOBACCO OR USING THE WASHROOM.

ENVIRONMENTAL HAZARDS

THIS MATERIAL IS TOXIC TO FISH. DO NOT APPLY DIRECTLY TO WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES. DO NOT ALLOW CHIPS AND DUST GENERATED DURING PAINT REMOVAL TO ENTER WATER. DISPOSE OF PAINT DEBRIS IN AN APPROVED LANDFILL

PHYSICAL OR CHEMICAL HAZARDS

FLAMMABLE. DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME.

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

ANTIFOULING FOR METAL BOTTOMS
TO CONTROL THE ATTACHMENT OF MARINE FOULING, I.E. BARNACLES, GRASS, ALGAE, TUBE WORMS, MUSSELS, AND SNAILS ON HULLS OF BOATS AND VESSELS IN SALT, BRACKISH AND FRESH WATER WHICH WOULD SUSTAIN SUCH GROWTH. NOT RECOMMENDED FOR USE ON ALUMINUM. A MINIMUM OF TWO COATS OF THIS PRODUCT IS RECOMMENDED FOR BEST PERFORMANCE.

SURFACE PREPARATION
BEFORE APPLICATION OF ANTIFOULING, ALL SURFACES MUST BE DRY AND CLEANED OF DIRT, DUST, OIL, RUST, LOOSE PAINT, SALT RESIDUES AND OTHER CONTAMINANTS. STEEL MUST BE COATED WITH A SUITABLE PRIMER OR ANTI-CORROSIVE BARRIER COATS.

MIXING
BEFORE USE, POWER MIX OR BOX THE PAINT UNTIL THE PRODUCT IS UNIFORM. STIR THE PAINT AT INTERVALS DURING APPLICATION TO MAINTAIN UNIFORMITY.

APPLICATION
APPLY BY BRUSH, ROLL, OR SPRAY. CONTENTS MAY BE APPLIED BY HOT SPRAY (TEMPERATURES NOT TO EXCEED 95°F) AIRLESS SPRAY OR REGULAR COLD SPRAY. APPLY A FULL WET COAT IN A DOUBLE CROSSHATCH PATTERN. DO NOT PAINT IN COLD OR DAMP WEATHER.

THINNING
NORMALLY NO THINNING REQUIRED. WHERE THINNING IS NECESSARY, USE THINNER 7-T-33, XYLENE.

DRYING TIME
AT 70°F AND 50% R.H. ALLOW AT LEAST 4 HOURS DRY TIME BETWEEN COATS, AND A MINIMUM OF 8 HOURS BEFORE IMMERSION.

REFER TO PRODUCT MATERIAL SAFETY DATA BULLETIN, AVAILABLE UPON REQUEST, FOR FURTHER SAFETY AND HANDLING INFORMATION.

**THE VOC OF THIS PAINT IS 330
GRAMS/LITER (2.75 LBS/GAL.)**

FIRST AID	
IF IN EYES:	HOLD EYE OPEN AND RINSE SLOWLY AND GENTLY FOR 15-20 MINUTES. REMOVE CONTACT LENSES, IF PRESENT, AFTER THE FIRST 5 MINUTES, AND THEN CONTINUE RINSING. CALL A POISON CONTROL CENTER OR DOCTOR FOR TREATMENT ADVICE.
IF SWALLOWED:	IMMEDIATELY CALL A POISON CONTROL CENTER OR DOCTOR. DO NOT INDUCE VOMITING UNLESS TOLD TO DO SO BY A POISON CONTROL CENTER OR DOCTOR. DO NOT GIVE ANY LIQUID TO THE PERSON. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
IF ON SKIN OR CLOTHING:	TAKE OFF CONTAMINATED CLOTHING. RINSE SKIN IMMEDIATELY WITH PLENTY OF WATER FOR 15-20 MINUTES. CALL A POISON CONTROL CENTER OR DOCTOR FOR TREATMENT ADVICE.
IF INHALED:	MOVE PERSON TO FRESH AIR. IF PERSON IS NOT BREATHING, CALL 911 OR AN AMBULANCE, THEN GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH-TO-MOUTH IF POSSIBLE. CALL A POISON CONTROL CENTER OR DOCTOR FOR FURTHER TREATMENT ADVICE.
OTHER:	HAVE THE PRODUCT CONTAINER OR LABEL WITH YOU WHEN CALLING A POISON CONTROL CENTER OR DOCTOR, OR GOING FOR TREATMENT.
MEDICAL EMERGENCY NUMBER: 1-800-424-9300	
NOTE TO PHYSICIAN Contains petroleum distillate - vomiting may cause aspiration pneumonia.	



LICENSED

PERIOD 2009-2011 LIC. NO.



LICENSED

PERIOD 2012-2014 LIC. NO.



LICENSED

PERIOD 2015-2017 LIC. NO. 8425.4

LOT# 51119605 DOM 12/06/2007

STORAGE AND DISPOSAL

Health	3
Fire hazard	3
Reactivity	1
Protective Equipment	C

DO NOT CONTAMINATE WATER, FOOD OR FEED BY STORAGE OR DISPOSAL. KEEP CONTAINER CLOSED WHEN NOT IN USE. IN CASE OF SPILLAGE, ABSORB WITH INERT MATERIAL AND DISPOSE OF IN ACCORDANCE WITH APPLICABLE REGULATIONS.

PESTICIDE DISPOSAL

PESTICIDE WASTES ARE TOXIC. IMPROPER DISPOSAL OF EXCESS PESTICIDE, SPRAY MIXTURE OR RINSATE IS A VIOLATION OF FEDERAL LAW. IF THESE WASTES CANNOT BE DISPOSED OF BY USE ACCORDING TO LABEL INSTRUCTIONS, CONTACT YOUR STATE PESTICIDE OR ENVIRONMENTAL CONTROL AGENCY, OR THE HAZARDOUS WASTE REPRESENTATIVE AT THE NEAREST EPA REGIONAL OFFICE FOR GUIDANCE.

CONTAINER DISPOSAL

DO NOT REUSE OR REFILL THIS CONTAINER. OFFER FOR RECYCLING IF AVAILABLE. TRIPLE RINSE CONTAINER PROMPTLY AFTER EMPTYING. TRIPLE RINSE AS FOLLOWS: EMPTY THE REMAINING CONTENTS INTO APPLICATION EQUIPMENT OR A MIX TANK AND DRAIN FOR 10 SECONDS AFTER THE FLOW BEGINS TO DRIP. FILL THE CONTAINER 1/10th FULL WITH THINNER AND RECAP. SHAKE FOR 10 SECONDS. POUR RINSATE INTO APPLICATION EQUIPMENT OR A MIX TANK OR STORE RINSATE FOR LATER USE OR RECYCLING. DRAIN FOR 10 SECONDS AFTER THE FLOW BEGINS TO DRIP. REPEAT THIS PROCEDURE TWO MORE TIMES. THEN OFFER FOR RECYCLING OR RECONDITIONING, OR PUNCTURE AND DISPOSE OF IN A SANITARY LANDFILL, OR BY OTHER APPROVED STATE AND LOCAL PROCEDURES.

D.O.T. SHIPPING NAME: PAINT
D.O.T. HAZARD CLASS: FLAMMABLE LIQUID
D.O.T. HAZARD IDENTIFICATION NUMBER: UN1263

3GEBLU

E.P.A. REG. NO.: 2563-93
E.P.A. EST. NO.: 002568-LA-001

Jotun Paints, Inc.
9203 Highway 23
Belle Chasse, LA 70037

ANTIFOULING
SEAFORCE 200 AV
BLUE
3GEBLU

ACTIVE INGREDIENT: CUPROUS OXIDE.....44.59%*
INERT INGREDIENTS.....55.41%**

* METALLIC COPPER EQUIVALENT: 39.60%
** CONTAINS PETROLEUM DISTILLATES, XYLENE, OR XYLENE RANGE AROMATIC SOLVENTS

KEEP OUT OF THE REACH OF CHILDREN.

WARNING

FOR COMMERCIAL USE ONLY. DO NOT USE IN OR AROUND A HOUSEHOLD OR DWELLING.

NOT SOLD FOR USE IN AIR POLLUTION REGULATION AREAS. PHOTOCHEMICALLY REACTIVE PER RULE 102

SEE SIDE PANEL FOR FIRST AID AND ADDITIONAL PRECAUTIONARY STATEMENTS

Net 3.785 Liters (1 gallons)
3GEBLUDSJ

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS & DOMESTIC ANIMALS

WARNING

CAUSES EYE IRRITATION.
HARMFUL IF ABSORBED THROUGH SKIN.

AVOID CONTACT WITH EYES, SKIN AND CLOTHING. WEAR PROTECTIVE CLOTHING SUCH AS GLOVES, LONG-SLEEVED COTTON SHIRT, LONG PANTS, AND HAT. MAY BE FATAL IF SWALLOWED OR INHALED. DO NOT BREATHE VAPORS OR SPRAY MIST. WHEN USED IN ENCLOSED AREAS, SPRAYING PAINT OR SANDING BOAT SURFACE. WEAR APPROPRIATE PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) DURING AND AFTER APPLICATION UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS ARE BELOW APPLICABLE LEVELS.

REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING AND BEFORE EATING, DRINKING, CHEWING GUM, USING TOBACCO OR USING THE WASHROOM.

ENVIRONMENTAL HAZARDS

THIS MATERIAL IS TOXIC TO FISH. DO NOT APPLY DIRECTLY TO WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES. DO NOT ALLOW CHIPS AND DUST GENERATED DURING PAINT REMOVAL TO ENTER WATER. DISPOSE OF PAINT DEBRIS IN AN APPROVED LANDFILL.

PHYSICAL OR CHEMICAL HAZARDS

FLAMMABLE. DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME.

FIRST AID

IF IN EYES:	HOLD EYE OPEN AND RINSE SLOWLY AND GENTLY FOR 15-20 MINUTES. REMOVE CONTACT LENSES, IF PRESENT, AFTER THE FIRST 5 MINUTES, AND THEN CONTINUE RINSING. CALL A POISON CONTROL CENTER OR DOCTOR FOR TREATMENT ADVICE.
IF SWALLOWED:	IMMEDIATELY CALL A POISON CONTROL CENTER OR DOCTOR. DO NOT INDUCE VOMITING UNLESS TOLD TO DO SO BY A POISON CONTROL CENTER OR DOCTOR. DO NOT GIVE ANY LIQUID TO THE PERSON. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
IF ON SKIN OR CLOTHING:	TAKE OFF CONTAMINATED CLOTHING. RINSE SKIN IMMEDIATELY WITH PLENTY OF WATER FOR 15-20 MINUTES. CALL A POISON CONTROL CENTER OR DOCTOR FOR TREATMENT ADVICE.
IF INHALED:	MOVE PERSON TO FRESH AIR. IF PERSON IS NOT BREATHING, CALL 911 OR AN AMBULANCE. THEN GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH-TO-MOUTH IF POSSIBLE. CALL A POISON CONTROL CENTER OR DOCTOR FOR FURTHER TREATMENT ADVICE.
OTHER:	HAVE THE PRODUCT CONTAINER OR LABEL WITH YOU WHEN CALLING A POISON CONTROL CENTER OR DOCTOR, OR GOING FOR TREATMENT.
MEDICAL EMERGENCY NUMBER: 1-800-424-9300	
NOTE TO PHYSICIAN Contains petroleum distillate - vomiting may cause aspiration pneumonia.	

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

ANTIFOULING FOR METAL BOTTOMS TO CONTROL THE ATTACHMENT OF MARINE FOULING, IE. BARNACLES, GRASS, ALGAE, TUBE WORMS, MUSSELS, AND SNAILS ON HULLS OF BOATS AND VESSELS IN SALT, BRACKISH AND FRESH WATER WHICH WOULD SUSTAIN SUCH GROWTH. NOT RECOMMENDED FOR USE ON ALUMINUM. A MINIMUM OF TWO COATS OF THIS PRODUCT IS RECOMMENDED FOR BEST PERFORMANCE.

SURFACE PREPARATION

BEFORE APPLICATION OF ANTIFOULING, ALL SURFACES MUST BE DRY AND CLEANED OF DIRT, DUST, OIL, RUST, LOOSE PAINT, SALT RESIDUES AND OTHER CONTAMINANTS. STEEL MUST BE COATED WITH A SUITABLE PRIMER OR ANTI-CORROSIVE BARRIER COATS.

MIXING

BEFORE USE, POWER MIX OR BOX THE PAINT UNTIL THE PRODUCT IS UNIFORM. STIR THE PAINT AT INTERVALS DURING APPLICATION TO MAINTAIN UNIFORMITY.

APPLICATION

APPLY BY BRUSH, ROLL, OR SPRAY. CONTENTS MAY BE APPLIED BY HOT SPRAY (TEMPERATURES NOT TO EXCEED 95°F) AIRLESS SPRAY OR REGULAR COLD SPRAY. APPLY A FULL WET COAT IN A DOUBLE CROSSHATCH PATTERN. DO NOT PAINT IN COLD OR DAMP WEATHER.

THINNING

NORMALLY NO THINNING REQUIRED. WHERE THINNING IS NECESSARY, USE THINNER 7-T-33, XYLENE.

DRYING TIME

AT 70°F AND 50% R.H. ALLOW AT LEAST 4 HOURS DRY TIME BETWEEN COATS, AND A MINIMUM OF 8 HOURS BEFORE IMMERSION.

REFER TO PRODUCT MATERIAL SAFETY DATA BULLETIN, AVAILABLE UPON REQUEST, FOR FURTHER SAFETY AND HANDLING INFORMATION.

THE VOC OF THIS PAINT IS 330 GRAMS/LITER (2.75 LBS/GAL).



LICENSED

PERIOD 2009-2011 LIC. NO.



LICENSED

PERIOD 2012-2014 LIC. NO.



LICENSED

PERIOD 2015-2017 LIC. NO.

8425.4

LOT# 51122598 DOM 11/06/2008

Health	3
Fire hazard	3
Reactivity	1
Protective Equipment	C

STORAGE AND DISPOSAL

DO NOT CONTAMINATE WATER, FOOD OR FEED BY STORAGE OR DISPOSAL. KEEP CONTAINER CLOSED WHEN NOT IN USE. IN CASE OF SPILLAGE, ABSORB WITH INERT MATERIAL AND DISPOSE OF IN ACCORDANCE WITH APPLICABLE REGULATIONS.

PESTICIDE DISPOSAL

PESTICIDE WASTES ARE TOXIC. IMPROPER DISPOSAL OF EXCESS PESTICIDE, SPRAY MIXTURE OR RINSATE IS A VIOLATION OF FEDERAL LAW. IF THESE WASTES CANNOT BE DISPOSED OF BY USE ACCORDING TO LABEL INSTRUCTIONS, CONTACT YOUR STATE PESTICIDE OR ENVIRONMENTAL CONTROL AGENCY, OR THE HAZARDOUS WASTE REPRESENTATIVE AT THE NEAREST EPA REGIONAL OFFICE FOR GUIDANCE.

CONTAINER DISPOSAL

DO NOT REUSE OR REFILL THIS CONTAINER. OFFER FOR RECYCLING IF AVAILABLE. TRIPLE RINSE CONTAINER PROMPTLY AFTER EMPTYING. TRIPLE RINSE AS FOLLOWS: EMPTY THE REMAINING CONTENTS INTO APPLICATION EQUIPMENT OR A MIX TANK AND DRAIN FOR 10 SECONDS AFTER THE FLOW BEGINS TO DRIP. FILL THE CONTAINER 1/10th FULL WITH THINNER AND RECAP. SHAKE FOR 10 SECONDS. POUR RINSATE INTO APPLICATION EQUIPMENT OR A MIX TANK OR STORE RINSATE FOR LATER USE OR RECYCLING. DRAIN FOR 10 SECONDS AFTER THE FLOW BEGINS TO DRIP. REPEAT THIS PROCEDURE TWO MORE TIMES. THEN OFFER FOR RECYCLING OR RECONDITIONING, OR PUNCTURE AND DISPOSE OF IN A SANITARY LANDFILL, OR BY OTHER APPROVED STATE AND LOCAL PROCEDURES.

ANTIFOULING SEAFORCE 200 AV DARK RED 3GEDRD

ACTIVE INGREDIENT: CUPROUS OXIDE.....44.59%*
INERT INGREDIENTS.....55.41%**
.....100.00%

* METALLIC COPPER EQUIVALENT: 39.60%
** CONTAINS PETROLEUM DISTILLATES, XYLENE, OR XYLENE RANGE AROMATIC SOLVENTS

KEEP OUT OF THE REACH OF CHILDREN.

WARNING

FOR COMMERCIAL USE ONLY. DO NOT USE IN OR AROUND A HOUSEHOLD OR DWELLING.

NOT SOLD FOR USE IN AIR POLLUTION REGULATION AREAS.
PHOTOCHEMICALLY REACTIVE PER RULE 102

SEE SIDE PANEL FOR FIRST AID AND ADDITIONAL PRECAUTIONARY STATEMENTS

Net 3.785 Liters (1 gallons)
3GEDRDDSJ

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS & DOMESTIC ANIMALS

WARNING

CAUSES EYE IRRITATION.
HARMFUL IF ABSORBED THROUGH SKIN.

AVOID CONTACT WITH EYES, SKIN AND CLOTHING. WEAR PROTECTIVE CLOTHING SUCH AS GLOVES, LONG-SLEEVED COTTON SHIRT, LONG PANTS, AND HAT. MAY BE FATAL IF SWALLOWED OR INHALED. DO NOT BREATHE VAPORS OR SPRAY MIST. WHEN USED IN ENCLOSED AREAS, SPRAYING PAINT OR SANDING BOAT SURFACE. WEAR APPROPRIATE PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) DURING AND AFTER APPLICATION UNLESS AIR MONITORING DEMONSTRATES VAPOR/ MIST LEVELS ARE BELOW APPLICABLE LEVELS.

REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING AND BEFORE EATING, DRINKING, CHEWING GUM, USING TOBACCO OR USING THE WASHROOM.

ENVIRONMENTAL HAZARDS

THIS MATERIAL IS TOXIC TO FISH. DO NOT APPLY DIRECTLY TO WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES. DO NOT ALLOW CHIPS AND DUST GENERATED DURING PAINT REMOVAL TO ENTER WATER. DISPOSE OF PAINT DEBRIS IN AN APPROVED LANDFILL

PHYSICAL OR CHEMICAL HAZARDS

FLAMMABLE. DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME.

FIRST AID

Table with 2 columns: Condition (IF IN EYES, IF SWALLOWED, IF ON SKIN OR CLOTHING, IF INHALED, OTHER) and First Aid instructions.

MEDICAL EMERGENCY NUMBER: 1-800-424-9300

NOTE TO PHYSICIAN
Contains petroleum distillate - vomiting may cause aspiration pneumonia.

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

ANTIFOULING FOR METAL BOTTOMS
TO CONTROL THE ATTACHMENT OF MARINE FOULING, IE. BARNACLES, GRASS, ALGAE, TUBE WORMS, MUSSELS, AND SNAILS ON HULLS OF BOATS AND VESSELS IN SALT, BRACKISH AND FRESH WATER WHICH WOULD SUSTAIN SUCH GROWTH. NOT RECOMMENDED FOR USE ON ALUMINUM. A MINIMUM OF TWO COATS OF THIS PRODUCT IS RECOMMENDED FOR BEST PERFORMANCE.

SURFACE PREPARATION
BEFORE APPLICATION OF ANTIFOULING, ALL SURFACES MUST BE DRY AND CLEANED OF DIRT, DUST, OIL, RUST, LOOSE PAINT, SALT RESIDUES AND OTHER CONTAMINANTS. STEEL MUST BE COATED WITH A SUITABLE PRIMER OR ANTI-CORROSIVE BARRIER COATS.

MIXING
BEFORE USE, POWER MIX OR BOX THE PAINT UNTIL THE PRODUCT IS UNIFORM. STIR THE PAINT AT INTERVALS DURING APPLICATION TO MAINTAIN UNIFORMITY.

APPLICATION
APPLY BY BRUSH, ROLL, OR SPRAY. CONTENTS MAY BE APPLIED BY HOT SPRAY (TEMPERATURES NOT TO EXCEED 95°F) AIRLESS SPRAY OR REGULAR COLD SPRAY. APPLY A FULL WET COAT IN A DOUBLE CROSSHATCH PATTERN. DO NOT PAINT IN COLD OR DAMP WEATHER.

THINNING
NORMALLY NO THINNING REQUIRED. WHERE THINNING IS NECESSARY, USE THINNER 7-T-33, XYLENE.

DRYING TIME
AT 70°F AND 50% R.H. ALLOW AT LEAST 4 HOURS DRY TIME BETWEEN COATS, AND A MINIMUM OF 8 HOURS BEFORE IMMERSION.

REFER TO PRODUCT MATERIAL SAFETY DATA BULLETIN, AVAILABLE UPON REQUEST, FOR FURTHER SAFETY AND HANDLING INFORMATION.

THE VOC OF THIS PAINT IS 330 GRAMS/LITER (2.75 LBS/GAL.)



LICENSED

PERIOD 2009-2011 LIC. NO.



LICENSED

PERIOD 2012-2014 LIC. NO.



LICENSED

PERIOD 2015-2017 LIC. NO.

8425.4

LOT# 51115935 DOM 09/25/2006

STORAGE AND DISPOSAL

DO NOT CONTAMINATE WATER, FOOD OR FEED BY STORAGE OR DISPOSAL. KEEP CONTAINER CLOSED WHEN NOT IN USE. IN CASE OF SPILLAGE, ABSORB WITH INERT MATERIAL AND DISPOSE OF IN ACCORDANCE WITH APPLICABLE REGULATIONS.

PESTICIDE DISPOSAL

PESTICIDE WASTES ARE TOXIC. IMPROPER DISPOSAL OF EXCESS PESTICIDE, SPRAY MIXTURE OR RINSATE IS A VIOLATION OF FEDERAL LAW. IF THESE WASTES CANNOT BE DISPOSED OF BY USE ACCORDING TO LABEL INSTRUCTIONS, CONTACT YOUR STATE PESTICIDE OR ENVIRONMENTAL CONTROL AGENCY, OR THE HAZARDOUS WASTE REPRESENTATIVE AT THE NEAREST EPA REGIONAL OFFICE FOR GUIDANCE.

CONTAINER DISPOSAL
NONREFILLABLE CONTAINER

DO NOT REUSE OR REFILL THIS CONTAINER. OFFER FOR RECYCLING IF AVAILABLE. TRIPLE RINSE CONTAINER PROMPTLY AFTER EMPTYING. TRIPLE RINSE AS FOLLOWS: EMPTY THE REMAINING CONTENTS INTO APPLICATION EQUIPMENT OR A MIX TANK AND DRAIN FOR 10 SECONDS AFTER THE FLOW BEGINS TO DRIP. FILL THE CONTAINER 1/10TH FULL WITH THINNER AND RECAP. SHAKE FOR 10 SECONDS. POUR RINSATE INTO APPLICATION EQUIPMENT OR A MIX TANK OR STORE RINSATE FOR LATER USE OR RECYCLING. DRAIN FOR 10 SECONDS AFTER THE FLOW BEGINS TO DRIP. REPEAT THIS PROCEDURE TWO MORE TIMES. THEN OFFER FOR RECYCLING OR RECONDITIONING, OR PUNCTURE AND DISPOSE OF IN A SANITARY LANDFILL, OR BY OTHER APPROVED STATE AND LOCAL PROCEDURES.

Table with 2 columns: Hazard Type, Rating. Health: 3, Fire hazard: 3, Reactivity: 1, Protective Equipment: C

D.O.T. SHIPPING NAME: PAINT
D.O.T. HAZARD CLASS: FLAMMABLE LIQUID
D.O.T. HAZARD IDENTIFICATION NUMBER: UN1263

3GEGRN

E.P.A. REG. NO.: 2568-93
E.P.A. EST. NO.: 002568-LA-001

Jotun Paints, Inc.
9203 Highway 23
Belle Chasse, LA 70037

ANTIFOULING
SEAFORCE 200 AV
GREEN
3GEGRN

ACTIVE INGREDIENT: CUPROUS OXIDE.....44.59%*
INERT INGREDIENTS.....55.41%**
.....100.00%

* METALLIC COPPER EQUIVALENT: 39.60%
** CONTAINS PETROLEUM DISTILLATES, XYLENE, OR XYLENE RANGE AROMATIC SOLVENTS

KEEP OUT OF THE REACH OF CHILDREN.

WARNING

FOR COMMERCIAL USE ONLY. DO NOT USE IN OR AROUND A HOUSEHOLD OR DWELLING.

NOT SOLD FOR USE IN AIR POLLUTION REGULATION AREAS.
PHOTOCHEMICALLY REACTIVE PER RULE 102

SEE SIDE PANEL FOR FIRST AID AND ADDITIONAL PRECAUTIONARY STATEMENTS

Net 5 Gallons (18.925 liters)

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS & DOMESTIC ANIMALS

WARNING

CAUSES EYE IRRITATION.
HARMFUL IF ABSORBED THROUGH SKIN.

AVOID CONTACT WITH EYES, SKIN AND CLOTHING. WEAR PROTECTIVE CLOTHING SUCH AS GLOVES, LONG-SLEEVED COTTON SHIRT, LONG PANTS, AND HAT. MAY BE FATAL IF SWALLOWED OR INHALED. DO NOT BREATHE VAPORS OR SPRAY MIST. WHEN USED IN ENCLOSED AREAS, SPRAYING PAINT OR SANDING BOAT SURFACE. WEAR APPROPRIATE PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) DURING AND AFTER APPLICATION UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS ARE BELOW APPLICABLE LEVELS.

REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING AND BEFORE EATING, DRINKING, CHEWING GUM, USING TOBACCO OR USING THE WASHROOM.

ENVIRONMENTAL HAZARDS

THIS MATERIAL IS TOXIC TO FISH. DO NOT APPLY DIRECTLY TO WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES. DO NOT ALLOW CHIPS AND DUST GENERATED DURING PAINT REMOVAL TO ENTER WATER. DISPOSE OF PAINT DEBRIS IN AN APPROVED LANDFILL

PHYSICAL OR CHEMICAL HAZARDS

FLAMMABLE. DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME.

Table with 2 columns: Exposure Type, First Aid Instructions. Includes sections for IF IN EYES, IF SWALLOWED, IF ON SKIN OR CLOTHING, IF INHALED, OTHER, MEDICAL EMERGENCY NUMBER, and NOTE TO PHYSICIAN.

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

ANTIFOULING FOR METAL BOTTOMS
TO CONTROL THE ATTACHMENT OF MARINE FOULING, IE. BARNACLES, GRASS, ALGAE, TUBE WORMS, MUSSELS, AND SNAILS ON HULLS OF BOATS AND VESSELS IN SALT, BRACKISH AND FRESH WATER WHICH WOULD SUSTAIN SUCH GROWTH. NOT RECOMMENDED FOR USE ON ALUMINUM. A MINIMUM OF TWO COATS OF THIS PRODUCT IS RECOMMENDED FOR BEST PERFORMANCE.

SURFACE PREPARATION
BEFORE APPLICATION OF ANTIFOULING, ALL SURFACES MUST BE DRY AND CLEANED OF DIRT, DUST, OIL, RUST, LOOSE PAINT, SALT RESIDUES AND OTHER CONTAMINANTS. STEEL MUST BE COATED WITH A SUITABLE PRIMER OR ANTI-CORROSSIVE BARRIER COATS.

MIXING
BEFORE USE, POWER MIX OR BOX THE PAINT UNTIL THE PRODUCT IS UNIFORM. STIR THE PAINT AT INTERVALS DURING APPLICATION TO MAINTAIN UNIFORMITY.

APPLICATION
APPLY BY BRUSH, ROLL, OR SPRAY. CONTENTS MAY BE APPLIED BY HOT SPRAY (TEMPERATURES NOT TO EXCEED 99°F) AIRLESS SPRAY OR REGULAR COLD SPRAY. APPLY A FULL WET COAT IN A DOUBLE CROSSHATCH PATTERN. DO NOT PAINT IN COLD OR DAMP WEATHER.

THINNING
NORMALLY NO THINNING REQUIRED. WHERE THINNING IS NECESSARY, USE THINNER 7-T-33, XYLENE.

DRYING TIME
AT 70°F AND 50% R.H. ALLOW AT LEAST 4 HOURS DRY TIME BETWEEN COATS, AND A MINIMUM OF 8 HOURS BEFORE IMMERSION.

REFER TO PRODUCT MATERIAL SAFETY DATA BULLETIN, AVAILABLE UPON REQUEST, FOR FURTHER SAFETY AND HANDLING INFORMATION.

THE VOC OF THIS PAINT IS 330 GRAMS/LITER (2.75 LBS/GAL.)



LICENSED

PERIOD 2009-2011 LIC. NO.

LICENSED

PERIOD 2012-2014 LIC. NO.



LICENSED

PERIOD 2015-2017 LIC. NO.



LICENSED

8425.4

LOT# 51121249 DOM 07/30/2008

Health	3
Fire hazard	3
Reactivity	1
Protective Equipment	C

STORAGE AND DISPOSAL

DO NOT CONTAMINATE WATER, FOOD OR FEED BY STORAGE OR DISPOSAL. KEEP CONTAINER CLOSED WHEN NOT IN USE. IN CASE OF SPILLAGE, ABSORB WITH INERT MATERIAL AND DISPOSE OF IN ACCORDANCE WITH APPLICABLE REGULATIONS.

PESTICIDE DISPOSAL

PESTICIDE WASTES ARE TOXIC. IMPROPER DISPOSAL OF EXCESS PESTICIDE, SPRAY MIXTURE OR RINSATE IS A VIOLATION OF FEDERAL LAW. IF THESE WASTES CANNOT BE DISPOSED OF BY USE ACCORDING TO LABEL INSTRUCTIONS, CONTACT YOUR STATE PESTICIDE OR ENVIRONMENTAL CONTROL AGENCY, OR THE HAZARDOUS WASTE REPRESENTATIVE AT THE NEAREST EPA REGIONAL OFFICE FOR GUIDANCE.

CONTAINER DISPOSAL

DO NOT REUSE OR REFILL THIS CONTAINER. OFFER FOR RECYCLING IF AVAILABLE. TRIPLE RINSE CONTAINER PROMPTLY AFTER EMPTYING. TRIPLE RINSE AS FOLLOWS: EMPTY THE REMAINING CONTENTS INTO APPLICATION EQUIPMENT OR A MIX TANK AND DRAIN FOR 10 SECONDS AFTER THE FLOW BEGINS TO DRIP. FILL THE CONTAINER 1/10th FULL WITH THINNER AND RECAP. SHAKE FOR 10 SECONDS. POUR RINSATE INTO APPLICATION EQUIPMENT OR A MIX TANK OR STORE RINSATE FOR LATER USE OR RECYCLING. DRAIN FOR 10 SECONDS AFTER THE FLOW BEGINS TO DRIP. REPEAT THIS PROCEDURE TWO MORE TIMES. THEN OFFER FOR RECYCLING OR RECONDITIONING, OR PUNCTURE AND DISPOSE OF IN A SANITARY LANDFILL, OR BY OTHER APPROVED STATE AND LOCAL PROCEDURES.

D.O.T. SHIPPING NAME: PAINT
D.O.T. HAZARD CLASS: FLAMMABLE LIQUID
D.O.T. HAZARD IDENTIFICATION NUMBER: UN1263

3GELRD

E.P.A. REG. NO.: 2568-93
E.P.A. EST. NO.: 002568-LA-001

Jotun Paints, Inc.
9203 Highway 23
Belle Chasse, LA 70037

ANTIFOULING
SEAFORCE 200 AV
LIGHT RED
3GELRD

ACTIVE INGREDIENT: CUPROUS OXIDE.....44.59%*
INERT INGREDIENTS.....55.41%**
.....100.00%

* METALLIC COPPER EQUIVALENT: 39.60%
** CONTAINS PETROLEUM DISTILLATES, XYLENE, OR XYLENE RANGE AROMATIC SOLVENTS

KEEP OUT OF THE REACH OF CHILDREN.

WARNING

FOR COMMERCIAL USE ONLY. DO NOT USE IN OR AROUND A HOUSEHOLD OR DWELLING.

NOT SOLD FOR USE IN AIR POLLUTION REGULATION AREAS.
PHOTOCHEMICALLY REACTIVE PER RULE 102

SEE SIDE PANEL FOR FIRST AID AND ADDITIONAL PRECAUTIONARY STATEMENTS

Net 3.785 Liters (1 gallons)
3GELRDDSJ

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS & DOMESTIC ANIMALS

WARNING

CAUSES EYE IRRITATION.
HARMFUL IF ABSORBED THROUGH SKIN.

AVOID CONTACT WITH EYES, SKIN AND CLOTHING. WEAR PROTECTIVE CLOTHING SUCH AS GLOVES, LONG-SLEEVED COTTON SHIRT, LONG PANTS, AND HAT. MAY BE FATAL IF SWALLOWED OR INHALED. DO NOT BREATHE VAPORS OR SPRAY MIST. WHEN USED IN ENCLOSED AREAS, SPRAYING PAINT OR SANDING BOAT SURFACE. WEAR APPROPRIATE PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) DURING AND AFTER APPLICATION UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS ARE BELOW APPLICABLE LEVELS.

REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING AND BEFORE EATING, DRINKING, CHEWING GUM, USING TOBACCO OR USING THE WASHROOM.

ENVIRONMENTAL HAZARDS

THIS MATERIAL IS TOXIC TO FISH. DO NOT APPLY DIRECTLY TO WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES. DO NOT ALLOW CHIPS AND DUST GENERATED DURING PAINT REMOVAL TO ENTER WATER. DISPOSE OF PAINT DEBRIS IN AN APPROVED LANDFILL

PHYSICAL OR CHEMICAL HAZARDS

FLAMMABLE. DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME.

FIRST AID

IF IN EYES:	HOLD EYE OPEN AND RINSE SLOWLY AND GENTLY FOR 15-20 MINUTES. REMOVE CONTACT LENSES, IF PRESENT, AFTER THE FIRST 5 MINUTES, AND THEN CONTINUE RINSING. CALL A POISON CONTROL CENTER OR DOCTOR FOR TREATMENT ADVICE.
IF SWALLOWED:	IMMEDIATELY CALL A POISON CONTROL CENTER OR DOCTOR. DO NOT INDUCE VOMITING UNLESS TOLD TO DO SO BY A POISON CONTROL CENTER OR DOCTOR. DO NOT GIVE ANY LIQUID TO THE PERSON. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
IF ON SKIN OR CLOTHING:	TAKE OFF CONTAMINATED CLOTHING. RINSE SKIN IMMEDIATELY WITH PLENTY OF WATER FOR 15-20 MINUTES. CALL A POISON CONTROL CENTER OR DOCTOR FOR TREATMENT ADVICE.
IF INHALED:	MOVE PERSON TO FRESH AIR. IF PERSON IS NOT BREATHING, CALL 911 OR AN AMBULANCE, THEN GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH-TO-MOUTH IF POSSIBLE. CALL A POISON CONTROL CENTER OR DOCTOR FOR FURTHER TREATMENT ADVICE.
OTHER:	HAVE THE PRODUCT CONTAINER OR LABEL WITH YOU WHEN CALLING A POISON CONTROL CENTER OR DOCTOR, OR GOING FOR TREATMENT.

MEDICAL EMERGENCY NUMBER: 1-800-424-9300

NOTE TO PHYSICIAN
Contains petroleum distillate - vomiting may cause aspiration pneumonia.

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

ANTIFOULING FOR METAL BOTTOMS
TO CONTROL THE ATTACHMENT OF MARINE FOULING, IE. BARNACLES, GRASS, ALGAE, TUBE WORMS, MUSSELS, AND SNAILS ON HULLS OF BOATS AND VESSELS IN SALT, BRACKISH AND FRESH WATER WHICH WOULD SUSTAIN SUCH GROWTH. NOT RECOMMENDED FOR USE ON ALUMINUM. A MINIMUM OF TWO COATS OF THIS PRODUCT IS RECOMMENDED FOR BEST PERFORMANCE.

SURFACE PREPARATION

BEFORE APPLICATION OF ANTIFOULING, ALL SURFACES MUST BE DRY AND CLEANED OF DIRT, DUST, OIL, RUST, LOOSE PAINT, SALT RESIDUES AND OTHER CONTAMINANTS. STEEL MUST BE COATED WITH A SUITABLE PRIMER OR ANTI-CORROSIVE BARRIER COATS.

MIXING

BEFORE USE, POWER MIX OR BOX THE PAINT UNTIL THE PRODUCT IS UNIFORM. STIR THE PAINT AT INTERVALS DURING APPLICATION TO MAINTAIN UNIFORMITY.

APPLICATION

APPLY BY BRUSH, ROLL, OR SPRAY. CONTENTS MAY BE APPLIED BY HOT SPRAY (TEMPERATURES NOT TO EXCEED 95°F) AIRLESS SPRAY OR REGULAR COLD SPRAY. APPLY A FULL WET COAT IN A DOUBLE CROSSHATCH PATTERN. DO NOT PAINT IN COLD OR DAMP WEATHER.

THINNING

NORMALLY NO THINNING REQUIRED. WHERE THINNING IS NECESSARY, USE THINNER 7-T-33, XYLENE.

DRYING TIME

AT 70°F AND 50% R.H. ALLOW AT LEAST 4 HOURS DRY TIME BETWEEN COATS, AND A MINIMUM OF 8 HOURS BEFORE IMMERSION.

REFER TO PRODUCT MATERIAL SAFETY DATA BULLETIN, AVAILABLE UPON REQUEST, FOR FURTHER SAFETY AND HANDLING INFORMATION.

THE VOC OF THIS PAINT IS 330 GRAMS/LITER (2.75 LBS/GAL).