



LICENSED

PERIOD 2009-2011 LIC. NO.



LICENSED

PERIOD 2012-2014 LIC. NO.



LICENSED

PERIOD 2015-2017 LIC. NO.

8425.5

BATCH 51121909 D O M 08/19/2008

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS & DOMESTIC ANIMALS

STORAGE AND DISPOSAL

Health	3
Fire hazard	3
Reactivity	1
Protective Equipment	X

DO NOT CONTAMINATE WATER, FOOD OR FEED BY STORAGE OR DISPOSAL. KEEP CONTAINER CLOSED WHEN NOT IN USE. IN CASE OF SPILLAGE, ABSORB WITH INERT MATERIAL AND DISPOSE OF IN ACCORDANCE WITH APPLICABLE REGULATIONS

PESTICIDE DISPOSAL
PESTICIDE WASTES ARE TOXIC. IMPROPER DISPOSAL OF EXCESS PESTICIDE, SPRAY MIXTURE OR RINSATE IS A VIOLATION OF FEDERAL LAW. IF THESE WASTES CANNOT BE DISPOSED OF BY USER ACCORDING TO LABEL INSTRUCTIONS, CONTACT YOUR STATE PESTICIDE OR ENVIRONMENTAL CONTROL AGENCY, OR THE HAZARDOUS WASTE REPRESENTATIVE AT THE NEAREST EPA REGIONAL OFFICE FOR GUIDANCE.

CONTAINER DISPOSAL
NONREFILLABLE CONTAINER

DO NOT REUSE OR REFILL THIS CONTAINER. OFFER FOR RECYCLING IF AVAILABLE. TRIPLE RINSE CONTAINER PROMPTLY AFTER EMPTYING. TRIPLE RINSE AS FOLLOWS: EMPTY THE REMAINING CONTENTS INTO APPLICATION EQUIPMENT OR A MIX TANK AND DRAIN FOR 10 SECONDS AFTER THE FLOW BEGINS TO DRIP. FILL THE CONTAINER 1/10TH FULL WITH THINNER AND RECAP. SHAKE FOR 10 SECONDS. POUR RINSATE INTO APPLICATION EQUIPMENT OR A MIX TANK OR STORE RINSATE FOR LATER USE OR RECYCLING. DRAIN FOR 10 SECONDS AFTER THE FLOW BEGINS TO DRIP. REPEAT THIS PROCEDURE TWO MORE TIMES. THEN OFFER FOR RECYCLING OR RECONDITIONING, OR PUNCTURE AND DISPOSE OF IN A SANITARY LANDFILL, OR BY OTHER APPROVED STATE AND LOCAL PROCEDURES.

D.O.T. SHIPPING NAME: PAINT

D.O.T. HAZARD CLASS: FLAMMABLE LIQUID

D.O.T. HAZARD IDENTIFICATION NUMBER: UN1263

3GFDRD

E.P.A. REG. NO.: 2568-99
E.P.A. EST. NO.: 002568-LA-001

Jotun Paints, Inc.
9203 Highway 23
Belle Chasse, LA 70037

ANTIFOULING SEAFORCE 300 AV DARK RED 3GFDRD

ACTIVE INGREDIENT: CUPROUS OXIDE.....39.59%
ACTIVE INGREDIENT: 4, 5-DICHLORO-2-N-OCTYL-4-ISOTHIAZOLIN-3-ONE.....2.19%
INERT INGREDIENTS.....58.22%
.....100.00%

- * METALLIC COPPER EQUIVALENT: 35.16%
- ** CONTAINS PETROLEUM DISTILLATES, XYLENE, OR XYLENE RANGE AROMATIC SOLVENTS

KEEP OUT OF THE REACH OF CHILDREN.

DANGER

FOR USE IN COMMERCIAL OR GOVERNMENT SHIPYARDS ONLY. NOT FOR USE BY PRIVATE APPLICATORS OR MARINAS. NOT FOR USE ON STATIONARY STRUCTURES

NOT SOLD FOR USE IN AIR POLLUTION REGULATION AREAS.
PHOTOCHEMICALLY REACTIVE PER RULE 102

SEE FIRST AID AND OTHER PRECAUTIONS ON SIDE PANEL.

NET 20 LITERS (5.284 GALLONS)
3GFLRDWVA

DANGER

CORROSIVE. CAUSES IRREVERSIBLE EYE DAMAGE. HARMFUL IF SWALLOWED OR ABSORBED THROUGH SKIN. AVOID CONTACT WITH EYES, SKIN, OR CLOTHING. WEAR A FULL FACE SHIELD. AVOID BREATHING VAPOR, MIST, DUST OR CHIPS FROM PAINTING OR SANDING WHILE SPRAYING PAINT OR SANDING BOAT SURFACE. WEAR A SUPPLIED-AIR OR POWERED AIR PURIFYING RESPIRATOR (PAPR) APPROVED BY NIOSH FOR USE WITH PAINTS AND COATINGS.

WEAR A TYVEK HOODED COVERALL OR THE EXACT EQUIVALENT, COVERALLS BENEATH THE TYVEK HOODED COVERALLS, IMPERVIOUS GLOVES AND IMPERVIOUS FOOTWEAR THAT PROTECTS THE LOWER LEG. REMOVE CONTAMINATED CLOTHING AND DISCARD AFTER EACH USE. DO NOT REUSE. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING AND BEFORE EATING OR SMOKING

ENVIRONMENTAL HAZARDS

THIS PESTICIDE IS TOXIC TO FISH AND AQUATIC INVERTEBRATES. DO NOT DISCHARGE EFFLUENT CONTAINING THIS PRODUCT INTO LAKES, STREAMS, PONDS, ESTUARIES, OCEANS OR OTHER WATER UNLESS IN ACCORDANCE WITH THE REQUIREMENTS OF A NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM (NPDES) PERMIT AND THE PERMITTING AUTHORITY HAS BEEN NOTIFIED IN WRITING PRIOR TO DISCHARGE. DO NOT DISCHARGE EFFLUENT CONTAINING THIS PRODUCT TO SEWER SYSTEMS WITHOUT PREVIOUSLY NOTIFYING THE LOCAL SEWAGE TREATMENT PLANT AUTHORITY. FOR GUIDANCE CONTACT YOUR STATE WATER BOARD OR REGIONAL OFFICES OF THE EPA. DO NOT APPLY DIRECTLY TO WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES. DO NOT ALLOW CHIPS AND DUST GENERATED DURING PAINT REMOVAL TO ENTER WATER. DISPOSE OF PAINT DEBRIS IN AN APPROVED LANDFILL. WEAR PROTECTIVE CLOTHING AND SUPPLIED AIR RESPIRATOR IN ACCORDANCE WITH THE PRECAUTIONARY STATEMENTS ABOVE WHEN HANDLING, PAINTING OR REMOVING THIS PAINT.

PHYSICAL OR CHEMICAL HAZARDS

COMBUSTIBLE. DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME

FIRST AID	
IF IN EYES:	HOLD EYES OPEN AND RINSE SLOWLY AND GENTLY FOR 15-20 MINUTES. REMOVE CONTACT LENSES, IF PRESENT, AFTER THE FIRST 5 MINUTES, AND THEN CONTINUE RINSING. CALL A POISON CONTROL CENTER OR DOCTOR FOR TREATMENT ADVICE.
IF SWALLOWED:	IMMEDIATELY CALL A POISON CONTROL CENTER OR DOCTOR. DO NOT INDUCE VOMITING UNLESS TOLD TO DO SO BY A POISON CONTROL CENTER OR DOCTOR. DO NOT GIVE ANY LIQUID TO THE PERSON. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
IF ON SKIN OR CLOTHING:	TAKE OFF CONTAMINATED CLOTHING. RINSE SKIN IMMEDIATELY WITH PLENTY OF WATER FOR 15-20 MINUTES. CALL A POISON CONTROL CENTER OR DOCTOR FOR TREATMENT ADVICE.
IF INHALED:	MOVE A PERSON TO FRESH AIR. IF PERSON IS NOT BREATHING, CALL 911 OR AN AMBULANCE, THEN GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH-TO-MOUTH IF POSSIBLE. CALL A POISON CONTROL CENTER OR DOCTOR FOR FURTHER TREATMENT ADVICE.
OTHER:	HAVE THE PRODUCT CONTAINER OR LABEL WITH YOU WHEN CALLING A POISON CONTROL CENTER OR DOCTOR, OR GOING FOR TREATMENT.
MEDICAL EMERGENCY NUMBER: 1-800-424-9300	
NOTE TO PHYSICIAN Contains petroleum distillate - vomiting may cause aspiration pneumonia.	

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

ANTIFOULING FOR METAL BOTTOMS

TO CONTROL THE ATTACHMENT OF MARINE FOULING, IE, BARNACLES, GRASS, ALGAE, TUBE WORMS, MUSSELS, AND SNAILS ON HULLS OF BOATS AND VESSELS IN SALT, BRACKISH AND FRESH WATER WHICH WOULD SUSTAIN SUCH GROWTH. WHEN USED ON ALUMINUM HULLS, A BARRIER COAT OF TWO COATS OF EPOXY COATING ATTAINING AT LEAST 12 MILS DFT MUST BE APPLIED FIRST. CONSULT WITH YOUR REPRESENTATIVE FOR SPECIFIC BARRIER RECOMMENDATIONS. A MINIMUM OF TWO COATS OF THIS PRODUCT IS RECOMMENDED FOR BEST PERFORMANCE. THIS PRODUCT IS NOT FOR USE ON PLEASURE CRAFTS OR USE IN MARINAS.

SURFACE PREPARATION

BEFORE APPLICATION OF ANTIFOULING, ALL SURFACES MUST BE DRY AND CLEANED OF DIRT, DUST, OIL, RUST, LOOSE PAINT, SALT RESIDUES AND OTHER CONTAMINANTS. STEEL MUST BE COATED WITH A SUITABLE PRIMER OR ANTI-CORROSIVE BARRIER COATS.

MIXING

BEFORE USE, POWER MIX OR BOX THE PAINT UNTIL THE PRODUCT IS UNIFORM. STIR THE PAINT AT INTERVALS DURING APPLICATION TO MAINTAIN UNIFORMITY.

APPLICATION

APPLY BY BRUSH, ROLL, OR SPRAY. CONTENTS MAY BE APPLIED BY HOT SPRAY (TEMPERATURES NOT TO EXCEED 95°F) AIRLESS SPRAY OR REGULAR COLD SPRAY. APPLY A FULL WET COAT IN A DOUBLE CROSSHATCH PATTERN. DO NOT PAINT IN COLD OR DAMP WEATHER.

THINNING

NORMALLY NO THINNING REQUIRED. WHERE THINNING NECESSARY, USE THINNER NO. 7 XYLENE.

DRYING TIME

AT 70°F AND 50% R.H. ALLOW AT LEAST 4 HOURS DRY TIME BETWEEN COATS, AND A MINIMUM OF 8 HOURS BEFORE IMMERSION.

REFER TO PRODUCT MATERIAL SAFETY DATA BULLETIN, AVAILABLE UPON REQUEST, FOR FURTHER SAFETY AND HANDLING INFORMATION

**THE VOC OF THIS PAINT IS
396 GRAMS/LITER (3.3 LBS.
/GAL.).**



LICENSED

PERIOD 2009-2011 LIC. NO.



LICENSED

PERIOD 2012-2014 LIC. NO.



Department of Agriculture
STATE OF HAWAII

LICENSED 8425.5

PERIOD 2015-2017 LIC. NO.

BATCH 51121909 D O M 08/19/2008

Health	3
Fire hazard	3
Reactivity	1
Protective Equipment	x

D.O.T. SHIPPING NAME: PAINT
 D.O.T. HAZARD CLASS: FLAMMABLE LIQUID
 D.O.T. HAZARD IDENTIFICATION NUMBER: UN1263
 3GFLRD
 E.P.A. REG. NO.: 2568-99
 E.P.A. EST. NO.: 002568-LA-001

Jotun Paints, Inc.
 9203 Highway 23
 Belle Chasse, LA 70037

STORAGE AND DISPOSAL

DO NOT CONTAMINATE WATER, FOOD OR FEED BY STORAGE OR DISPOSAL. KEEP CONTAINER CLOSED WHEN NOT IN USE. IN CASE OF SPILLAGE, ABSORB WITH INERT MATERIAL AND DISPOSE OF IN ACCORDANCE WITH APPLICABLE REGULATIONS

PESTICIDE DISPOSAL

PESTICIDE WASTES ARE TOXIC. IMPROPER DISPOSAL OF EXCESS PESTICIDE, SPRAY MIXTURE OR RINSATE IS A VIOLATION OF FEDERAL LAW. IF THESE WASTES CANNOT BE DISPOSED OF BY USER ACCORDING TO LABEL INSTRUCTIONS, CONTACT YOUR STATE PESTICIDE OR ENVIRONMENTAL CONTROL AGENCY, OR THE HAZARDOUS WASTE REPRESENTATIVE AT THE NEAREST EPA REGIONAL OFFICE FOR GUIDANCE.

CONTAINER DISPOSAL
NONREFILLABLE CONTAINER

DO NOT REUSE OR REFILL THIS CONTAINER. OFFER FOR RECYCLING IF AVAILABLE. TRIPLE RINSE CONTAINER PROMPTLY AFTER EMPTYING. TRIPLE RINSE AS FOLLOWS: EMPTY THE REMAINING CONTENTS INTO APPLICATION EQUIPMENT OR A MIX TANK AND DRAIN FOR 10 SECONDS AFTER THE FLOW BEGINS TO DRIP. FILL THE CONTAINER 1/10TH FULL WITH THINNER AND RECAP. SHAKE FOR 10 SECONDS. POUR RINSATE INTO APPLICATION EQUIPMENT OR A MIX TANK OR STORE RINSATE FOR LATER USE OR RECYCLING. DRAIN FOR 10 SECONDS AFTER THE FLOW BEGINS TO DRIP. REPEAT THIS PROCEDURE TWO MORE TIMES. THEN OFFER FOR RECYCLING OR RECONDITIONING, OR PUNCTURE AND DISPOSE OF IN A SANITARY LANDFILL, OR BY OTHER APPROVED STATE AND LOCAL REGULATIONS

ANTIFOULING SEAFORCE 300 AV LIGHT RED 3GFLRD

ACTIVE INGREDIENT: CUPROUS OXIDE.....39.59%
 ACTIVE INGREDIENT: 4, 5-DICHLORO-2-N-OCTYL-4-ISOTHIAZOLIN-3-ONE.....2.19%
 INERT INGREDIENTS.....58.22%
100.00%

- * METALLIC COPPER EQUIVALENT: 35.16%
- ** CONTAINS PETROLEUM DISTILLATES, XYLENE, OR XYLENE RANGE AROMATIC SOLVENTS

KEEP OUT OF THE REACH OF CHILDREN.

DANGER

FOR USE IN COMMERCIAL OR GOVERNMENT SHIPYARDS ONLY. NOT FOR USE BY PRIVATE APPLICATORS OR MARINAS. NOT FOR USE ON STATIONARY STRUCTURES

NOT SOLD FOR USE IN AIR POLLUTION REGULATION AREAS.
 PHOTOCHEMICALLY REACTIVE PER RULE 102

SEE FIRST AID AND OTHER PRECAUTIONS ON SIDE PANEL.

NET 20 LITERS (5.284 GALLONS)
3GFLRDWVA

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS & DOMESTIC ANIMALS
DANGER

CORROSIVE. CAUSES IRREVERSIBLE EYE DAMAGE. HARMFUL IF SWALLOWED OR ABSORBED THROUGH SKIN. AVOID CONTACT WITH EYES, SKIN, OR CLOTHING. WEAR A FULL FACE SHIELD. AVOID BREATHING VAPOR, MIST, DUST OR CHIPS FROM PAINTING OR SANDING WHILE SPRAYING PAINT OR SANDING BOAT SURFACE. WEAR A SUPPLIED-AIR OR POWERED AIR PURIFYING RESPIRATOR (PAPR) APPROVED BY NIOSH FOR USE WITH PAINTS AND COATINGS.

WEAR A TYVEK HOODED COVERALL OR THE EXACT EQUIVALENT, COVERALLS BENEATH THE TYVEK HOODED COVERALLS, IMPERVIOUS GLOVES AND IMPERVIOUS FOOTWEAR THAT PROTECTS THE LOWER LEG. REMOVE CONTAMINATED CLOTHING AND DISCARD AFTER EACH USE. DO NOT REUSE. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING AND BEFORE EATING OR SMOKING

ENVIRONMENTAL HAZARDS

THIS PESTICIDE IS TOXIC TO FISH AND AQUATIC INVERTEBRATES. DO NOT DISCHARGE EFFLUENT CONTAINING THIS PRODUCT INTO LAKES, STREAMS, PONDS, ESTUARIES, OCEANS OR OTHER WATER UNLESS IN ACCORDANCE WITH THE REQUIREMENTS OF A NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM (NPDES) PERMIT AND THE PERMITTING AUTHORITY HAS BEEN NOTIFIED IN WRITING PRIOR TO DISCHARGE. DO NOT DISCHARGE EFFLUENT CONTAINING THIS PRODUCT TO SEWER SYSTEMS WITHOUT PREVIOUSLY NOTIFYING THE LOCAL SEWAGE TREATMENT PLANT AUTHORITY. FOR GUIDANCE CONTACT YOUR STATE WATER BOARD OR REGIONAL OFFICES OF THE EPA. DO NOT APPLY DIRECTLY TO WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES. DO NOT ALLOW CHIPS AND DUST GENERATED DURING PAINT REMOVAL TO ENTER WATER. DISPOSE OF PAINT DEBRIS IN AN APPROVED LANDFILL. WEAR PROTECTIVE CLOTHING AND SUPPLIED AIR RESPIRATOR IN ACCORDANCE WITH THE PRECAUTIONARY STATEMENTS ABOVE WHEN HANDLING, PAINTING OR REMOVING THIS PAINT.

PHYSICAL OR CHEMICAL HAZARDS

COMBUSTIBLE. DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME

FIRST AID	
IF IN EYES:	HOLD EYES OPEN AND RINSE SLOWLY AND GENTLY FOR 15-20 MINUTES. REMOVE CONTACT LENSES, IF PRESENT, AFTER THE FIRST 5 MINUTES, AND THEN CONTINUE RINSING. CALL A POISON CONTROL CENTER OR DOCTOR FOR TREATMENT ADVICE.
IF SWALLOWED:	IMMEDIATELY CALL A POISON CONTROL CENTER OR DOCTOR. DO NOT INDUCE VOMITING UNLESS TOLD TO DO SO BY A POISON CONTROL CENTER OR DOCTOR. DO NOT GIVE ANY LIQUID TO THE PERSON. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
IF ON SKIN OR CLOTHING:	TAKE OFF CONTAMINATED CLOTHING. RINSE SKIN IMMEDIATELY WITH PLENTY OF WATER FOR 15-20 MINUTES. CALL A POISON CONTROL CENTER OR DOCTOR FOR TREATMENT ADVICE.
IF INHALED:	MOVE A PERSON TO FRESH AIR. IF PERSON IS NOT BREATHING, CALL 911 OR AN AMBULANCE, THEN GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH-TO-MOUTH IF POSSIBLE. CALL A POISON CONTROL CENTER OR DOCTOR FOR FURTHER TREATMENT ADVICE.
OTHER:	HAVE THE PRODUCT CONTAINER OR LABEL WITH YOU WHEN CALLING A POISON CONTROL CENTER OR DOCTOR, OR GOING FOR TREATMENT.
MEDICAL EMERGENCY NUMBER: 1-800-424-9300	
NOTE TO PHYSICIAN Contains petroleum distillate -- vomiting may cause aspiration pneumonia.	

DIRECTIONS FOR USE
IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

ANTIFOULING FOR METAL BOTTOMS
TO CONTROL THE ATTACHMENT OF MARINE FOULING, IE. BARNACLES, GRASS, ALGAE, TUBE WORMS, MUSSELS, AND SNAILS ON HULLS OF BOATS AND VESSELS IN SALT, BRACKISH AND FRESH WATER WHICH WOULD SUSTAIN SUCH GROWTH. WHEN USED ON ALUMINUM HULLS, A BARRIER COAT OF TWO COATS OF EPOXY COATING ATTAINING AT LEAST 12 MILS DFT MUST BE APPLIED FIRST. CONSULT WITH YOUR REPRESENTATIVE FOR SPECIFIC BARRIER RECOMMENDATIONS. A MINIMUM OF TWO COATS OF THIS PRODUCT IS RECOMMENDED FOR BEST PERFORMANCE. THIS PRODUCT IS NOT FOR USE ON PLEASURE CRAFTS OR USE IN MARINAS.

SURFACE PREPARATION

BEFORE APPLICATION OF ANTI-FOULING, ALL SURFACES MUST BE DRY AND CLEANED OF DIRT, DUST, OIL, RUST, LOOSE PAINT, SALT RESIDUES AND OTHER CONTAMINANTS. STEEL MUST BE COATED WITH A SUITABLE PRIMER OR ANTI-CORROSIVE BARRIER COATS.

MIXING

BEFORE USE, POWER MIX OR BOX THE PAINT UNTIL THE PRODUCT IS UNIFORM. STIR THE PAINT AT INTERVALS DURING APPLICATION TO MAINTAIN UNIFORMITY.

APPLICATION

APPLY BY BRUSH, ROLL, OR SPRAY. CONTENTS MAY BE APPLIED BY HOT SPRAY (TEMPERATURES NOT TO EXCEED 95°F) AIRLESS SPRAY OR REGULAR COLD SPRAY. APPLY A FULL WET COAT IN A DOUBLE CROSSHATCH PATTERN. DO NOT PAINT IN COLD OR DAMP WEATHER.

THINNING

NORMALLY NO THINNING REQUIRED. WHERE THINNING NECESSARY, USE THINNER NO. 7 XYLENE.

DRYING TIME

AT 70°F AND 50% R.H. ALLOW AT LEAST 4 HOURS DRY TIME BETWEEN COATS, AND A MINIMUM OF 8 HOURS BEFORE IMMERSION.

REFER TO PRODUCT MATERIAL SAFETY DATA BULLETIN, AVAILABLE UPON REQUEST, FOR FURTHER SAFETY AND HANDLING INFORMATION

THE VOC OF THIS PAINT IS
396 GRAMS/LITER (3.3 LBS./GAL.).