DISCONTINUED

POOL CARE SYSTEM
KEM-TEK™
Kemex™ ALL-IN-ONE

Stabilized Chlorinating Granules

For Control Of Algae & Bacteria
Fast Acting Daily & Super Chlorination

ACTIVE INGREDIENT:
Sodium Dichloro-s-triazinetrione-Dihydrate...99.0%
INERT INGREDIENTS.....1.0%

Net Wt. 4 Lbs. (1.81 Kg.)

KEEP OUT OF REACH OF CHILDREN
NO SE DEJE AL ALCANCE DE LOS NIÑOS

DANGER
PELIGRO

See back panel for first aid statement and other precautions

Free Pool Care Advice
1-800-SOS-POOL · www.kem-tek.com

Pesticide Disposal: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or Hazardous Waste Representative at the EPA Regional Office for guidance.

Container Disposal: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

NOTE: Do not allow direct contact of this product on thefollowing pool surfaces: vinyl, metallic, fiberglass, painted or colored plaster. Product will bleach color out.

EPA Reg. No. 7615-70
EPA Est. No. 7616-CA-1

Manufactured By
CHEM LAB PRODUCTS, INC.
Ontario, California 91761

Made in USA

SAVE A CHILD
FENCE THE POOL

Product #006

0 41596 00002 9

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

DANGER: Never mix this concentrated chemical with any other substance except generous amounts of water. See CHEMICAL HAZARDS on this label.

The use of KEM-TEK™ ALL-IN-ONE STABILIZED CHLORINATING GRANULES also requires the one time use of KEM TEK™ STABILIZER CONDITIONER as described in the directions below under Start Up. This two-component system results in a longer-lasting chlorine residual and reduced chlorine consumption. Both products are completely soluble.

VINYL-LINED POOL CARE: Vinyl-lined pools are easily damaged by chemicals used to treat and maintain pools. ALL-IN-ONE STABILIZED CHLORINATING GRANULES are well suited for use in these pools, especially the above-ground pools which have 3-4 foot depths and are not equipped with a bottom drain. ALL-IN-ONE STABILIZED CHLORINATING GRANULES dissolves fast and completely (is easily pre-dissolved in a bucket of water to help avoid potential problems), so direct contact with the pool liner is reduced and there are not residues to be swept or vacuumed from the pool bottom. ALL-IN-ONE STABILIZED CHLORINATING GRANULES also simplifies pH control because it's pH neutral, compared to other forms of chlorinating products which contain calcium hypochlorite, sodium hypochlorite, and trichloroisocyanuric acid. (**NOTE:** Insoluble crystal-forming reaction will result when using sodium bisulfate (dry pool acid) to adjust pH when used in conjunction with calcium hypochlorite). ALL-IN-ONE STABILIZED CHLORINATING GRANULES will not cloud water even when superchlorinating which often occurs with calcium hypochlorite products.

START UP: Step 1. Condition pool water with KEM TEK™ STABILIZER CONDITIONER as per directions on its label. Thereafter, regular use of ALL-IN-ONE STABILIZED CHLORINATING GRANULES alone will maintain proper stabilization. NOTE: Omit Step 1 if pool is already conditioned with a similar stabilizer. **Step 2.** Concurrently with Step 1, superchlorinate water by adding 12 oz. of ALL-IN-ONE STABILIZED CHLORINATING GRANULES per 10,000 gallons of pool water. See additional superchlorination instructions below.

DAILY CARE: After Step 1 and 2 above, regularly check chlorine residual with a test kit and chlorinate daily or as needed to maintain 1.0 to 1.5 ppm residual chlorine. NOTE: One ounce of this product per 5,000 gallons of pool water will increase an existing chlorine residual by 0.8 ppm (1/8 rounded measuring cup = 1 oz.). Broadcast ALL-IN-ONE STABILIZED CHLORINATING GRANULES directly into the pool water. **pH:** Keep pH of water between 7.2 and 7.6. Use KEM TEK™ pH MINUS (dry acid) to lower pH and KEM-TEK™ pH PLUS (soda ash) to raise it.

SUPERCHLORINATION: When ever the pool water loses its sparkle or turns green or the chlorine residual falls rapidly after regular chlorination, superchlorination is recommended. Experience shows that during summer months, water should be superchlorinated with 6 oz. of ALL-IN-ONE STABILIZED CHLORINATING GRANULES per 5,000 gallons of pool water every 10 to 14 days. Do not use the pool until the chlorine residual has dropped to 3 ppm.

GENERAL: The following tables are a handy reference to average chlorine requirements, but must not be substituted for regular use of a test kit since pools and conditions vary considerably. Test water frequently and chlorinate as needed. Anticipate an increased chlorine consumption with increased swimming, hot water or weather, rain, a dirty or neglected pool, etc.

TYPICAL DAILY DOSAGE (SUMMERTIME)
After Steps 1 & 2 above

ABOVE GROUND POOL - 3' to 4' Deep

Pool Diameter	12 Ft.	15 Ft.	18 Ft.	20 Ft.	24 Ft.
Approx. Gallons	2,500	4,500	7,000	9,000	13,000
Dosage (ounces)	3/4-1	1 1/2-2	2-3	3-4	4-5

IN GROUND POOL - 7' to 9' DEEP

Pool Size (Feet)	14x28	16x32	17x34	18x36	20x40
Approx. Gallons	15,000	20,000	25,000	30,000	35,000
Dosage (ounces)	5-6	6-7	7-8	8-9	9-10

PRECAUTIONARY STATEMENTS • HAZARDS TO HUMANS AND DOMESTICATED ANIMALS

CORROSIVE: Causes irreversible eye damage. May be fatal if inhaled. Harmful if swallowed or absorbed through the skin. Do not get in eyes, on skin or on clothing. Do not breathe dust, vapor or spray mist. Wear goggles, face shield or safety glasses. Wash thoroughly with soap and water after handling. Remove and wash contaminated clothing before reuse.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to the discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARD: STRONG OXIDIZING AGENT. WILL BURN WITH THE EVOLUTION OF CHLORINE AND EQUALLY TOXIC GASES. CONTACT WITH WATER SLOWLY LIBERATES IRRITATING AND HAZARDOUS CHLORINE CONTAINING GASES. DECOMPOSES AT 460° F TO 480° F WITH LIBERATION OF HARMFUL GASES. Mix only with water. Use clean dry utensils. Do not add this product to any dispensing device containing remnants of any other product. Such use may cause a violent reaction leading to a fire or explosion. Contamination with moisture, organic matter or other chemicals may start a chemical reaction with generation of heat, liberation of hazardous gases and possible generation of fire and explosion. IN CASE OF FIRE, if possible, isolate container in open air or well ventilated area. Flood with large volume of water. IN CASE OF CONTAMINATION OR DECOMPOSITION, do not reseal container.

PRACTICAL TREATMENT (First Aid):

IF IN EYES: Hold eyelids open and flush with a steady, gentle stream of water for 15 minutes. Get medical attention. IF INHALED: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Get medical attention if irritation persists. IF SWALLOWED: Drink promptly large quantities of water. Avoid alcohol. Get medical attention.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

STORAGE AND DISPOSAL: Do not contaminate water, food or feed by storage or disposal. Keep product dry in tightly closed container when not in use. Store in a cool, dry well ventilated area away from heat or open flame. In case of decomposition, isolate container in open area, if possible, and flood with large amounts of water. Do not reuse empty container.

Department of Agriculture
STATE OF HAWAII
LICENSED
PERIOD 2009-2011 LIC. NO.

Department of Agriculture
STATE OF HAWAII
LICENSED
PERIOD 2012-2014 LIC. NO.

Department of Agriculture
STATE OF HAWAII
LICENSED
PERIOD 2015-2017 LIC. NO.
9163.24

LICENSED
HAWAII
DEPT. OF AGRICULTURE
Period 2003-2005 No. 9163.24
2006-2008