KEMTEK

pool & spa care™

2

chlorinate

Spa Chlorinating Granules

STATE OF HAWAII
Department of Agriculture
ACCEPTED
LICENSE NO. 9163.63

FOR DAILY CHLORINATION. FOR USE IN ALL SPAS

Balanced pH

Fast Dissolving

Kills Algae & Bacteria

KEEP OUT OF REACH OF CHILDREN

DANGER

See back panel for other precautions

ACTIVE INGREDIENT:

Sodium Dichloro-s-Triazinetrione-Dihydrate....99.0%
OTHER INGREDIENTS.....1.0%
TOTAL.....100.0%
AVAILABLE CHLORINE.....56.0%

NET WT 2 LBS (32 FL OZ.)

FIRST AID: Call a poison control center or doctor for treatment advice. Have the product container or label with you when calling poison control center or doctor, or going for treatment. IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration preferably mouth-to-mouth, if possible. IF SWALLOWED: Have person sip a glass of water if able to swallow. DO NOT induce vomiting unless told to do so by poison control center or doctor. Do not give anything by mouth to an unconscious person. IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

SEAL TO FALL HERE

DIRECTIONS FOR USE: It is a violation of federal law to use this product in a manner inconsistent with its labeling.

ATTENTION: Never mix this concentrated chemical with any other substance except generous amounts of water. See CHEMICAL HAZARDS on this label.

FOR CONTROL OF BACTERIA AND ALGAE (OUTDOORS) IN SPAS:

1. Before bathing, test water pH, chlorine residual and alkalinity using a suitable test kit. Adjust chlorine residual to 3.0 ppm. After bathing, super chlorinate to 5.0 ppm (1 level Tablespoon per 500 gallons of water). Use a chlorine stabilizer, especially for outdoors, to prolong chlorine residual. Maintain pH of water between 7.2 and 7.6 and total alkalinity between 125 and 175 ppm with KEM-TEK POOL & SPA CARE SPA pH PLUS or KEM-TEK POOL & SPA CARE SPA pH MINUS.

2. This product does not affect pH or alkalinity of water. One tenth oz. (1/2 tsp.) per 500 gal. of water gives 0.8 ppm and 1 level Tbsp. gives 5.0 ppm of chlorine. To use, broadcast granules into water with jets running. Do not use the spa until the chlorine residual has dropped to 3 ppm.

3. With bathers in a 500 gal. spa a 2.0 ppm chlorine residual can drop below the minimum 1.0 ppm in 15 to 20 minutes. Less water or more bathers will accelerate loss. Test often and keep chlorine residual above 1.0 ppm.

4. Weekly, super chlorinate water to 5 or 6 ppm (see 2 above). Re-entry into spas is prohibited above levels of 3 ppm of chlorine. Drain and clean spa whenever the water becomes difficult to manage or chlorine stabilizer goes over 100 ppm as measured with a suitable cyanuric acid test kit. Avoid use of products such as body lotion that consume chlorine.

PRECAUTIONARY STATEMENTS:

Hazards to humans and domestic animals

DANGER: CORROSIVE: Causes irreversible eye damage. May be fatal if inhaled. Harmful if swallowed or absorbed through skin. Do not get in eyes, on skin or on clothing. Do not breathe dust, vapor or spray mist. Wear goggles, face shield or safety glasses. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove contaminated clothing and wash clothing before reuse.

ENVIRONMENTAL HAZARDS: This product is toxic to fish and aquatic organisms.

PHYSICAL OR CHEMICAL HAZARD: STRONG OXIDIZING AGENT. Will burn with the evolution of chlorine and equally toxic gases. Contact with water slowly liberates irritating and hazardous chlorine containing gases. Decomposes at 460°F to 480°F with the liberation of harmful gases. Mix only with water. Use clean dry utensils. Do not add this product to any dispensing device containing remnants of any other product. Such use may cause a violent reaction leading to fire or explosion. Contamination with moisture, organic matter, or other chemicals may start a chemical reaction with the generation of heat, liberation of hazardous gases, and possible generation of fire or explosion. In case of fire, if possible isolate container in open air or well ventilated area. Flood with a large volume of water. In case of contamination or decomposition, do not reseal container.

STORAGE AND DISPOSAL:

STORAGE: Keep product in tightly closed container when not in use. Store in a cool, dry well-ventilated area away from heat or open flame. **CONTAINER DISPOSAL:** If empty: Nonrefillable container. Do not reuse or refill this container. Place in trash collection or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions. Never place unused product down any indoor or outdoor drain.

NOTE: Do not allow direct contact of this product on the following surfaces: vinyl, metallic, fiberglass, painted or colored plaster. Always dilute in the water; direct contact with surfaces will bleach color.

EPA Reg. No. 7616-70 EPA Est. No. 7616-CA-1

Free Pool Care Advice 1-800-SOS-POOL. www.kem-tek.com

MANUFACTURED BY: KIK POOL ADDITIVES INC.,
5160 E. AIRPORT DRIVE, ONTARIO, CA 91761-7824

UPC # X XXXXX XXXXX X
FOR POSITION ONLY
X 80% 00000 X