

9197.228

LICENSED

PERIOD 2014-2016 LIC. NO.

# AQUCAR™ 504 Water Treatment Microbiocide

## DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

### AIR WASHERS AND INDUSTRIAL SCRUBBING SYSTEMS/RECIRCULATING COOLING AND PROCESS WATER SYSTEMS

This product may be used only in industrial air washers and air washer systems which have mist-eliminating components.

AQUCAR 504 Water Treatment Microbiocide should be added at the application rates described below to a water treatment system at a convenient point of uniform mixing such as the basin area. Addition may be made intermittently (SLUG DOSE) or continuously. Badly fouled systems can be shock treated with AQUCAR 504 Water Treatment Microbiocide. Under these conditions, blowdown should be discontinued for up to 24 hours. AQUCAR 504 Water Treatment Microbiocide can be used in industrial process water systems that contain ultra filtration units and non-medical reverse osmosis membranes (where approved for compatibility by the membrane manufacturer) and associated distribution systems.

### INTERMITTENT (SLUG DOSE) METHOD

**Initial Dose:** When the system is noticeably fouled, apply 16 to 32 fluid ounces (1 pint to 1 quart) of AQUCAR 504 Water Treatment Microbiocide per 100 gallons of water in the system. Repeat until control is achieved.

**Subsequent dose:** When microbial control is evident, add 8 to 16 fluid ounces (1 cup to 1 pint) of AQUCAR 504 Water Treatment Microbiocide per 100 gallons of water in the system weekly, or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

### CONTINUOUS FEED METHOD

**Initial Dose:** When the system is noticeably fouled, apply 16 to 32 fluid ounces (1 pint to 1 quart) of AQUCAR 504 Water Treatment Microbiocide per 100 gallons of water in the system.

**Subsequent Dose:** Maintain this treatment level by starting a continuous feed of 4 to 16 fluid ounces (1/2 cup to 1 pint) of AQUCAR 504 Water Treatment Microbiocide per 100 gallons of water in the system per day. Badly fouled systems must be cleaned before treatment is begun.

### SERVICE WATER AND AUXILIARY SYSTEMS

AQUCAR 504 Water Treatment Microbiocide should be used at the same application rates, and in the same manner as described above. It should be added to the system at a point that will allow for uniform mixing throughout the system.

### HEAT TRANSFER SYSTEMS

(Evaporative Condensers, Dairy Sweetwater Systems, Hydrostatic Sterilizers and Retorts, and Pasteurizers)

AQUCAR 504 Water Treatment Microbiocide should be used at the same application rates, and in the same manner as described above. It should be added to the system at a point of uniform mixing such as a basin area, sump area, or other reservoir or collecting area from which the treated water will be circulated uniformly throughout the system.

### INDUSTRIAL WASTEWATER SYSTEMS

(Wastewater Systems, Wastewater Sludge And Wastewater Holding Tanks)

AQUCAR 504 Water Treatment Microbiocide should be added to a wastewater system or sludge at a convenient point of uniform mixing such as digester. Add 72 to 360 fluid ounces (2.25 to 11.25 quarts) (5,600 to 28,000 ppm) AQUCAR 504 Water Treatment Microbiocide per 100 gallons of wastewater or sludge.

### PAPER MILLS AND PAPER MILL PROCESS WATER SYSTEMS

*Product not registered for this use in the State of California*

AQUCAR 504 Water Treatment Microbiocide should be added to the paper making system at a point of uniform mixing such as the beaters, broke chest pump, save-all tank, or white-water tank.

**Initial Dose:** When the system is noticeably contaminated, add 6.25 to 37.5 lbs of AQUCAR 504 Water Treatment Microbiocide per ton of pulp or paper (dry basis) as a slug dose. Repeat until control is achieved. Heavily fouled systems should be boiled out prior to initial treatment.

**Subsequent Dose:** When microbial control is evident, add 3.75 to 25 lbs of AQUCAR 504 Water Treatment Microbiocide per ton of pulp or paper (dry basis) as a slug dose as necessary to maintain control.

### PIGMENTS AND FILLER SLURRIES FOR PAPER AND PAPERBOARD

*Product not registered for this use in the State of California*

**(For use in food and non-food contact pigments and filler slurries)**

Use from 1.25 to 7.5 lbs. of AQUCAR 504 Water Treatment Microbiocide per 1,000 lbs. of dry powder to produce a concentration from 1,250 to 7,500 ppm as product (based on slurry solids) in the mixed slurry.

### WATER BASED COATINGS FOR PAPER AND PAPERBOARD

*Product not registered for this use in the State of California*

**NOTE:** For use in non-food contact coatings only.

Use from 1.25 to 7.5 lbs. of AQUCAR 504 Water Treatment Microbiocide per 1,000 lbs. of dry powder to produce a concentration from 1,250 to 7,500 ppm as product (based on slurry solids) in the mixed slurry.

### WATER FLOODS

*Product not registered for this use in the State of California*

AQUCAR 504 Water Treatment Microbiocide should be added to a water flood system at a point of uniform mixing.

**Initial Treatment:** When the system is noticeably contaminated, add 1,250 to 62,500 ppm AQUCAR 504 Water Treatment Microbiocide to the system (1.13 to 55 gallons AQUCAR 504 Water Treatment Microbiocide per 1,000 gallons flood water). Repeat until control is achieved.

**Subsequent Dose:** When microbial control is evident, add 250 to 62,500 ppm AQUCAR 504 Water Treatment Microbiocide (0.25 to 55 gallons AQUCAR 504 Water Treatment Microbiocide per 1,000 gallons flood water) to the system weekly, or as needed to maintain control.

**Optional** - 3<sup>rd</sup> party certification label verbiage and symbols in label space outside of FIFRA elements. Example: NSF Certification.

### Active Ingredient:

Glutaraldehyde .....	4%
Inert Ingredients: .....	96%
<b>TOTAL</b> .....	<b>100%</b>

FIRST AID	
<b>IF SWALLOWED</b>	<ul style="list-style-type: none"> <li>• Call a poison control center or doctor immediately for treatment advice.</li> <li>• Have person sip a glass of water if able to swallow.</li> <li>• Do not induce vomiting unless told to do so by the poison control center or doctor.</li> </ul>
<b>IF IN EYES</b>	<ul style="list-style-type: none"> <li>• Wash immediately and continuously with flowing water for at least 30 minutes.</li> <li>• Remove contact lenses after the first 5 minutes and continue washing.</li> <li>• Obtain prompt medical consultation, preferably from an ophthalmologist.</li> </ul>
<b>IF ON SKIN OR CLOTHING</b>	<ul style="list-style-type: none"> <li>• Take off contaminated clothing.</li> <li>• Rinse skin immediately with plenty of water for 15–20 minutes.</li> <li>• Call a poison control center or doctor for treatment advice.</li> </ul>
<b>IF INHALED</b>	<ul style="list-style-type: none"> <li>• Move person to fresh air.</li> <li>• If person is not breathing, call 911 or an ambulance, and then give artificial respiration, using pocket mask or face protection if via mouth-to-mouth.</li> <li>• Call a poison control center or a doctor for further treatment advice.</li> </ul>

Have product container or label with you when calling a poison control center or doctor or going for treatment.

HOT LINE NUMBER	
IN CASE OF AN EMERGENCY endangering life or property involving this product, call collect (989)636-4400.	E.P.A. Registration No. 464-707 E.P.A. Est. 10352-WV-002
NOTE TO PHYSICIAN	
Inhalation, ingestion or aspiration may cause lung or G-I tract damage. Probable mucosal damage may contraindicate the use of gastric lavage. Chemical eye burns may require extended irrigation. No specific antidote, symptomatic treatment.	

Produced For (used when manufactured by contract manufacturer)



## THE DOW CHEMICAL COMPANY

Midland, Michigan 48674

(989) 636-4400

® TM Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

MADE IN U.S.A.

**NET CONTENTS: 55 gallons**  
**NET WT: 475 lb / 215.5 kg**  
**LOT:**

## KEEP OUT OF REACH OF CHILDREN DANGER PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS DANGER

Corrosive • Causes irreversible eye damage • Causes skin irritation • Harmful if inhaled • Harmful if swallowed • Harmful if absorbed through skin • Prolonged or frequently repeated skin contact may cause allergic skin reaction in some individuals. • Causes asthmatic signs and symptoms in hyper-reactive individuals. • Do not get in eyes, on skin, on clothing • Avoid breathing vapor. • Do not swallow • Wear goggles, protective clothing, and butyl or nitrile gloves. • Wash thoroughly with soap and water after handling • Remove contaminated clothing and wash before reuse.

## ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

## STORAGE AND HANDLING

AQUCAR 504 Water Treatment Microbiocide is incompatible with many commonly used materials of construction such as steel, galvanized iron, aluminum, tin, and zinc. AQUCAR 504 Water Treatment Microbiocide can be stored and handled in baked phenolic-lined steel, polyethylene, stainless steel, or reinforced epoxy-plastic equipment. This product freezes at about 25° F (-4° C). Therefore, unless the storage tank is inside or underground, heating and insulation may be required. If heating is needed, exposure to high temperatures should be avoided. For short storage times (up to about 1 month), temperatures of up to 100° F (37.8° C) can be tolerated but the preferred maximum storage temperature is about 80° F (26.7° C). A stainless steel centrifugal pump is suggested for transfer service. Spiral-wound stainless steel with TEFLON® Polymer is suitable for gaskets and packing. Handle in a well-ventilated area. If vapors are irritating to the nose or eyes, special ventilation or respiratory protection (MSHA/NIOSH approved air purifying respirator equipped with an organic vapor cartridge) may be required.

## STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

**PESTICIDE DISPOSAL:** Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited. Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

### CONTAINER DISPOSAL

*Option - labels for nonrefillable rigid containers of all sizes.*

**Nonrefillable Container.** Do not reuse or refill this container. Triple or pressure rinse container (or equivalent) promptly after emptying. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

*Option - labels on refillable rigid containers of all sizes*

**Refillable Container.** Refill this container with pesticide only. Do not reuse this container for any other purpose. Cleaning of the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller. To clean container before final disposal, empty contents into application equipment and triple rinse. Pour or pump rinsate into application equipment or rinsate collection system. Then offer for recycling if available, or puncture and dispose of in a sanitary landfill, or by incineration, or by other procedures allowed by state and local authorities.

## WARRANTY DISCLAIMER

Seller warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions, subject to the inherent risks set forth below. SELLER MAKES NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.