

FUNGIBLOCK™ CX4300 Antifungal Agent

DISC.

FOR INDUSTRIAL USE ONLY
Industrial Fungicide

Fungicidal Additive for use in exterior paint and coatings, adhesives, caulks and sealants, exterior plaster coatings, architectural coatings and coatings for wallboard, gypsum cores in wallboard and ceiling tiles, insulation covering, and aqueous and solvent based paper and paperboard applications.

Active Ingredients:

Methyl (1H-benzimidazol-2-yl)Carbamate 43.54%
Other Ingredients 56.46%
Total 100.00%

EPA Registration No. 74075-2-464

EPA Establishment No. 74086-FRA-001

KEEP OUT OF REACH OF CHILDREN

CAUTION

See side panel for additional Precautionary Statements

PRECAUTIONARY STATEMENTS

HAZARD TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Causes moderate eye irritation. Avoid contact with eyes, skin or clothing. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, or, using tobacco.

Distributed by:



The Dow Chemical Company

Midland, Michigan 48674 U.S.A.

(989)636-4400

©TM Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

Made in U.S.A.

00159710-01/02/2008-2397



LICENSED

PERIOD **2011-2013** LIC. NO.



LICENSED

PERIOD **2008-2010** LIC. NO.



LICENSED

PERIOD **2014-2016** LIC. NO.

DISC.

9197.26

FIRST AID	
Call a Poison Control Center or doctor for treatment advice.	
If in Eyes	<ul style="list-style-type: none"> • Hold eye open and rinse slowly and gently with water for 15-20 minutes. • Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
If on Skin	<ul style="list-style-type: none"> • Take off contaminated clothing. • Rinse skin immediately with plenty of water for 15-20 minutes. • Call a poison control center or doctor for treatment advice.
If Inhaled	<ul style="list-style-type: none"> • Move person to fresh air. • If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible.
Have the product container or label with you when calling a poison control center or doctor, or going for treatment. For Medical Emergency ONLY call: 24 Hour Emergency Response Number.	

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage and disposal.

Pesticide Storage: Store this product in a cool dry area, away from direct sunlight and heat to avoid deterioration. In case of spill, flood areas with large quantities of water.

Pesticide Disposal: Product or rinsates that cannot be used should be diluted with water before disposal in a sanitary sewer.

Container Disposal: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by state and local authorities; by burning. If burned, stay out of smoke.

ENVIRONMENTAL HAZARDS

Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

FUNGIBLOCK CX4300 Antifungal Agent is intended for use as an industrial fungicide for the control of fungal growth on exterior paint and coatings, adhesives, caulks and sealants, exterior plaster coatings, architectural coatings and coatings for wallboard, gypsum cores in wallboard and ceiling tiles, insulation covering, and aqueous and solvent based paper and paper board applications.

NOT FOR US IN COATINGS, ADHESIVES, PAINTS, CAULKS, SEALANTS, OR PAPER THAT WILL COME IN CONTACT WITH FOOD.

It is chemically inert and will not react with the other ingredients in the solution.

Industrial Use Settings Only: Add FUNGIBLOCK CX4300 Antifungal Agent to the exterior paint and coatings, adhesives, caulks and sealants, exterior plaster coatings, and architectural coatings, and coatings for wallboard and insulation covering at levels of 2 gallons/1000 gallons to 20 gallons/1000 gallons depending on the substance to be protected, the fungal hazard, and the duration of the product desired. For gypsum cores in wallboard and ceiling tiles, add FUNGIBLOCK CX4300 Antifungal Agent to wet gypsum during the manufacturing process at levels in the range of 0.2 to 1 gallon per 1000 square feet.

For aqueous and solvent based non food paper and paperboard applications including:

- packaging soap bars
- manufacturing file folders, boxes and other storage devices for items to be stored for long periods
- coverings for insulation, wallboard and other construction materials
- battle labels and other labels

Use at levels of 350 ppm - 1500 ppm active ingredient in the paper. It is the responsibility of the formulator to test FUNGIBLOCK CX4300 Antifungal Agent for optimum dose levels and to determine compatibility and suitability for the intended use.

Net Contents: 6.93 gallons (66 lb) or 227.5 gallons (2200 lb)