

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER
CORROSIVE

CAUSES IRREVERSIBLE EYE DAMAGE AND SKIN BURNS, MAY CAUSE ALLERGIC SKIN REACTION
HARMFUL IF INHALED, HARMFUL IF SWALLOWED OR ABSORBED THROUGH THE SKIN

Do not get in eyes, on skin, or on clothing. Mixers, loaders and others exposed to this product must wear: long-sleeved shirt and long pants; chemical resistant gloves such as nitrile or butyl rubber; shoes plus socks; goggles and face shield; and chemical resistant apron. Discard clothing or other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry. Users should wash hands before eating, drinking, chewing gum, using tobacco or using the toilet. Users should remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users should remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly. This product may cause skin sensitization reactions in some people.

ENVIRONMENTAL HAZARDS

This chemical is toxic to aquatic plants, fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on this label.

STORAGE AND DISPOSAL

PESTICIDE STORAGE: Do not contaminate water, food or feed by storage, disposal, or cleaning of equipment. Do not apply this product in a way that will contact workers or other persons.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container. Triple rinse or pressure rinse container (or equivalent) promptly after emptying. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by procedures approved by state and local authorities.

GENERAL: CONSULT FEDERAL, STATE, OR LOCAL DISPOSAL AUTHORITIES FOR APPROVED ALTERNATIVE PROCEDURES

NET CONTENTS SHOWN ELSEWHERE ON CONTAINER



LICENSED

PERIOD 2014-2016 LIC. NO.



Revised: 08-03-2010



LICENSED

PERIOD 2011-2013 LIC. NO. 9323.104



Nalco 77352

Industrial Microbiocide for use in Industrial Recirculating Water Cooling Towers, Recirculating Closed Loop Water Cooling Systems, Brewery Pasteurizer/Can Warmer Systems, Air Washer Systems, Industrial Wastewater Treatment Systems and Sewage Systems.

ACTIVE INGREDIENTS:

5-Chloro-2-methyl-4-isothiazolin-3-one	1.11%
2-Methyl-4-isothiazolin-3-one	0.39%
INERT INGREDIENTS:	98.50%
Total:	100.00%

KEEP OUT OF REACH OF CHILDREN

DANGER

FIRST AID

IF ON SKIN:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 min.
- Call a poison control center or doctor for treatment advice.

IF IN EYES:

- Hold eye open and rinse slowly and gently with water for 15-20 min.
- Remove contact lenses, if present, after first 5 min, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

IF INHALED:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or doctor for further treatment advice.

IF SWALLOWED:

- Call a poison control center or doctor immediately for treatment advice.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Have person sip a glass of water if able to swallow.
- Do not give anything to an unconscious person.

Have the product container or label with you when calling a poison control center or doctor, or going for treatment.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsions may be necessary.

IN CASE OF EMERGENCY CALL (800) 424-9300.

SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS

EPA Reg. No. 707-133-1706

Letters in () that match prefix in batch number identify the establishment number.

EPA Est. No.

1706-IL-1 (BP); 1706-LA-1 (GV); 1706-PA-1 (EL)

SOLD BY:

Nalco Company
1601 W. Diehl Rd.
Naperville, IL 60563

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. For the control of microbial biofilms, bacteria, algae, and fungi, add Nalco 77352 to: **industrial recirculating water cooling towers, industrial recirculating closed loop water cooling systems, brewery pasteurizer and can warmer systems.** Add Nalco 77352 at some point in the system to insure uniform mixing.

INITIAL DOSE: When the system is noticeably fouled, apply 148 - 883 ppm Nalco 77352 (1.26 - 7.46 pound or 19 - 113 fluid ounce of Nalco 77352 per 1000 gallon of water in the system.) Repeat until control is achieved. Badly fouled systems should be cleaned before treatment is begun.

SUBSEQUENT DOSE: When microbial control is evident, add 35 - 219 ppm Nalco 77352 (0.3 - 1.86 pound or 4.5 - 28 fluid ounce of Nalco 77352 per 1000 gallon of water in the system) weekly or as needed to maintain control.

AIR WASHER SYSTEMS

Add to the air washer sump or chill water sump to insure uniform mixing, 35 - 883 ppm Nalco 77352 (0.3 - 7.46 pound or 4.5 - 113 fluid ounce of Nalco 77352 per 1000 gallon of water in the system) depending upon the severity of contamination to control microbial biofilms, bacteria, fungi, and algae which cause fouling in industrial air washer systems.

INTERMITTENT OR SLUG METHOD

INITIAL DOSE: When the system is noticeably fouled, apply 148 - 883 ppm Nalco 77352 (1.26 - 7.46 pound or 19 - 113 fluid ounce of Nalco 77352 per 1000 gallon of water in the system.) Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 35 - 219 ppm Nalco 77352 (0.3 - 1.86 pound or 4.5 - 28 fluid ounce of Nalco 77352 per 1000 gallon of water) in the system weekly or as needed to maintain control. Badly fouled systems should be cleaned before treatment is begun.

CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is noticeably fouled, apply 148 - 883 ppm Nalco 77352 (1.26 - 7.46 pound or 19 - 113 fluid ounce of Nalco 77352 per 1000 gallon of water in the system.)

SUBSEQUENT DOSE: Maintain this treatment level by adding a continuous feed of 35 - 219 ppm Nalco 77352 (0.3 - 1.86 pound or 4.5 - 28 fluid ounce of Nalco 77352 per 1000 gallon of makeup water). Badly fouled systems must be cleaned before initial treatment.

NOTE: For use only in systems that maintain effective mist-eliminating components.

INDUSTRIAL WASTEWATER TREATMENT SYSTEMS AND SEWAGE SYSTEMS

Nalco 77352 is recommended for the control of microbial biofilms, bacteria, fungi, and algae in industrial wastewater treatment and sewage systems. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority.

INITIAL DOSE: When the system is noticeably fouled, apply 148 - 883 ppm Nalco 77352 (1.26 - 7.46 pound or 19-113 fluid ounce of Nalco 77325 per 1000 gallon of water in the system.) Repeat until control is achieved. Badly fouled systems should be cleaned before treatment is begun.

SUBSEQUENT DOSE: When microbial control is evident, add 35 - 219 ppm Nalco 77352 (0.3 - 1.86 pound or 4.5 - 28 fluid ounce of Nalco 77352 per 1000 gallon of water in the system) weekly or as needed to maintain control.

Nalco 77352 weighs 8.4 pounds/gallon.

CONDITIONS OF SALE AND WARRANTY

Nalco Company warrants that this product conforms to its chemical description and is reasonably fit for the purpose stated on the label only when used in accordance with label directions and as defined the Directions for Use on this label. NALCO COMPANY MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, EITHER OF MERCHANTABILITY OR FITNESS, FOR A PARTICULAR USE. Handling, storage, and use of the product by Buyer or User are beyond the control of Nalco Company and Seller. Risks such as ineffectiveness or other unintended consequences resulting from, but not limited to, failure to follow directions will be assumed by the Buyer or User. TO THE EXTENT PERMITTED BY LAW, NEITHER NALCO COMPANY NOR SELLER SHALL BE LIABLE FOR CONSEQUENTIAL, SPECIAL OR INDIRECT DAMAGES RESULTING FROM THE HANDLING, STORAGE OR USE OF THIS PRODUCT.

UN 3265, Corrosive Liquid, Acidic, Organic, N.O.S. (5-chloro-2-methyl-4-isothiazolin-3-one) 8, PG II

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER
CORROSIVE

CAUSES IRREVERSIBLE EYE DAMAGE AND SKIN BURNS, MAY CAUSE ALLERGIC SKIN REACTION
HARMFUL IF INHALED, HARMFUL IF SWALLOWED OR ABSORBED THROUGH THE SKIN

Do not get in eyes, on skin, or on clothing. Mixers, loaders and others exposed to this product must wear: long-sleeved shirt and long pants; chemical resistant gloves such as nitrile or butyl rubber; shoes plus socks; goggles and face shield; and chemical resistant apron. Discard clothing or other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry. Users should wash hands before eating, drinking, chewing gum, using tobacco or using the toilet. Users should remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users should remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly. This product may cause skin sensitization reactions in some people.

ENVIRONMENTAL HAZARDS

This chemical is toxic to aquatic plants, fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on this label.

STORAGE AND DISPOSAL

PESTICIDE STORAGE: Do not contaminate water, food or feed by storage, disposal, or cleaning of equipment. Do not apply this product in a way that will contact workers or other persons.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container. Triple rinse or pressure rinse container (or equivalent) promptly after emptying. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by procedures approved by state and local authorities.

GENERAL: CONSULT FEDERAL, STATE, OR LOCAL DISPOSAL AUTHORITIES FOR APPROVED ALTERNATIVE PROCEDURES

NET CONTENTS SHOWN ELSEWHERE ON CONTAINER



LICENSED

PERIOD 2014-2016 LIC. NO. 9323.104

UN 3265, Corrosive Liquid, Acidic, Organic, N.O.S. (5-chloro-2-methyl-4-isothiazolin-3-one) 8, PG II



Industrial Microbiocide for use in Industrial Recirculating Water Cooling Towers, Recirculating Closed Loop Water Cooling Systems, Brewery Pasteurizer/Can Warmer Systems, Air Washer Systems, Industrial Wastewater Treatment Systems and Sewage Systems.

ACTIVE INGREDIENTS:

5-Chloro-2-methyl-4-isothiazolin-3-one 1.11%
2-Methyl-4-isothiazolin-3-one 0.39%
INERT INGREDIENTS:..... 98.50%
Total:..... 100.00%

KEEP OUT OF REACH OF CHILDREN
DANGER

FIRST AID

IF ON SKIN:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 min.
- Call a poison control center or doctor for treatment advice.

IF IN EYES:

- Hold eye open and rinse slowly and gently with water for 15-20 min.
- Remove contact lenses, if present, after first 5 min, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

IF INHALED:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or doctor for further treatment advice.

IF SWALLOWED:

- Call a poison control center or doctor immediately for treatment advice.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Have person sip a glass of water if able to swallow.
- Do not give anything to an unconscious person.

Have the product container or label with you when calling a poison control center or doctor, or going for treatment.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsions may be necessary.

IN CASE OF EMERGENCY CALL (800) 424-9300.

SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS

EPA Reg. No. 707-133-1706

Letters in () that match prefix in batch number identify the establishment number.

EPA Est. No.

1706-IL-1 (BP); 1706-LA-1 (GV); 1706-PA-1 (EL)

SOLD BY:

Nalco Company
1601 W. Diehl Rd.
Naperville, IL 60563

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. For the control of microbial biofilms, bacteria, algae, and fungi, add Nalco 77352 to: **industrial recirculating water cooling towers, industrial recirculating closed loop water cooling systems, brewery pasteurizer and can warmer systems.** Add Nalco 77352 at some point in the system to insure uniform mixing.

INITIAL DOSE: When the system is noticeably fouled, apply 148 - 883 ppm Nalco 77352 (1.26 - 7.46 pound or 19 - 113 fluid ounce of Nalco 77352 per 1000 gallon of water in the system.) Repeat until control is achieved. Badly fouled systems should be cleaned before treatment is begun.

SUBSEQUENT DOSE: When microbial control is evident, add 35 - 219 ppm Nalco 77352 (0.3 - 1.86 pound or 4.5 - 28 fluid ounce of Nalco 77352 per 1000 gallon of water in the system) weekly or as needed to maintain control.

AIR WASHER SYSTEMS

Add to the air washer sump or chill water sump to insure uniform mixing, 35 - 883 ppm Nalco 77352 (0.3 - 7.46 pound or 4.5 - 113 fluid ounce of Nalco 77352 per 1000 gallon of water in the system) depending upon the severity of contamination to control microbial biofilms, bacteria, fungi, and algae which cause fouling in industrial air washer systems.

INTERMITTENT OR SLUG METHOD

INITIAL DOSE: When the system is noticeably fouled, apply 148 - 883 ppm Nalco 77352 (1.26 - 7.46 pound or 19 - 113 fluid ounce of Nalco 77352 per 1000 gallon of water in the system.) Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 35 - 219 ppm Nalco 77352 (0.3 - 1.86 pound or 4.5 - 28 fluid ounce of Nalco 77352 per 1000 gallon of water) in the system weekly or as needed to maintain control. Badly fouled systems should be cleaned before treatment is begun.

CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is noticeably fouled, apply 148 - 883 ppm Nalco 77352 (1.26 - 7.46 pound or 19 - 113 fluid ounce of Nalco 77352 per 1000 gallon of water in the system.)

SUBSEQUENT DOSE: Maintain this treatment level by adding a continuous feed of 35 - 219 ppm Nalco 77352 (0.3 - 1.86 pound or 4.5 - 28 fluid ounce of Nalco 77352 per 1000 gallon of makeup water). Badly fouled systems must be cleaned before initial treatment.

NOTE: For use only in systems that maintain effective mist-eliminating components.

INDUSTRIAL WASTEWATER TREATMENT SYSTEMS AND SEWAGE SYSTEMS

Nalco 77352 is recommended for the control of microbial biofilms, bacteria, fungi, and algae in industrial wastewater treatment and sewage systems. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority.

INITIAL DOSE: When the system is noticeably fouled, apply 148 - 883 ppm Nalco 77352 (1.26 - 7.46 pound or 19-113 fluid ounce of Nalco 77325 per 1000 gallon of water in the system.) Repeat until control is achieved. Badly fouled systems should be cleaned before treatment is begun.

SUBSEQUENT DOSE: When microbial control is evident, add 35 - 219 ppm Nalco 77352 (0.3 - 1.86 pound or 4.5 - 28 fluid ounce of Nalco 77352 per 1000 gallon of water in the system) weekly or as needed to maintain control.

Nalco 77352 weighs 8.4 pounds/gallon.

CONDITIONS OF SALE AND WARRANTY

Nalco Company warrants that this product conforms to its chemical description and is reasonably fit for the purpose stated on the label only when used in accordance with label directions and as defined the Directions for Use on this label. NALCO COMPANY MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, EITHER OF MERCHANTABILITY OR FITNESS, FOR A PARTICULAR USE. Handling, storage, and use of the product by Buyer or User are beyond the control of Nalco Company and Seller. Risks such as ineffectiveness or other unintended consequences resulting from, but not limited to, failure to follow directions will be assumed by the Buyer or User. TO THE EXTENT PERMITTED BY LAW, NEITHER NALCO COMPANY NOR SELLER SHALL BE LIABLE FOR CONSEQUENTIAL, SPECIAL OR INDIRECT DAMAGES RESULTING FROM THE HANDLING, STORAGE OR USE OF THIS PRODUCT.



Revised: 08-03-2010

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER
CORROSIVE

CAUSES IRREVERSIBLE EYE DAMAGE AND SKIN BURNS, MAY CAUSE ALLERGIC SKIN REACTION
HARMFUL IF INHALED, HARMFUL IF SWALLOWED OR ABSORBED THROUGH THE SKIN

Do not get in eyes, on skin, or on clothing. Mixers, loaders and others exposed to this product must wear: long-sleeved shirt and long pants; chemical resistant gloves such as nitrile or butyl rubber; shoes plus socks; goggles and face shield; and chemical resistant apron. Discard clothing or other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry. Users should wash hands before eating, drinking, chewing gum, using tobacco or using the toilet. Users should remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users should remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly. This product may cause skin sensitization reactions in some people.

ENVIRONMENTAL HAZARDS

This chemical is toxic to aquatic plants, fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on this label.

STORAGE AND DISPOSAL

PESTICIDE STORAGE: Do not contaminate water, food or feed by storage, disposal, or cleaning of equipment. Do not apply this product in a way that will contact workers or other persons.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Refillable container. Refill this container with pesticide only. Do not reuse this container for any other purpose. Cleaning of the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller. To clean container before final disposal, empty contents into application equipment and triple rinse. Pour or pump rinsate into application equipment or rinsate collection system. Then offer for recycling if available, or puncture and dispose of in a sanitary landfill, or by incineration, or by other procedures allowed by state and local authorities.

GENERAL: CONSULT FEDERAL, STATE, OR LOCAL DISPOSAL AUTHORITIES FOR APPROVED ALTERNATIVE PROCEDURES

NET CONTENTS SHOWN ELSEWHERE ON CONTAINER

 Revised: 08-03-2010



Industrial Microbiocide for use in Industrial Recirculating Water Cooling Towers, Recirculating Closed Loop Water Cooling Systems, Brewery Pasteurizer/Can Warmer Systems, Air Washer Systems, Industrial Wastewater Treatment Systems and Sewage Systems.

ACTIVE INGREDIENTS:

5-Chloro-2-methyl-4-isothiazolin-3-one 1.11%
2-Methyl-4-isothiazolin-3-one 0.39%
INERT INGREDIENTS:..... 98.50%
Total:..... 100.00%

KEEP OUT OF REACH OF CHILDREN
DANGER

FIRST AID

IF ON SKIN:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 min.
- Call a poison control center or doctor for treatment advice.

IF IN EYES:

- Hold eye open and rinse slowly and gently with water for 15-20 min.
- Remove contact lenses, if present, after first 5 min, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

IF INHALED:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or doctor for further treatment advice.

IF SWALLOWED:

- Call a poison control center or doctor immediately for treatment advice.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Have person sip a glass of water if able to swallow.
- Do not give anything to an unconscious person.

Have the product container or label with you when calling a poison control center or doctor, or going for treatment.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsions may be necessary.

IN CASE OF EMERGENCY CALL (800) 424-9300.

SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS

EPA Reg. No. 707-133-1706

Letters in () that match prefix in batch number identify the establishment number.

EPA Est. No.

1706-IL-1 (BP); 1706-LA-1 (GV); 1706-PA-1 (EL)

SOLD BY:

Nalco Company
1601 W. Diehl Rd.
Naperville, IL 60563



LICENSED

PERIOD 2014-2016 LIC. NO. **9323.104**

UN 3265, Corrosive Liquid, Acidic, Organic, N.O.S. (5-chloro-2-methyl-4-isothiazolin-3-one) 8, PG II

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. For the control of microbial biofilms, bacteria, algae, and fungi, add Nalco 77352 to: **industrial recirculating water cooling towers, industrial recirculating closed loop water cooling systems, brewery pasteurizer and can warmer systems.** Add Nalco 77352 at some point in the system to insure uniform mixing.

INITIAL DOSE: When the system is noticeably fouled, apply 148 - 883 ppm Nalco 77352 (1.26 - 7.46 pound or 19 - 113 fluid ounce of Nalco 77352 per 1000 gallon of water in the system.) Repeat until control is achieved. Badly fouled systems should be cleaned before treatment is begun.

SUBSEQUENT DOSE: When microbial control is evident, add 35 - 219 ppm Nalco 77352 (0.3 - 1.86 pound or 4.5 - 28 fluid ounce of Nalco 77352 per 1000 gallon of water in the system) weekly or as needed to maintain control.

AIR WASHER SYSTEMS

Add to the air washer sump or chill water sump to insure uniform mixing, 35 - 883 ppm Nalco 77352 (0.3 - 7.46 pound or 4.5 - 113 fluid ounce of Nalco 77352 per 1000 gallon of water in the system) depending upon the severity of contamination to control microbial biofilms, bacteria, fungi, and algae which cause fouling in industrial air washer systems.

INTERMITTENT OR SLUG METHOD

INITIAL DOSE: When the system is noticeably fouled, apply 148 - 883 ppm Nalco 77352 (1.26 - 7.46 pound or 19 - 113 fluid ounce of Nalco 77352 per 1000 gallon of water in the system.) Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 35 - 219 ppm Nalco 77352 (0.3 - 1.86 pound or 4.5 - 28 fluid ounce of Nalco 77352 per 1000 gallon of water) in the system weekly or as needed to maintain control. Badly fouled systems should be cleaned before treatment is begun.

CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is noticeably fouled, apply 148 - 883 ppm Nalco 77352 (1.26 - 7.46 pound or 19 - 113 fluid ounce of Nalco 77352 per 1000 gallon of water in the system.)

SUBSEQUENT DOSE: Maintain this treatment level by adding a continuous feed of 35 - 219 ppm Nalco 77352 (0.3 - 1.86 pound or 4.5 - 28 fluid ounce of Nalco 77352 per 1000 gallon of makeup water). Badly fouled systems must be cleaned before initial treatment.

NOTE: For use only in systems that maintain effective mist-eliminating components.

INDUSTRIAL WASTEWATER TREATMENT SYSTEMS AND SEWAGE SYSTEMS

Nalco 77352 is recommended for the control of microbial biofilms, bacteria, fungi, and algae in industrial wastewater treatment and sewage systems. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority.

INITIAL DOSE: When the system is noticeably fouled, apply 148 - 883 ppm Nalco 77352 (1.26 - 7.46 pound or 19-113 fluid ounce of Nalco 77325 per 1000 gallon of water in the system.) Repeat until control is achieved. Badly fouled systems should be cleaned before treatment is begun.

SUBSEQUENT DOSE: When microbial control is evident, add 35 - 219 ppm Nalco 77352 (0.3 - 1.86 pound or 4.5 - 28 fluid ounce of Nalco 77352 per 1000 gallon of water in the system) weekly or as needed to maintain control.

Nalco 77352 weighs 8.4 pounds/gallon.

CONDITIONS OF SALE AND WARRANTY

Nalco Company warrants that this product conforms to its chemical description and is reasonably fit for the purpose stated on the label only when used in accordance with label directions and as defined the Directions for Use on this label. NALCO COMPANY MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, EITHER OF MERCHANTABILITY OR FITNESS, FOR A PARTICULAR USE. Handling, storage, and use of the product by Buyer or User are beyond the control of Nalco Company and Seller. Risks such as ineffectiveness or other unintended consequences resulting from, but not limited to, failure to follow directions will be assumed by the Buyer or User. TO THE EXTENT PERMITTED BY LAW, NEITHER NALCO COMPANY NOR SELLER SHALL BE LIABLE FOR CONSEQUENTIAL, SPECIAL OR INDIRECT DAMAGES RESULTING FROM THE HANDLING, STORAGE OR USE OF THIS PRODUCT.