

PRECAUTIONARY STATEMENTS: HAZARDS TO HUMANS AND DOMESTIC ANIMALS: DANGER: Corrosive. Causes irreversible eye damage. May be fatal if inhaled. Causes skin irritation. Harmful if swallowed or absorbed through the skin. Do not get in eyes, on skin, or on clothing. Do not breathe vapor or spray mist.

APPLICATORS AND OTHER HANDLERS MUST WEAR: Goggles or face shield, coveralls worn over long sleeve shirt and long pants, chemical resistant gloves (such as Barrier Laminate, Butyl Rubber, Neoprene Rubber, Nitrile Rubber) and shoes plus socks, chemical resistant headgear for overhead exposure and chemical resistant apron when cleaning equipment, mixing or loading. Wear a mask or pesticide respirator jointly approved by the Mine Safety Health Administration and the National Institute for Occupational Safety and Health. Wash thoroughly with soap and water after handling.

USER SAFETY REQUIREMENTS:

Follow manufacturer's instructions for cleaning/ maintaining PPE. If no such instructions exist for washables, use detergent and hot water. Keep and wash PPE separately from other laundry.

USER SAFETY RECOMMENDATIONS:

Users should wash hands before eating, drinking, chewing gum, using tobacco or using the toilet. Users must remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users must remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible wash thoroughly.

FIRST AID:

If in Eyes: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a Poison Control Center or doctor for treatment advice.

If on Skin or Clothing: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a Poison Control Center or doctor for treatment advice.

If Inhaled: Move person to fresh air. If person is not breathing, call 911 or an ambulance, and then give artificial respiration, preferably mouth-to-mouth, if possible. Call a Poison Control Center or doctor for further treatment advice.

If Swallowed: Call a Poison Control Center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a Poison Control Center or doctor. Do not give anything by mouth to an unconscious person. Have the product container or label with you when calling a poison control center or doctor, or going for treatment.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

In case of emergency, for additional information call 1-800-654-6911.

OMACIDE IPBC 30 DPG INDUSTRIAL FUNGICIDE

ACTIVE INGREDIENT:

3-Iodo-2-propynylbutylcarbamate...30%
Inert Ingredients.....70%
Total.....100%



LICENSED

PERIOD **2014-2016** LIC. NO.

9338.230

KEEP OUT OF REACH OF CHILDREN

DANGER

SEE FIRST AID & ADDITIONAL PRECAUTIONARY STATEMENTS
ON SIDE PANEL

MANUFACTURED FOR:



**Arch
Chemicals,
Inc.**

5660 New Northside Drive, Suite 1100
Atlanta, GA 30328

Made in the USA

Omacide® is a registered trademark of Arch Chemicals, Inc.

EPA Reg. No. 1258-1230

EPA Est. No. 1258-NY-3

Net Wt. 2200 Lbs.



LICENSED

PERIOD **2011-2013** LIC. NO.

STORAGE AND DISPOSAL: Do not contaminate water, food, or feed by storage or disposal.

PESTICIDE STORAGE: Keep container tightly closed when not in use. Do not reuse container. Do not store with strong oxidizing agents or strong (concentrated) acids.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance. Triple rinse as follows: Empty remaining contents into application equipment or a mix tank. Fill the container 1/4 full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times.

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container. Offer for recycling if available. Triple rinse container promptly after emptying. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, ponds, streams, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

DIRECTIONS FOR USE: It is a violation of federal law to use this product in a manner inconsistent with its labeling. Do not apply this product in a way that will contact workers or other persons.

TO INHIBIT THE GROWTH OF MILDEW ON PAINTS & STAINS: This product, used in solvent and waterborne paints and stains will inhibit the growth of mildew. Addition, by pouring from the container, should be at the end of the manufacturing process and allowed to mix long enough to be adequately dispersed and should not be added to hot paint. Typical levels for protection against mildew on painted or stained surfaces are 0.35-1.7 % by weight on wet paint. For example, a house paint with a wet density of 10 lbs/gallon would use 3.5- 17.0 lbs. of this product per 100 gallons of wet paint. Where the climate is severe and mildew growth is a major problem for painted surfaces, more would be required, as much as 2.7 % by weight on wet paint. For interior paint use, approximately half the exterior concentrations should be used, 0.2% to 0.9% by weight on wet paint. Appropriate levels are best determined by field trials.

TO INHIBIT THE GROWTH OF FUNGI IN AQUEOUS METALWORKING, CUTTING, COOLING & LUBRICATING

CONCENTRATES: Add, by pouring from the container, an amount that will give up to 3333 ppm in the diluted fluid. The amount required in the concentrate will depend on the end use dilution. For example: If the desired level of this product in the diluted fluid is 333 ppm, and the end use dilution of the fluid is 5%, then a 0.666% concentration of this product is required in the concentrate ($333 \text{ ppm} / 0.05 = 6660 \text{ ppm}$ or 0.666%).

TO INHIBIT THE GROWTH OF FUNGI IN AQUEOUS METALWORKING, CUTTING, & LUBRICATING FLUIDS: Add, by pouring from the container, up to 3333 parts per million (0.333% v/v) of this product to the diluted fluid (0.33 gallons per 100 gallons of solution or 3.3 liters per 1000 liters of solution. This product may be added to the fluid at the time it is prepared (diluted) or to the reservoir (sump) containing the fluid after it is put into use. If it is added to the reservoir, the fluid should be circulated after addition to ensure mixing.

PRECAUTIONARY STATEMENTS: HAZARDS TO HUMANS AND DOMESTIC ANIMALS: DANGER: Corrosive. Causes irreversible eye damage. May be fatal if inhaled. Causes skin irritation. Harmful if swallowed or absorbed through the skin. Do not get in eyes, on skin, or on clothing. Do not breathe vapor or spray mist.

APPLICATORS AND OTHER HANDLERS MUST WEAR: Goggles or face shield, coveralls worn over long sleeve shirt and long pants, chemical resistant gloves (such as Barrier Laminate, Butyl Rubber, Neoprene Rubber, Nitrile Rubber) and shoes plus socks, chemical resistant headgear for overhead exposure and chemical resistant apron when cleaning equipment, mixing or loading. Wear a mask or pesticide respirator jointly approved by the Mine Safety Health Administration and the National Institute for Occupational Safety and Health. Wash thoroughly with soap and water after handling.

USER SAFETY REQUIREMENTS:

Follow manufacturer's instructions for cleaning/ maintaining PPE. If no such instructions exist for washables, use detergent and hot water. Keep and wash PPE separately from other laundry.

USER SAFETY RECOMMENDATIONS:

Users should wash hands before eating, drinking, chewing gum, using tobacco or using the toilet. Users must remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users must remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible wash thoroughly.

FIRST AID:

If in Eyes: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a Poison Control Center or doctor for treatment advice.

If on Skin or Clothing: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a Poison Control Center or doctor for treatment advice.

If Inhaled: Move person to fresh air. If person is not breathing, call 911 or an ambulance, and then give artificial respiration, preferably mouth-to-mouth, if possible. Call a Poison Control Center or doctor for further treatment advice.

If Swallowed: Call a Poison Control Center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a Poison Control Center or doctor. Do not give anything by mouth to an unconscious person. Have the product container or label with you when calling a poison control center or doctor, or going for treatment.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

In case of emergency, for additional information call 1-800-654-6911.

OMACIDE IPBC 30 DPG INDUSTRIAL FUNGICIDE

ACTIVE INGREDIENT:

3-Iodo-2-propynylbutylcarbamate...30%
Inert Ingredients.....70%
Total.....100%

KEEP OUT OF REACH OF CHILDREN

DANGER

SEE FIRST AID & ADDITIONAL PRECAUTIONARY STATEMENTS
ON SIDE PANEL

MANUFACTURED FOR:



5660 New Northside Drive, Suite 1100
Atlanta, GA 30328

Made in the USA

Omacide® is a registered trademark of Arch Chemicals, Inc.

EPA Reg. No. 1258-1230
EPA Est. No. 1258-NY-3

Net Wt. 2200 Lbs.

STORAGE AND DISPOSAL: Do not contaminate water, food, or feed by storage or disposal.

PESTICIDE STORAGE: Keep container tightly closed when not in use. Do not reuse container. Do not store with strong oxidizing agents or strong (concentrated) acids.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance. Triple rinse as follows: Empty remaining contents into application equipment or a mix tank. Fill the container 1/4 full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times.

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container. Offer for recycling if available. Triple rinse container promptly after emptying. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, ponds, streams, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

DIRECTIONS FOR USE: It is a violation of federal law to use this product in a manner inconsistent with its labeling. Do not apply this product in a way that will contact workers or other persons.

TO INHIBIT THE GROWTH OF MILDEW ON PAINTS & STAINS: This product, used in solvent and waterborne paints and stains will inhibit the growth of mildew. Addition, by pouring from the container, should be at the end of the manufacturing process and allowed to mix long enough to be adequately dispersed and should not be added to hot paint. Typical levels for protection against mildew on painted or stained surfaces are 0.35-1.7 % by weight on wet paint. For example, a house paint with a wet density of 10 lbs/gallon would use 3.5- 17.0 lbs. of this product per 100 gallons of wet paint. Where the climate is severe and mildew growth is a major problem for painted surfaces, more would be required, as much as 2.7 % by weight on wet paint. For interior paint use, approximately half the exterior concentrations should be used, 0.2% to 0.9% by weight on wet paint. Appropriate levels are best determined by field trials.

TO INHIBIT THE GROWTH OF FUNGI IN AQUEOUS METALWORKING, CUTTING, COOLING & LUBRICATING

CONCENTRATES: Add, by pouring from the container, an amount that will give up to 3333 ppm in the diluted fluid. The amount required in the concentrate will depend on the end use dilution. For example: If the desired level of this product in the diluted fluid is 333 ppm, and the end use dilution of the fluid is 5%, then a 0.666% concentration of this product is required in the concentrate (333 ppm/0.05 = 6660 ppm or 0.666%).

TO INHIBIT THE GROWTH OF FUNGI IN AQUEOUS METALWORKING, CUTTING, & LUBRICATING FLUIDS:

Add, by pouring from the container, up to 3333 parts per million (0.333% v/v) of this product to the diluted fluid (0.33 gallons per 100 gallons of solution or 3.3 liters per 1000 liters of solution. This product may be added to the fluid at the time it is prepared (diluted) or to the reservoir (sump) containing the fluid after it is put into use. If it is added to the reservoir, the fluid should be circulated after addition to ensure mixing.