STATE OF HAWAII
Department of Agriculture
ACCEPTED
LICENSE NO. 9669.194

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
WARNING

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding or sandblasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

FIRST AID

IF SWALLOWED:
- Immediately call a poison control center or doctor.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give ANY liquid to the person.
- Do not give anything by mouth to an unconscious person.

IF ON SKIN OR CLOTHING:
- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

IF INHALED:
- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or doctor for further treatment advice.

IF IN EYES:
- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

OTHER: Have the product container or label with you when calling a poison control center or doctor or going for treatment.

NOTE TO PHYSICIAN: Contains petroleum distillate – vomiting may cause aspiration pneumonia.

ENVIRONMENTAL HAZARDS:

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARD:

COMBUSTIBLE. Do not use or store near heat or open flame. . .

STORAGE AND DISPOSAL:

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.

Flash Point: Single Pack 80°F

VOC:3.25 lbs./U.S. Gal. (390 g/l) as supplied (EPA Method 24)

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of International Paint LLC including surface preparation, proper application, and environmental conditions. Therefore, International Paint LLC cannot guarantee this product's suitability for your particular purpose or application. Implied warranties of fitness for a particular purpose and of merchantability are excluded. International Paint LLC shall not, under any circumstances, be liable for incidental or consequential damages. By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at the option of International Paint LLC

Product Identity

Interspeed® 6200NA Antifouling

Color

Black

Sales Reference

BQA659/5GL

Net Contents

5 U.S. Gallons (18.93 Liters)

MSDS Reference **Revision**

BQA659 A0

Batch

BQA659/5GL

FOR COMMERCIAL USE ONLY

For specific state registrations contact your International Representative

Active Ingredient:	
CUPROUS OXIDE	21.31%
Inert Ingredients:	78.69%
.	100.00%
Copper as Metallic	**18.93%**

Contains petroleum distillates.

KEEP OUT OF REACH OF CHILDREN
WARNING

See side panel for additional Precautionary Statements

EPA Reg. No.: 2693-176 EPA Est. No.: 2693-TX-1

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

GENERAL DESCRIPTION
This product is an antifouling protective coating resistant to algae, barnacles and other marine fouling in fresh, sea and brackish waters on steel boat hulls. This product is for commercial and non-commercial use.

SURFACE PREPARATION AND COMPATABILITY: Surface preparation directions must be followed exactly in order to insure adhesion. Surface must always be clean and dry prior to painting.

GENERAL APPLICATION PROCEDURES: Airless spray is recommended. Tip Size 21-26 thou. inch., pump ratio of 30:1 or greater. For small areas, brush or roller may be used but multiple coats may be required to achieve the required dry film thickness. It is recommended to apply by airless spray one (1) or two (2) full coats of this product.

MIXING AND THINNING INSTRUCTIONS: Mix thoroughly with power mixer prior to application. This coating is designed to be applied without thinning. Should thinning be necessary consult your international representative prior to altering this coating.

CLEAN UP: For tools, equipment, etc., use international GTA007.

MINIMUM DRY AND LAUNCHING TIMES: Minimum drying time between coats is 8 hours, and before launching is 12 to 16 hours depending on paint thickness at a temperature of 73°F.

THEORECTICAL COVERAGE: 497 square feet per gallon, per coat at 2.0 mils D.T.F. Consult your international representative for practical application coverage. Practical square foot coverage per gallon per coat is directly proportional to surface, application techniques and climatic conditions.
APPLICATION SYSTEMS
EXISTING ANTIFOULING SYSTEMS - GOOD CONDITION: High pressure fresh water wash with a minimum of 2500 p.s.i. and/or scrape to remove all marine growth, slime, salts, etc. Spot blast all areas of corrosion to a Near White Metal Standard of SSPC-SP10-85. Blow down with clean and dry high pressure air to remove all spent abrasives. Apply an approved underwater anticorrosive system.

POOR CONDITION: For "optimum" results, blast entire area to a Near White Metal Standard SSPC-SP10-85. Apply an approved underwater anticorrosive system.

NEW SHIP CONSTRUCTION: Blast entire area to a Near White Metal Standard SSPC-SP10-85. Blow down with clean and dry high pressure air to remove all spent abrasives. Apply an approved underwater anticorrosive system.

International Paint LLC
Union, NJ 07083 • Houston, TX 77091

International and Interspeed are trade marks of the AkzoNobel Group of Companies.

STATE OF HAWAII
Department of Agriculture
ACCEPTED
LICENSE NO.
9669.194

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
WARNING

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding or sandblasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

FIRST AID

IF SWALLOWED:
- Immediately call a poison control center or doctor.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give ANY liquid to the person.
- Do not give anything by mouth to an unconscious person.

IF ON SKIN OR CLOTHING:
- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

IF INHALED:
- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or doctor for further treatment advice.

IF IN EYES:
- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

OTHER: Have the product container or label with you when calling a poison control center or doctor or going for treatment.

NOTE TO PHYSICIAN: Contains petroleum distillate – vomiting may cause aspiration pneumonia.

ENVIRONMENTAL HAZARDS:

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARD:

COMBUSTIBLE. Do not use or store near heat or open flame.

STORAGE AND DISPOSAL:

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.

Flash Point: Single Pack 80°F
VOC:3.21 lbs./U.S. Gal. (385 g/l) as supplied (EPA Method 24)

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of International Paint LLC including surface preparation, proper application, and environmental conditions. Therefore, International Paint LLC cannot guarantee this product's suitability for your particular purpose or application. Implied warranties of fitness for a particular purpose and of merchantability are excluded. International Paint LLC shall not, under any circumstances, be liable for incidental or consequential damages. By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at the option of International Paint LLC

Product Identity

Interspeed® 6200NA Antifouling

Color

Red

Sales Reference

BQA654/5GL

Net Contents

5 U.S. Gallons (18.93 Liters)

MSDS Reference **Revision**

BQA654 A0

Batch

*BQA654/5G

FOR COMMERCIAL USE ONLY

For specific state registrations contact your International Representative

Active Ingredient:	
CUPROUS OXIDE	21.31%
Inert Ingredients:	78.69%
	100.00%

Copper as Metallic 18.93%

Contains petroleum distillates.

KEEP OUT OF REACH OF CHILDREN
WARNING

See side panel for additional Precautionary Statements

EPA Reg. No.: 2693-176 EPA Est. No.: 2693-TX-1

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

GENERAL DESCRIPTION
This product is an antifouling protective coating resistant to algae, barnacles and other marine fouling in fresh, sea and brackish waters on steel boat hulls. This product is for commercial and non-commercial use.

SURFACE PREPARATION AND COMPATABILITY: Surface preparation directions must be followed exactly in order to insure adhesion. Surface must always be clean and dry prior to painting.

GENERAL APPLICATION PROCEDURES: Airless spray is recommended. Tip Size 21-26 thou. inch., pump ratio of 30:1 or greater. For small areas, brush or roller may be used but multiple coats may be required to achieve the required dry film thickness. It is recommended to apply by airless spray one (1) or two (2) full coats of this product.

MIXING AND THINNING INSTRUCTIONS: Mix thoroughly with power mixer prior to application. This coating is designed to be applied without thinning. Should thinning be necessary consult your International representative prior to altering this coating.

CLEAN UP: For tools, equipment, etc., use international GTA007.

MINIMUM DRY AND LAUNCHING TIMES: Minimum drying time between coats is 8 hours, and before launching is 12 to 16 hours depending on paint thickness at a temperature of 73°F.

THEORECTICAL COVERAGE: 497 square feet per gallon, per coat at 2.0 mils D.T.F. Consult your International representative for practical application coverage. Practical square foot coverage per gallon per coat is directly proportional to surface, application techniques and climatic conditions.
APPLICATION SYSTEMS
EXISTING ANTIFOULING SYSTEMS - GOOD CONDITION: High pressure fresh water wash with a minimum of 2500 p.s.i. and/or scrape to remove all marine growth, slime, salts, etc. Spot blast all areas of corrosion to a Near White Metal Standard of SSPC-SP10-85. Blow down with clean and dry high pressure air to remove all spent abrasives. Apply an approved underwater anticorrosive system.

POOR CONDITION: For "optimum" results, blast entire area to a Near White Metal Standard SSPC-SP10-85. Apply an approved underwater anticorrosive system.

NEW SHIP CONSTRUCTION: Blast entire area to a Near White Metal Standard SSPC-SP10-85. Blow down with clean and dry high pressure air to remove all spent abrasives. Apply an approved underwater anticorrosive system.

International Paint LLC
Union, NJ 07083 • Houston, TX 77091

International and Interspeed are trade marks of the AkzoNobel Group of Companies.