



LICENSED PERIOD 2014-2016 LIC. NO.

PERIOD 2011-2013 LIC. NO. **9669.195**

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
WARNING**

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding or sandblasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

FIRST AID

IF SWALLOWED:

- Immediately call a poison control center or doctor.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give any liquid to the person.
- Do not give anything by mouth to an unconscious person.

IF ON SKIN OR CLOTHING:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

IF INHALED:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or doctor for further treatment advice.

IF IN EYES:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

OTHER: Have the product container or label with you when calling a poison control center or doctor or going for treatment.

NOTE TO PHYSICIAN: Contains petroleum distillate -- vomiting may cause aspiration pneumonia.

ENVIRONMENTAL HAZARDS:

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARD: Flammable. Keep away from heat and open flame.

STORAGE AND DISPOSAL:

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container 1/4 full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of International Paint LLC including surface preparation, proper application, and environmental conditions. Therefore, International Paint LLC cannot guarantee this product's suitability for your particular purpose or application. Implied warranties of fitness for a particular purpose and of merchantability are excluded. International Paint LLC shall not, under any circumstances, be liable for incidental or consequential damages. By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at the option of International Paint LLC.

Product Identity

Interspeed® 6400NA

Controlled Depletion Polymer Antifouling

Color

Black

Sales Reference

BQA679/5GL

Net Contents


5 U.S. Gallons (18.93 Liters)

MSDS Reference Revision

BQA679

A0

Batch



FOR COMMERCIAL USE ONLY

For specific state registrations contact your International Representative

Active Ingredient:

CUPROUS OXIDE

37.20%

Inert Ingredients:

62.80%

100.00%

Copper as Metallic

32.90%

Contains petroleum distillates.

**KEEP OUT OF REACH OF CHILDREN
WARNING**

See side panel for additional Precautionary Statements

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

PRODUCT DESCRIPTION: An economical antifouling designed to offer fouling protection against algae, barnacles and other marine foulings for extended periods of time. For use in fresh, salt and brackish waters. Low VOC. This product is for industrial use and professional application only. Not for sale to the general public.

PRODUCT INFORMATION

Finish/Sheen: Semi-Gloss (ASTM D-523)
 Converter: One pack
 Volume Solids: 80% ± 2% (ASTM D-2697)
 Mix Ratio: One pack
 Flash Point: 79°F (26°C) (Setaflash) (ASTM D-3278)
 Film Thickness: 4.0 mils (102 microns) dry specified equivalent to 6.7 mils (170 microns) wet.
 4.0-5.0 mils (102-127 microns) dry practical range equivalent to 6.7-8.3 mils (170-211 microns) wet.
 Theoretical Coverage: 240 sq. ft./gal. (4.0 mils/102 microns)
 Allow appropriate loss factors.

APPLICATION DETAILS:

Method: Airless spray, brush or roller.
 Thinner: Not recommended. If necessary use GTA007, see thinning section.
 Cleaner: GTA007

Drying Time (hours)	Overcoating Interval by Salt		Minimum Drying Time* before flooding (for 2x5 mil (125 microns) DFT coats)
	(ASTM D 1640 7.5.1)	(ASTM D-1640 7.2)	
Substrate Temp.	Touch	Min.	Max.
41°F (5°C)	4	12	Indefinite 3 days
73°F (23°C)	6	8	Indefinite 2 days
95°F (35°C)	2	4	Indefinite 1 day

*Refer to your International Representative for minimum drying time before flooding at higher dry film thicknesses and to Limitations section for maximum recommended atmospheric exposure time before flooding.

REGULATORY DATA

V.O.C.: 2.8 lbs./gal. (336 g/l) as supplied. (EPA METHOD 24)

SYSTEMS AND COMPATIBILITY: International should be consulted for detailed application advice, specification recommendations and as to the suitability of specific products on individual vessels.

LIMITATIONS: Apply in good weather when air and surface temperatures are above 35°F (2°C). Surface temperature must be at least 5°F (3°C) above dew point. For optimum application properties, bring material to 70-80°F (21-27°C) temperature range prior to mixing and application. Unmixed material (in closed containers) should be maintained in protected storage between 40° and 100°F (4-38°C).

Prolonged atmospheric exposure of this product may detract from antifouling performance. Recommended maximum exposure time before flooding:
 Temperate conditions 20 days
 Tropical conditions 7 days
 These times may be extended under certain conditions. Contact your local International Representative for advice.

To maximize performance, a minimum of two full coats at the recommended dry film thickness should be applied.

Technical and application data herein is for the purpose of establishing a general guideline of the coating and proper coating application procedures. Test performance results were obtained in a controlled laboratory environment and International makes no claim that the exhibited published test results, or any other tests, accurately represent results actually found in all field environments. As application, environmental and design factors can vary significantly, due care should be exercised in the selection, verification of performance, and use of the coating.

SURFACE PREPARATION: Paint only clean, dry surfaces. Remove all grease, oil, soluble contaminants and other detrimental foreign matter by "solvent cleaning" (SSPC-SP1).

NEW CONSTRUCTION: Dependent on yard procedures, consult International.

UNPAINTED SURFACES: Prepare surface and apply recommended primer. Apply one or more coats of this product as specified. (Consult the relevant primer data sheet for surface preparation and overcoating information.)

MAINTENANCE: Use controlled close high pressure fresh water washing (3,000 psi, 211 kg./sq. cm.) to clean the entire area, and remove any leached layer at the surface of the existing antifouling system. Repair corroded areas with the recommended anticorrosive primer and apply this product within the overcoating Interval specified for the primer (consult relevant primer data sheet). Apply the specified number of full coats of this product.

MIXING: This material is a one component coating. Always mix thoroughly with a power agitator before application.
APPLICATION: Apply by airless spray only. Application by other methods, brush or roller, may require more than one coat and is suggested for small areas only or initial stripe coating. Apply 6-7 mils (170 microns) wet which will yield 4.0 mils (100 microns) dry film thickness. Consult the following equipment recommendations or utilize suitable equal.

EQUIPMENT:

Brush: Use appropriate size China bristle brush.
 Roller: Use All Purpose Roller Cover with 3/8" (9.5mm) pile smooth to medium. Prewash roller cover to remove loose fibers prior to use.
 Airless Spray: Minimum 23:1 ratio pump; .021"-.026" (533-660 microns) orifice tip; 3/8" (9.5mm) ID high pressure material hose; 60 mesh tip filter.

THINNING: do not thin beyond your state's compliance. Material is supplied at spray viscosity and normally does not need thinning. If thinning is necessary, thin up to a maximum of 4 ounces (118ml) per gallon (3.79 l) with International GTA007 Thinner.

WORK STOPPAGES & CLEAN UP: Clean all equipment immediately after use with International GTA007 Thinner. Spray equipment requires flushing with this solvent. It is good working practice to periodically flush out spray equipment during the course of the working day. Frequency will depend upon factors such as amount sprayed, temperature and elapsed time including work stoppages. Monitor material condition.

WELDING: In the event welding or flame cutting is performed on metal coated with this product, do so in accordance with instruction in ANSI/ASC Z49.1 "Safety in Welding and Cutting".

SAFETY: This product is not to be used without reference to the current relevant Product Data Sheet and Material Safety Data Sheet (MSDS). Prior to use, obtain, consult and follow both the Material Safety and Product Data Sheets for this product for details concerning both product and health and safety information. Read and follow all precautionary notices on the Material Safety and Product Data Sheets and this container label. If you do not fully understand these warnings and instructions or if you cannot strictly comply with them, do not use this product. Proper ventilation and protective measures must be provided during application and drying to keep solvent vapor concentrations within safe limits and to protect against toxic or oxygen deficient hazards and/or flash fire. Actual safety measures are dependent on application methods and work environment. This safety information is not a substitute for that contained in the Material Safety and Product Data Sheets. Medical Advisory Number 1-800-854-8813.
 UN Shipping No: 1263
STORAGE: Store in cool, dry conditions.
SHELF LIFE: One year minimum from date of manufacture when maintained in protected storage at 40-100°F (4-38°C). Subject to reinspection thereafter.

All representations and statements concerning the product on this label are accurate to the best of International's knowledge. Any statements herein are not intended to be specific recommendations or warranties of any product, combination of products or fitness for any particular purpose. Any warranty, if given, or specific Terms and Conditions of Sale are contained in International's Terms and Conditions of Sale. You should request a copy of this document and review it carefully.

International Paint LLC
 Union, NJ 07083 • Houston, TX 77091



LICENSED PERIOD 2014-2016 LIC. NO.

PERIOD 2011-2013 LIC. NO. 9669.195

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
WARNING

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding or sandblasting boat surfaces, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

FIRST AID

IF SWALLOWED:

- Immediately call a poison control center or doctor.
•Do not induce vomiting unless told to do so by a poison control center or doctor.
•Do not give any liquid to the person.
•Do not give anything by mouth to an unconscious person.

IF ON SKIN OR CLOTHING:

- Take off contaminated clothing.
•Rinse skin immediately with plenty of water for 15-20 minutes.
•Call a poison control center or doctor for treatment advice.

IF INHALED:

- Move person to fresh air.
•If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.
•Call a poison control center or doctor for further treatment advice.

IF IN EYES:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
•Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
•Call a poison control center or doctor for treatment advice.

OTHER: Have the product container or label with you when calling a poison control center or doctor or going for treatment.

NOTE TO PHYSICIAN: Contains petroleum distillate - vomiting may cause aspiration pneumonia.

ENVIRONMENTAL HAZARDS:

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARD: Flammable. Keep away from heat and open flame.

STORAGE AND DISPOSAL:

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container 1/4 full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of International Paint LLC including surface preparation, proper application, and environmental conditions. Therefore, International Paint LLC cannot guarantee this product's suitability for your particular purpose or application. Implied warranties of fitness for a particular purpose and of merchantability are excluded. International Paint LLC shall not, under any circumstances, be liable for incidental or consequential damages. By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at the option of International Paint LLC. International and Interspeed are trade marks of the AkzoNobel Group of Companies.

Product Identity

Interspeed® 6400NA
Controlled Depletion Polymer Antifouling

Color

Red

Sales Reference

BQA674/5GL


Net Contents

5 U.S. Gallons (18.93 Liters)

MSDS Reference Revision

BQA674 A0

Batch



FOR COMMERCIAL USE ONLY

For specific state registrations contact your International Representative

Table with 2 columns: Ingredient Name and Percentage. Includes Active Ingredient (CUPROUS OXIDE 37.20%), Inert Ingredients (62.80%), and Copper as Metallic (32.90%).

Contains petroleum distillates.

KEEP OUT OF REACH OF CHILDREN
WARNING

See side panel for additional Precautionary Statements

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

PRODUCT DESCRIPTION: An economical antifouling designed to offer fouling protection against algae, barnacles and other marine foulings for extended periods of time. For use in fresh, salt and brackish waters. Low VOC. This product is for industrial use and professional application only. Not for sale to the general public.

PRODUCT INFORMATION

Finish/Sheen: Semi-Gloss (ASTM D-523)
 Converter: One pack
 Volume Solids: 60% ± 2% (ASTM D-2697)
 Mix Ratio: One pack
 Flash Point: 79°F(26°C) (Setofflash) (ASTM D-3278)
 Film Thickness: 4.0 mils (102 microns) dry specified equivalent to 6.7 mils (170 microns) wet
 4.0-5.0 mils (102-127 microns) dry practical range equivalent to 6.7-8.3 mils (170-211 microns) wet
 Theoretical Coverage: 240 sq. ft./gal. (4.0 mils(102 microns))
 Allow appropriate loss factors.

APPLICATION DETAILS:

Method: Airless spray, brush or roller.
 Thinner: Not recommended. If necessary use GTA007, see thinning section.
 Cleaner: GTA007

Drying Time (hours)	Overcoating Interval by Self		Minimum Drying Time* before flooding (for 2x5 mil (125 microns) DFT coats)
	(ASTM D 1640 7.5.1)	(ASTM D-1640 7.8)	
Substrate Temp.	Touch	Min.	Max.
41°F (5°C)	6	12	Indefinite
73°F (23°C)	4	6	Indefinite
95°F (35°C)	2	4	Indefinite

*Refer to your International Representative for minimum drying time before flooding at higher dry film thicknesses and to Limitations section for maximum recommended atmospheric exposure time before flooding.

REGULATORY DATA

V.O.C.: 2.8 lbs./gal. (336 g/l) as supplied. (EPA METHOD 24)

SYSTEMS AND COMPATIBILITY: International should be consulted for detailed application advice, specification recommendations and as to the suitability of specific products on individual vessels.

LIMITATIONS: Apply in good weather when air and surface temperatures are above 35°F (2°C). Surface temperature must be at least 5°F (3°C) above dew point. For optimum application properties, bring material to 70-80°F (21-27°C) temperature range prior to mixing and application. Unmixed material (in closed containers) should be maintained in protected storage between 40° and 100°F (4-38°C).

Prolonged atmospheric exposure of this product may detract from antifouling performance. Recommended maximum exposure time before flooding:
 Temperate conditions 28 days
 Tropical conditions 7 days

These times may be extended under certain conditions. Contact your local International Representative for advice.

To maximize performance, a minimum of two full coats at the recommended dry film thickness should be applied.

Technical and application data herein is for the purpose of establishing a general guideline of the coating and proper coating application procedures. Test performance results were obtained in a controlled laboratory environment and International makes no claim that the exhibited published test results, or any other tests, accurately represent results actually found in all field environments. As application, environmental and design factors can vary significantly, due care should be exercised in the selection, verification of performance, and use of the coating.

SURFACE PREPARATION: Paint only clean, dry surfaces. Remove all grease, oil, soluble contaminants and other detrimental foreign matter by "solvent cleaning" (SSPC-SP1).

NEW CONSTRUCTION: Dependent on yard procedures, consult International.

UNPAINTED SURFACES: Prepare surface and apply recommended primer. Apply one or more coats of this product as specified. (Consult the relevant primer data sheet for surface preparation and overcoating information.)

MAINTENANCE: Use controlled close high pressure fresh water washing (3,000 psi, 211 kg./sq. cm.) to clean the entire area, and remove any leached layer at the surface of the existing antifouling system. Repair corroded areas with the recommended anticorrosive primer and apply this product within the overcoating interval specified for the primer (consult relevant primer data sheet). Apply the specified number of full coats of this product.

MIXING: This material is a one component coating. Always mix thoroughly with a power agitator before application.

APPLICATION: Apply by airless spray only. Application by other methods, brush or roller, may require more than one coat and is suggested for small areas only or initial stripe coating. Apply 5-7 mils (170 microns) wet which will yield 4.0 mils (100 microns) dry film thickness. Consult the following equipment recommendations or utilize suitable equal.

EQUIPMENT:

Brush: Use appropriate size China bristle brush.
 Roller: Use All Purpose Roller Cover with 3/8" (9.5mm) pile smooth to medium. Prewash roller cover to remove loose fibers prior to use.
 Airless Spray: Minimum 23:1 ratio pump; .021"-.026" (533-660 microns) orifice tip; 3/8"(9.5mm) ID high pressure material hose; 60 mesh tip filter.

THINNING: do not thin beyond your state's compliance. Material is supplied at spray viscosity and normally does not need thinning. If thinning is necessary, thin up to a maximum of 4 ounces (118ml) per gallon (3.79 L) with International GTA007 Thinner.

WORK STOPPAGES & CLEAN UP: Clean all equipment immediately after use with International GTA007 Thinner. Spray equipment requires flushing with this solvent. It is good working practice to periodically flush out spray equipment during the course of the working day. Frequency will depend upon factors such as amount sprayed, temperature and elapsed time including work stoppages. Monitor material condition.

WELDING: In the event welding or flame cutting is performed on metal coated with this product, do so in accordance with instruction in ANSI/ASC Z49.1 "Safety in Welding and Cutting".

SAFETY: This product is not to be used without reference to the current relevant Product Data Sheet and Material Safety Data Sheet (MSDS). Prior to use, obtain, consult and follow both the Material Safety and Product Data Sheets for this product for details concerning both product and health and safety information. Read and follow all precautionary notices on the Material Safety and Product Data Sheets and this container label. If you do not fully understand these warnings and instructions or if you cannot strictly comply with them, do not use this product. Proper ventilation and protective measures must be provided during application and drying to keep solvent vapor concentrations within safe limits and to protect against toxic or oxygen deficient hazards and/or flash fire. Actual safety measures are dependent on application methods and work environment. This safety information is not a substitute for that contained in the Material Safety and Product Data Sheets. Medical Advisory Number 1-800-854-6813.

UN Shipping No: 1263

STORAGE: Store in cool, dry conditions.

SHELF LIFE: One year minimum from date of manufacture when maintained in protected storage at 40-100°F (4-38°C). Subject to reinspection thereafter.

All representations and statements concerning the product on this label are accurate to the best of International's knowledge. Any statements herein are not intended to be specific recommendations or warranties of any product, combination of products or fitness for any particular purpose. Any warranty, if given, or specific Terms and Conditions of Sale are contained in International's Terms and Conditions of Sale. You should request a copy of this document and review it carefully.

International Paint LLC
 Union, NJ 07083 • Houston, TX 77091