



STATE OF HAWAII
Department of Agriculture
ACCEPTED
LICENSE NO.

9734.107

12/12/11

50-603 12oz


50-603 gal 2/c
PMS 200 PMS 281

West Marine®

OutDrive

Antifouling Spray Paint

For Outdrives,
Outboards & Props



BLACK
Model 11046620



DANGER!
EXTREMELY FLAMMABLE
CONTENTS UNDER PRESSURE
KEEP OUT OF REACH OF CHILDREN
See back panel for additional precautionary statements
NET CONTENTS: 12 oz. (340 grams)

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.
NEW OUTDRIVE UNIT: Lightly sand the factory paint with 80-grit sandpaper to dull the surface, clean with Pettit 120T-10 Brushing Thinner and apply two coats of Outdrive Antifouling Spray Paint allowing a minimum of 6 hours at 70°F or 12 hours at 50°F drying time between coats.
OUTDRIVES PREVIOUSLY PAINTED WITH ANTI-FOULING PAINT: Lightly sand the old antifouling paint, and then clean the sanded surface with Pettit 120T-10 Brushing Thinner. Apply one coat of Pettit 6627 Tie-Coat Primer and allow to dry at least 4 hours, then apply two coats of Outdrive Antifouling Spray Paint allowing a minimum of 6 hours drying time between coats. If the old paint has been chipped to bare metal, the entire surface must be primed. Smaller areas less than one square inch can be spot primed prior to applying Outdrive Antifouling Spray Paint.
BARE ALUMINUM OUTDRIVES AND OUTBOARDS: The metal surface should be properly sandblasted or cleaned to a bright metal. Apply two coats of Pettit Aluma Protect Aluminum Epoxy Primer 4400/4401 followed by two coats of Pettit Protect High Build Epoxy Primer 4700/4701 and two coats of Outdrive Antifouling Spray Paint.
DRY TIMES: This paint will dry to the touch in 30 minutes. The minimum recoat time is 6 hours. The minimum dry time between the final coat and launching is 16 hours. Under adverse drying conditions such as those encountered on cool or damp days extend the dry times by 50% in order to ensure that all the solvent is out of the paint film. There is no maximum time before launching.
APPLICATION: Shake can vigorously at least one minute after the mixing ball begins to rattle. Shake can often during use. Hold can 10-12 inches from the surface. Depress nozzle and spray with smooth even strokes. When finished spraying, clear spray valve by turning can upside down and spraying until no more paint comes out.
COVERAGE: One can covers approximately 15 square feet. Use entire contents of one can for each lower unit or outboard.
CLEAN-UP: Use Pettit 120T-10 Brushing Thinner.

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

ANGER: Corrosive. Causes skin burns and moderate eye irritation. Do not get in eyes, on skin, or on clothing. Avoid breathing spray mist, vapors or sanding dust. While spraying and/or sanding boat surfaces, wear a NIOSH/MSHA certified mask or respirator. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, or using tobacco. Wear coveralls worn over long-sleeved shirt and long pants, chemical resistant gloves, protective eyewear (goggles, face shield or safety glasses), socks, and chemical resistant footwear. Remove contaminated clothing and wash clothing before reuse. May pose an aspiration pneumonia hazard.

FIRST AID

IF IN EYES:	<ul style="list-style-type: none"> Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.
IF SWALLOWED:	<ul style="list-style-type: none"> Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.
IF INHALED:	<ul style="list-style-type: none"> Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.
IF ON SKIN OR CLOTHING:	<ul style="list-style-type: none"> Take off contaminated clothing. Rinse skin immediately with plenty of water for 15 – 20 minutes. Call a poison control center or doctor for treatment advice.
HOT LINE NUMBER	
Have the product container or label with you when calling a poison control center or doctor, or going for treatment. You may also contact 1-800-548-0489 for emergency medical treatment information.	
NOTE TO PHYSICIAN	
Probable mucosal damage may contraindicate the use of gastric lavage. This product contains petroleum distillates. Vomiting may cause aspiration pneumonia.	

ENVIRONMENTAL HAZARDS: This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent into sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.
PHYSICAL OR CHEMICAL HAZARDS: EXTREMELY FLAMMABLE! Contents under pressure. Keep away from heat, sparks or open flame. Do not puncture or incinerate container. Exposure to temperatures above 130° F may cause bursting. **Use only with adequate ventilation during mixing, application and drying.** Use absorbent clean-up material if spilled. For fires, blanket flames with foam, CO₂ or dry chemical. Wear NIOSH/MSHA certified breathing equipment.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.
PESTICIDE STORAGE: Keep away from heat, sparks and open flame. Store in a closed, properly labeled container in a cool, dry place. Keep container tightly closed and upright to prevent leakage. In case of spillage, absorb and dispose of in accordance with local and state authorities.
PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.
CONTAINER DISPOSAL: Do not puncture or incinerate. A completely empty can can be disposed of with household trash. Wrap in paper before disposing.

MAXIMUM VOC: 75%
NOTICE! THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.
GENERAL DESCRIPTION: West Marine Outdrive Antifouling Spray Paint is an antifouling protective coating resistant to slime, algae, barnacles and other marine and freshwater fouling organisms. This product's unique controlled erosion polymers combined with the latest organic biocide technology minimizes coating build-up and keeps underwater surfaces smooth and clean. This product is for use in fresh, salt or brackish water on underwater metal parts such as outdrive units and outboard motors below the waterline. This paint is intended for use on underwater metal surfaces of recreational and commercial vessels of any size.

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of West Marine including surface preparation, proper application, and environmental conditions. Therefore, West Marine cannot guarantee this product's suitability for your particular purpose or application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND OF MERCHANTABILITY ARE EXCLUDED. WEST MARINE SHALL NOT, UNDER ANY CIRCUMSTANCES, BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at West Marine's option.

Contains Petroleum Distillates
EPA Est. No.: 81405-WI-001
EPA Reg. No.: 60061-120

ACTIVE INGREDIENT:
Zinc Oxadine® 1.43%
INERT INGREDIENTS: 98.57%
Total 100.0%

KOP-COAT, INC.
PETTIT PAINT BRAND
BUCKRAM, NJ 07066 An RPM Company



Manufactured for
West Marine
Watsonville, CA 95076
Medical Emergencies
1-800-548-0489

50-603

12/09/11

421017