KOP-COAT

BAZOOKA ™

Sapstain and Mold Control Product

U.S. Patent Number 6,375,727and 7,056,919 additional Patents Pending

Aids in the control of blue stain, mold and decay of freshly cut lumber, dry lumber and other wood based products when properly used. Effective on softwoods including Douglas fir, White fir, Spruce, Hemlock, the Pines including both the Southern and Western Yellow Pines, Eastern and Western White Pines and many of the hardwoods.

KEEP OUT OF REACH OF CHILDREN

DANGER - PELIGRO

See side panel for additional precautionary statements.

Read Warranty On Side Panel Before Buying Or Using. If Such Terms Are Not Acceptable, Return At Once Unopened.

EPA Reg. No. 60061-112
EPA Est. No. 60061-MO-1

ACTIVE INGREDIENTS	
Diiodomethyl-para-Tolyl sulfone	0.95%
Propiconazole	3.50%
3-Iodo-2-Propynyl Butyl Carbamate	3.50%
OTHER INGREDIENTS	92.05%
TOTAL	**100.00%**

FIRST AID

IF IN EYES:	• Hold eye open and rinse slowly and gently with water for 15-20 minutes. • Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. • Call a poison control center or doctor for treatment advice
IF SWALLOWED:	• Call poison control center or doctor immediately for treatment advice. • Have person sip a glass of water if able to swallow. • Do not induce vomiting unless told to do so by the poison control center or doctor. • Do not give anything by mouth to an unconscious person.
IF ON SKIN OR ON CLOTHING:	• Take off contaminated clothing. • Rinse skin immediately with plenty of water for 15-20 minutes. • Call a poison control center or doctor for treatment advice.
IF INHALED:	• Move person to fresh air. • If person is not breathing, call 911 or an ambulance, then gives artificial respiration, preferably mouth-to-mouth if possible. • Call a poison control center or doctor for further treatment advice.
Have the product container or label with you when calling a poison control center or doctor, or going for treatment. In case of emergency call toll free: 1-800-548-0489.	
NOTE TO PHYSICIAN:	Probable mucosal damage may contraindicate the use of gastric lavage.

Kop-Coat, Inc.
Protection Products Division
5137 Southwest Avenue, St. Louis, MO 63110
314/772-2200

NET CONTENTS _____ U.S. GALLONS

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

GENERAL PRECAUTIONS AND RESTRICTIONS:

FOR INDUSTRIAL USE ONLY

DILUTE BEFORE USING

Do not apply this product in a way that will contact workers or other persons.

Wear synthetic rubber gloves or plastic coated gloves in handling solutions and freshly treated lumber.

Treated sawdust and other wood wastes should be disposed of properly and should not be used as mulch where it will come into contact with useful living plants. Care should be taken to prevent drip or spray from contacting ornamental shrubs, trees, grass, and other desirable vegetation.

GENERAL INFORMATION:

Freshly dipped or sprayed lumber should be protected from rain-washing. Dip tanks and drip aprons must be roofed, paved, and drained to prevent dilution and loss of the anti-stain solution. Treatment concentrations must be geared to achieve protection of the thickest or most valuable item being treated. The concentration of the ready-to-use solution must be adjusted to accommodate seasonal changes in the exposure, species being treated, Dip tanks, and spray equipment must be properly maintained.

MIXING INSTRUCTIONS:

For high-pressure spray applications: Thoroughly mix one gallon of BAZOOKA™ Sapstain and Mold Control Product per 2 to 500 gallons of water.

For dip applications: Thoroughly mix one gallon of BAZOOKA™ Sapstain and Mold Control Product per 20 to 1,000 gallons of water. In all cases, dilution levels will depend upon application methods, lumber species, and conditions of lumber storage. Mills should conduct tests to determine treatment requirements for their individual needs. Contact Kop-Coat for further information. When using proportioning pumps for mixing, this product should be maintained at temperatures above 50 °F to prevent inaccurate mixing due to viscosity changes. Minor proportioning rate changes can be affected by changing the setting on the pump dial.

NOTE: With normal dip or spray application long-term control of decay cannot be achieved. This product is intended to provide decay, mold, and blue stain control during storage. Such control would not likely extend to the use site.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

Pesticide Storage: Store in a closed, properly labeled container in a cool place. If static generating conditions exist, provide necessary grounding and bonding. Keep containers closed when not in use.

Pesticide Disposal: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Container Disposal: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

PHYSICAL OR CHEMICAL HAZARDS:

COMBUSTIBLE. DO NOT use, pour, spill, or store near heat or open flame.

IN CASE OF FIRE: Use dry chemicals, foam, water fog, or CO_2. Cool closed containers with water.

STATE OF HAWAII
Department of Agriculture
ACCEPTED
LICENSE NO. 9734.86

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
DANGER

CORROSIVE. Causes Irreversible Eye Damage and Skin Burns. Harmful if swallowed, inhaled or if absorbed through skin. Do not get in eyes, on skin, or on clothing. Avoid breathing vapors or spray mist. Wear protective eyewear (goggles, face shield or safety glasses). Wash thoroughly with soap and water after handling Remove contaminated clothing and wash clothing before reuse.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

Applicators and other handlers must wear:

1. Coveralls over long-sleeved shirt and long pants
2. chemical-resistant footwear plus socks
3. Goggles or face shield
4. chemical-resistant gloves (such as barrier laminate, nitrile rubber, neoprene rubber and viton)
5. Respirator with an organic vapor-removing cartridge with a prefilter approved for pesticides (MSHA/NIOSH approval prefix TC-23C) or a canister approved for pesticides (MSHA/NIOSH approval prefix TC-14G) or a NIOSH approved respirator with an organic vapor (OV) cartridge or canister with any R, P or HE prefilter
6. Follow manufacturers' instructions for cleaning/maintaining PPE. If no such instructions exist for washables, use detergent and hot water. Discard clothing or other absorbent materials that have been drenched or heavily contaminated with this products concentrate. Do not reuse them. Keep and wash PPE separately from other laundry.

USER SAFETY RECOMMENDATIONS

Users should:

- Wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet.
- Remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing.
- Remove personal protective equipment immediately after handling this product. Wash outside of gloves before removing. As soon as possible wash thoroughly.

ENVIRONMENTAL HAZARDS:

This pesticide is toxic to fish. Do not apply directly to any body of water or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment washwaters or rinsate. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other water unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

WARRANTY: We warrant this material to comply with our published specifications and to be of good merchantable quality and such as will regularly pass in the trade for goods within the description, and further warrant such goods to be fit for the normal purposes which goods are used. We assume no responsibility that the goods concerned in this contract are fit for any particular purpose for which they are being bought outside of the general purposes of goods of the description.

An RPM Company

PPD R02 06/06

RECEIVED
AUG 7 2007
Branch