

LONZA INC.  
90 BOROLINE ROAD  
ALLENDALE, NEW JERSEY 07401 USA  
EMERGENCY TEL NO. 309-697-7200

# Lonza

HEALTH	3
FLAMMABILITY	1
REACTIVITY	0

**UN3265**  
CORROSIVE LIQUID, ACIDIC,  
ORGANIC, N.O.S.  
(5-CHLORO-2-METHYL-4-  
ISOTHIAZOLIN-3-ONE)



LICENSED

PERIOD 2014-2016 LIC. NO. 9899.64

Manufactured for Lonza Inc.

## ISOCIL™ IG-C MICROBICIDE

### IN-CONTAINER AND INDUSTRIAL PRESERVATIVE

#### PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS DANGER

**CORROSIVE.** Causes eye damage and skin burns. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. May be harmful if inhaled. May be fatal if swallowed or absorbed through the skin. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Avoid breathing vapor or mist. Wash thoroughly with soap and water after handling and before eating, drinking or using tobacco. Remove contaminated clothing and wash before reuse.

#### ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste.

#### STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

**PESTICIDE STORAGE:** Open dumping is prohibited. Store in original container in areas inaccessible to children.

**PESTICIDE DISPOSAL:** Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray or mixture of rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

#### CONTAINER DISPOSAL:

Nonrefillable container. Do not reuse or refill this container. Clean container promptly after emptying. (Plastic containers): Triple rinse (or equivalent). Then offer for recycling or reconditioning or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by state and local authorities by burning. If burned, stay out of way of smoke. (Metal Containers): Triple rinse (or equivalent), then offer for recycling or reconditioning, or dispose of in a sanitary landfill, or by other procedures approved by state and local authorities. DO NOT cut or weld metal containers.

Active Ingredients	
5-Chloro-2-methyl-4-isothiazolin-3-one	1.11%
2-Methyl-4-isothiazolin-3-one	0.39%
Other Ingredients	98.50%
Total	100.00%

EPA Reg. No. 6836-259 EPA Est. No. 10508-PA-001

#### KEEP OUT OF REACH OF CHILDREN DANGER FIRST AID

**IF IN EYES:** Hold eye open and rinse slowly and gently with water for 15 - 20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.  
**IF ON SKIN OR CLOTHING:** Take off contaminated clothing. Rinse skin immediately with plenty of water for 15 - 20 minutes.  
**IF SWALLOWED:** Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to an unconscious person.  
**IF INHALED:** Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth if possible.  
Call a poison control center or doctor for treatment advice. Have the product container or label with you when calling a Poison Control Center or doctor or going for treatment.  
**NOTE TO PHYSICIAN:** Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed.

#### DIRECTIONS FOR USE

It is a violation of Federal law to use this product in manner inconsistent with its labeling.

Isocil IG-C is an in-container preservative for the control of bacteria and fungi in industrial and household consumer products including all purpose liquid cleaners; polishers and anti-tarnish products; air fresheners and carpet shampoos; pre-spotter; liquid dishwashing detergents; automotive appearance products such as cleaners, wax and polishes; liquid laundry products; package utility products such as premoistened sponges and mops; paints and coatings. Isocil IG-C preserves and controls the growth of bacteria and fungi in adhesives, polymer emulsions and natural latex, surfactant solutions, mineral and pigment slurries and dispersions; water-based building compounds, caulks and sealants; pesticides for non-food applications, including fungicides, herbicides, insecticides, repellents and biopesticides. Add 0.5 to 4.0 lbs Isocil IG-C (227 - 1814 g) to each 1000 lbs. (453.6 kg) of product to be treated to provide 8 - 63 ppm active isothiazolones. To ensure uniform distribution, slowly disperse Isocil IG-C into product with agitation. Mix thoroughly until evenly dispersed throughout product.

#### METALWORKING FLUID PRESERVATION

Isocil IG-C is used for the control of bacteria and fungi in soluble and emulsifiable-type aqueous metal working fluids. For the maintenance of a nonfouled system, use Isocil IG-C at 33 fl. ounces (2.2 lbs.) per 1000 gallons of emulsion every 4 weeks or 33 - 141 fl. ounces (2.2 - 9.5 lbs.) per 1000 gallons of emulsion every 8 - 12 weeks. For a noticeably fouled system use an initial dose of 66 - 141 fl. ounces (4.5 - 9.5 lbs.) per 1000 gallons of emulsion to be followed by subsequent maintenance dosages depending upon the treatment interval noted above. A higher dosage and / or increased frequency of treatment may be required depending upon the rate of dilution of the preservative with makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc.

Isocil IG-C must be dispensed into the use-solution of the metalworking fluid using a metering pump and uniformly dispersed throughout the system.

#### METAL CLEANING FLUID PRESERVATION

Isocil IG-C is used as a preservative for use in the manufacture and use of alkaline, acid and emulsion-based metal cleaning fluids typically used in electroplating, phosphatizing, galvanizing and general metal cleaning operations. For addition to a metal cleaning concentrate, add Isocil IG-C at a level to ensure that the final use-dilution fluid will contain 420 - 1670 ppm product (6.25 - 25 ppm active isothiazolones). For direct addition to a fouled system, add 52.5 - 210 fl. ounces (3.6 - 14.4 lbs.) of Isocil IG-C to each 1000 gallons of use-dilution metal cleaning fluid every 3 to 4 weeks to provide 420 - 1670 ppm product (6.25 - 25 ppm active isothiazolones). A higher dosage range and / or increased frequency of treatment may be required depending upon rate of dilution of the preservative with makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc.

Isocil IG-C must be dispensed into the use-dilution of the metal cleaning fluid using a metering pump and uniformly dispersed throughout the system.

#### WATER-BASED HYDRAULIC FLUID PRESERVATION

Isocil IG-C is used as a preservative for use in the manufacture and use of high water-based hydraulic fluids and invert emulsion hydraulic fluids typically prepared by emulsifying 40% by volume water in 60% by volume of mineral oil using an oil soluble emulsifying agent.

For maintenance of a non-fouled system, use Isocil IG-C at 108 - 133 fl. ounces (7.3 - 9.0 lbs) per 1000 gallons fluid every 8 weeks. For a noticeably fouled system use an initial dose of 133 - 224 fl. ounces (9.0 - 15.1 lbs.) per 1000 gallons fluid followed by subsequent maintenance dosage. A higher dosage range and / or increased frequency of treatment may be required depending upon rate of dilution of the preservative with makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc. Isocil IG-C must be dispensed into the use-dilution of the hydraulic fluid using a metering pump and uniformly dispersed throughout the system.

#### INDUSTRIAL PROCESS WATER SYSTEMS:

Isocil IG-C is used as a preservative for the control of bacteria and fungi in pretreatment system and process waters used for washing metal or plastic parts and/or paint reduction. Add Isocil IG-C to some other point in the system to insure uniform mixing. Badly fouled systems must be pre-cleaned before treatment is begun. **INITIAL DOSE:** When the system is noticeably fouled, add 2.46 to 7.46 lbs. (37 to 113 fl. ounces) of Isocil IG-C to each 1000 gallons of water in the system. Repeat until control is achieved. **SUBSEQUENT DOSE:** When microbial control is evident, add 1.25 to 1.86 lbs. (19 to 28 fl. ounces) of Isocil IG-C to each 1000 gallons of water. in the system weekly or as needed to maintain control.

PROD. NO. (P)	<b>1008032</b>	
LOT NO. (S)		
WEIGHT. (Q)	<b>0 lb.</b>	<b>0.00 kg.</b>
PROD. NO. (P)		
LOT NO. (S)		

6412A

20110321

ISOCIL® IG-C

1008032

PROD. NO.  
(P)

LOT NO.  
(S)

WEIGHT.  
(Q)

0 lb.

0.00 kg.

FOR HELP IN A CHEMICAL EMERGENCY CALL CHEMTREC 800-424-9300. BEFORE USING CONSULT MATERIAL SAFETY DATA SHEET

6412A

20110321